

Description

Centrecoat Single Pack Epoxy Road Line Paint is a fast drying, high build, epoxy ester based road and line marking paint. Centrecoat Single Pack Road Epoxy is designed to be compatible with most of the surfaces that require line marking paints to be applied. Displays superior durability over chlorinated rubber systems.

Suitable substrates include roads, car parks (concrete or tarmac/weathered blacktop), airfield runways etc. Typical other substrates that accept application are brick, paving, factory floor demarcations and wood.

Benefits

- Fast drying
- Hard wearing
- Chemical resistant
- Interior & exterior compatible
- Meets BS 1436
- Available in strong bold colours

Colours & Finish

Available in Black, White and Yellow. Matt finish.

Preparation

The substrate should be dry and free from dust, oily residues and any other contaminants that might affect adhesion or performance. It is recommended that asphalt and other similar surfaces be allowed to through harden for up to 6 months before painting. Do not apply when either the air or surface temperature is below 5°C.

Application

Apply by lining machine, airless spray, conventional spray, brush or roller. 11-13 thou tip size recommended. Mix thoroughly before use.

Technical Data

- State: Liquid at 20°C
- Viscosity: Viscous
- Volume Solids: Nominally 52%, varying slightly with colour.
- Oxidising: Non oxidising by EC criteria
- Solubility In Water: Not miscible
- Flammability Limits: Lower: 0.8%, Upper: 8.0%
- Flash Point OC: 6
- Relative Density: 1.52
- Wet Film Thickness: 288 µm
- Dry Film Thickness: 150 µm

- Touch Dry: 10 minutes at 20°C
- Recoatable: 1 - 2 hours at 20°C
- Fully Cured: 15 minutes at 20°C

Coverage

Theoretically 3.6 square metres per litre; approximately a 48 metre line at 75mm wide.

PRODUCT DATA SHEET

Centrecoat Single Pack Epoxy Road Line Paint

Storage

Store between 5 - 35°C.

Shelf Life

12 months in original unopened packaging.

Packaging

Available in 5 and 20 Litres