



BLOCKFILL

HIGH BUILD MATT FINISH

- ✱ **EASY APPLICATION**
- ✱ **DURABLE**
- ✱ **WATER BASED**
- ✱ **LOW ODOUR**
- ✱ **QUICK DRY**
- ✱ **BRUSH**
- ✱ **ROLLER**
- ✱ **SPRAY**

MAGNOLIA

WHITE

FOR A SMOOTHER FINISH

INTERIOR - BLOCKS, BRICKS, PLASTER, MASONRY

BLOCKFILL

A high build obliterating water based matt finish suitable for use on internal walls and ceilings. Designed to infill block and brickwork to give a smoother surface where cost of rendering and plastering is not required. Giving one coat coverage on most applications.

Uses: Interior applications, including warehouses, stockrooms, factories etc., over suitably prepared surfaces..

Preparation: Surfaces must be sound, clean and free from wax, grease, oil, dust and loose particles. On existing painted surfaces, remove all loose and flaking paint and thoroughly rub down with abrasive paper. Prime any bare surfaces with an appropriate primer. New plaster and cement should be allowed to dry thoroughly before application. Previously unpainted porous surfaces should be treated with a first coat thinned up to 10% with clean water. Previously unpainted woodwork should be primed with Bedec Acrylic Wood Primer / Undercoat.

Application: Stir thoroughly and check colour before use. Apply by brush, roller or airless spray, applying one or two coats as necessary. Do not overspread.

Coverage: Approximately 6-10 sq. metres per litre, depending on porosity of substrate.

Drying: (At 18° Centigrade and 65% humidity.) Touch dry: 1 hour.

Recoatable: After 4 hours.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Pack sizes: 10 litre & 20 litre

Storage: Protect from frost. Keep out of reach of children.

Colour Range: White and Magnolia. Other colours made on request, subject to economical batch quantities.

Surface Spread of Flame: Tested to BS 476 (Part 7: 1997) – On Plasterboard Rated – Class 1