# Torstrip WDA10 wash down agent

## SS4200005

#### intended uses

For the washing down of previously painted surfaces prior to application of paint systems.

For the washing down recently stripped surfaces prior to application of paint systems.

## product description

A blend of surfactants, detergents and water.

#### product information

Product reference	SS4200005
Theoretical coverage	N/A
Practical coverage	N/A
Appearance/Colour range	Clear
VOC content	0 grams/litre

## application details

Method of application Dilute with water, 1 part Torstrip WDA10 to 10 parts

Apply by brush or cloth.

## storage and handling

Storage	Store in a safe place out of the reach of children
Pack Size	5 and 25 litres
Flash point	Non flammable
Product weight	1.1kilogram/litre
Shelf life	1 year

#### surface preparation

**Previously painted**: Prepare by removing all defective paint back to a solid edge. Repair with a high quality surface filler if necessary. Spot prime filled or bare areas. Remove existing graffiti using Torclean Graffiti Remover Wipe System SS456 or Torclean 'G' Graffiti Remover DM424. Make good any damaged surfaces.

**Stripped**: To be applied following application of Torstrip VSA20 Multi-Layer Paint Stripper, Torstrip HSA20 Multi-Layer Paint Stripper or Torstrip WBS Multi-Layer Paint Stripper.

#### limitations

Rinse off thoroughly with water.

## safety precautions

A copy of the appropriate Health & Safety Data Sheet should be consulted prior to using the product. This can be faxed if urgently required.

A draft Torstrip Method Statement is available and recommended for use.

Minimum precautions for all paints:

- 1. Avoid skin and eye contact i.e. wear gloves, goggles, etc.
- 2. Ensure good ventilation, mechanical if necessary.
- 3. Store and use away from heat and flame.
- 4. Do not eat or smoke in the vicinity of work.
- 5. Wash hands before eating.
- 6. Refer to supply container for additional warning labels.

#### definitions

**Tolerances** All information quoted in this data sheet is subject to

normal manufacturing tolerances.

Practical coverage can vary considerably depending on

method of application, surface roughness, weather

conditions and complexity of the structure.

Pot Life Applies only to two pack products and refers to the

time the mixture remains usable.

VOC Volatile organic compounds

dft Dry film thickness
wft Wet film thickness

#### disclaimer

The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Tor Coatings be liable for consequential or incidental damages.

This document will normally be updated at least every two years. It is the users responsibility to ensure that they have the current copy.

**Updated: September 2010** 

SS420005