

PRODUCT TYPE	Water-borne wood oil for outdoor use.
USAGE	<p>Natural oil for outdoor use for protection of garden deck floors, jetties and wooden garden furniture. Other suitable objects are fences, trellises, doors and stairs. For untreated, heat-treated and press-impregnated wood. Applied on clean, dry wooden surface by brush, sponge or by dipping. Protects wooden surfaces from moisture, soiling and when tinted from UV radiation of the sun. Deminishes cracking of the wooden surface.</p> <p>Not suitable for greenhouses, hotbeds and shelters for livestock.</p>

TECHNICAL DATA

Solids	About 10 % by volume				
Volatile organic compound (VOC)	The product is not included in the EU VOC directive.				
Practical spreading rate	<table><tr><td>Sawn timber</td><td>5 - 8 m²/l</td></tr><tr><td>Planed timber</td><td>8 - 10 m²/l</td></tr></table>	Sawn timber	5 - 8 m ² /l	Planed timber	8 - 10 m ² /l
Sawn timber	5 - 8 m ² /l				
Planed timber	8 - 10 m ² /l				
Density	abt. 1.0 g/ml				
Drying time, +23°C - dust free - dry	<p>after 4 hours after 16 hours</p> <p>Mechanical abrasion on the surface is to be avoided during the first few days. If a renewed treatment is required, it can be applied after about 24 hours.</p> <p>The drying process will be slower in cold and/or damp.</p>				
Thinner, clean up	Water. Wash the equipment immediately after use with detergent and warm water.				
Finish	Is absorbed into the wood and does not usually form any visible film.				
Colours	Clear, brown, grey and translucent colours.				
Weather resistance	For surfaces that are continuously exposed to weathering a renewed treatment is done yearly, or whenever required.				
Packages (availability varies by country)	<p>Clear: 0,9 L, 2,7 L, 9 L</p> <p>Brown: 0,9 L, 2,7 L, 9 L</p> <p>Grey: 0,9 L, 2,7 L, 9 L</p>				

SAFETY MARKINGS

See Safety Data Sheet.
NOTE! Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers. Immersion in water is also recommended.

PTO

DIRECTION FOR USE**Surface preparation**

Clean the surface to be treated. Use RENSA TERRACE deck cleaner on surfaces to be treated, when needed. Rinse the surfaces thoroughly with water and allow to dry. Remove from the surface all loose and poorly adherent old matter and fluffy top layers of the wood. We recommend that untreated wood is primed with wood preservative from WOODEX-series. Remove old paint or varnish layers before the treatment.

Application

Stir well before application. Tinted product must also be stirred during the application, if needed. Applied on the surface 1 - 2 times by brush, sponge or by dipping. The wood oil can be diluted by 10 - 30% to improve the absorption. Depending on the quality of the wood, the treatment is renewed. The possible excess oil is wiped off.

Application conditions

The surface to be treated must be dry. The relative moisture of the wood must be below 20% of the weight of the wood. During the application and drying period the temperature of the ambient air, the surface and the product shall be above +5 °C and the relative air humidity below 80%. Painting in strong sunlight or in moist weather is to be avoided.

STORAGE

Must not freeze.

The information of this data sheet is based on laboratory tests and practical experience. The figures are for guidance only and depend on, for example, colour and gloss. As we have no control over the use and application conditions, we are only responsible for the quality of the product and guarantee that it conforms to our quality control. We accept no liability for any loss or damage resulting from the application of the product contrary to the directions or the intended use. The latest versions of our data sheets, material safety data sheets and system sheets are on our home pages www.teknos.com.



EN_1703_Tuoteseloste.pdf