

ROAD MARKING PAINT, WATER-BORNE

DESCRIPTION	Extremely fast drying water-borne road marking paint formulated with a special acrylic resin.
EXAMPLES OF USE	For marking traffic lines on asphalt and bitumen etc. surfaces.
TECHNICAL DATA	
Coverage	About 1-2 m ² /l, depending on porosity of the surface
Solids volume	About 62 %
Density	About 1.7 kg/l, ISO 2811
Thinner	Water
Application	Spray, brush or roller
Drying time at 23E C relative humidity of the air 50 %	Approximately in 5-15 min. Drying time depends on relative humidity of the air, the temperature of the air, air flow and thinning of paint.
Finish	Matt
Colour Range	White, yellow
Resistance	Weather: Good Wear: Good
Storage and transport	Protect from frost
Packaging	1 l, 10 l

ROAD MARKING PAINT, WATER-BORNE

DIRECTIONS FOR USE

Pretreatment	Remove sand and other loose particles as well as oil and grease from the surface.
Painting conditions	The surface to be painted must be dry, the temperature of the air, paint and surface during application should be at least +5EC, and the relative humidity of the air below 80 %. The surface must not be more than 3EC colder than the air. Do not use the paint when rain is expected.
Painting	Stir well before use. Paint dries extremely fast, but it is possible to make the drying time longer by adding water up to 5 %. Apply by brush, roller or spray. For spray application, spray a thin layer of water on the surface of the paint to prevent a thin layer of dried paint from forming on top of the open container. If you are storing an opened can, spray water on the top of the paint and close the lid well.
Cleaning of tools	Clean tools with water. Tikkurila Pensselipesu (Brush Cleaner) is recommended to be used to remove a bit harden paint. If the sprayer has been used to apply paint requiring thinner, the equipments must be cleaned with appropriate thinner very carefully. A large quantity of water must then be used to rinse out the thinner from the sprayer. Pay special attention to the cleaning of the sprayer filters. Dirty surface can be cleaned on the following day with water, without detergent.
Instructions for treatment	
ENVIRONMENTAL	Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations for hazardous waste.
HEALTH AND SAFETY	Not classified as hazardous for health. Handle with care. Avoid prolonged contact with skin and breathing of spray mist.
CLASSIFICATION according to EC Directive 99/45/EC	A Material Safety Data Sheet is available at request.
TRANSPORT CLASSIFICATION	VAK/ADR -

SNA241095/ENI241095/inh051005/mpy050905/006 6900, -6901