





The VELOPA Model SR (V) Cycle Holder

The Model SR (V) is a freestanding variant of the simplest cycle holder, the Model R. A familiar sight throughout the UK, these holders allow the tyre of the bicycle to be supported. The Model SR (V) is suitable for a single bicycle. The stand is fixed to the ground, in either ragged (for casting into concrete) or flanged (for bolting down) versions and can be spaced at not less than 610mm between holders for cost effective cycle parking.

The practical and durable nature of the VELOPA Model SR (V) cycle holder ensures it has been consistently specified and used since it's introduction in the 1950's.

Shown is the flanged version of the Model SR (V) Cycle Holder.

| U | р | τı | O | n | S |
|---|---|----|---|---|---|
| | | | | | |

| Order Code | Description | Weight |
|-------------|----------------------|--------|
| 138 200 004 | Model SR (V) Ragged | 3.0kg |
| 138 200 005 | Model SR (V) Flanged | 3.0kg |

Accessories & installation parts

| 138 100 994 | M12 Expanding Bolt (3 required per stand. Flanged only) |
|-------------|--|
| 138 100 993 | M12 Foundation Bolt (3 required per stand. Flanged only) |
| 138 100 995 | M12 Rawl Bolt (3 required per stand. Flanged only) |

Product details

Galvanised steel tube and bar. Black polypropylene cap.

Installation & use

Available Ragged (for casting in to ground) or Flanged for bolting down.

Ragged version must be set into a suitable concrete foundation of at least 300mm cube. Stand to be set approx 490mm from top of holder to ground level.

Flanged version must be bolted down to a suitable concrete surface and requires three M12 bolts.

This product is guaranteed for 12 months (if installed and used correctly).



www.velopa.co.uk +44 (0)1788 550556

