



The AUTOPA GFC 3000 Removable Ornamental Bollard

With a practical and classic appearance the GFC 3000 Ornamental Mild Steel Bollard is suitable for various locations and purposes.

The main post is constructed from mild steel, galvanised to ensure its longevity. Caps and rings of cast iron are welded on to the steel body to complete the design.

The bollards are available in a galvanised and a galvanised and coated finish. RAL numbers must be specified at time of order. Supplied ragged as standard, flanged and removable options are available. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Lift Out Weight	Weight
138 120 067	Removable (Galvanised)	13.2kg	17.9kg
138 120 069	Removable (Galvanised and Black)	13.2kg	17.9kg
138 120 068	Removable (Galvanised and Colour)	13.2kg	17.9kg

Accessories and installation parts

138 100 906	40mm Brass Padlock with 2 Keys (Random Key)
138 100 907	40mm Brass Padlock with 2 Keys (Identical Key)
138 150 206	Additional Socket

Product details

900mm above ground
267mm below ground
114mm diameter tube
3mm wall thickness

Installation & use

Removable bollards require an excavated hole of at least 300mm square and 500mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).