



The AUTOPA P Series Automatic Rising Arm Barrier

With fast operating speeds, the AUTOPA P Series Automatic Arm Barrier is ideal for controlling access to car parks and commercial sites.

Designed for entrances up to 5 metres wide, the barrier is compatible with a variety of different control mechanisms including remote controls, keypads and swipe cards. Manufactured from high quality aluminium, this system has an IP54 protection rating.

Manual Override Handles are included for power failure or manual operation. Additional Manual Override Switches can be added to programme the barrier allowing it to remain in the open or closed positions.

Product Range		
Order Code	Description	Weight
138 105 025	2.5 metres Automatic Arm Barrier (boom is included)	57.0 kg
138 105 030	3.0 metres Automatic Arm Barrier (boom is included)	58.0 kg
138 105 035	3.5 metres Automatic Arm Barrier (boom is included)	58.0 kg
138 105 040	4.0 metres Automatic Arm Barrier (boom is included)	59.0 kg
138 105 050	5.0 metres Automatic Arm Barrier (boom is included)	60.0 kg
(All sizes are measured from the front of the Barrier cabinet to the end of the Barrier Arm)		
	Accessories and installation parts	
138 105 931	Fixed Catch Post	
138 105 025	2.5 metres Replacement Boom	3.8 kg
138 105 030	3.0 metres Replacement Boom	4.5 kg
138 105 035	3.5 metres Replacement Boom	5.0 kg
138 105 040	4.0 metres Replacement Boom	5.8 kg
138 105 050	5.0 metres Replacement Boom	10.0 kg
All versions can be colour coated upon request (please specify BS/RAL numbers) Standard blue (RAL 5012), white (RAL 9010)		
Product details		

1100mm (approx.) overall height. Width 360mm, Length 300mm (approx) Boom lengths from 2.5m - 5.0m Operating Speed 0.9-3.8 seconds

Installation & use

All Automatic Rising Arm Barrier Systems must only be installed by experienced and trained personnel. The barrier cabinet requires bolting to a suitable concrete foundation of at least 800mm deep and approximately 550mm². Provision for control and power cabling should be made through plastic ducting. This product is guaranteed for 12 months (if installed and used correctly).





