



### The AUTOPA Double Fixed Height Restrictor

The AUTOPA Double Fixed Height Restrictor limits access to high sided vehicles and is perfect for use on commercial and industrial sites. The height restrictor has a standard clearance of 2.05m and spans two carriageways, preventing vehicles from circumventing the access control measures in place.

Manufactured from galvanised mild steel, the body of the height restrictor is available ragged or flanged and is coated red as standard. Other colours are available upon request (please state BS/RAL numbers at time of order). To alert drivers of the oncoming obstruction knocking bars and maximum height warning signs can be added as required.

### Options

Order Code	Description	Weight
138 106 600	6m Galvanised and Colour (Flanged)	125.0kg
138 106 602	8m Galvanised and Colour (Flanged)	134.0kg
138 106 604	10m Galvanised and Colour (Flanged)	143.0kg
138 106 606	12m Galvanised and Colour (Flanged)	156.0kg
138 106 608	14m Galvanised and Colour (Flanged)	165.0kg
<b>Accessories &amp; installation parts</b>		
138 500 725	3m Knocking Bar	
138 500 730	4m Knocking Bar	
138 500 735	5m Knocking Bar	
138 500 740	6m Knocking Bar	
138 106 287	Maximum Height Warning Sign	
138 100 991	M16 Expanding Bolt	

### Product details

Knocking Bar: 48mm diameter tube  
Standard Clearance: 2.05m  
600mm below ground (ragged only)

### Installation & use

Flanged Height Restrictors require bolting down to a suitable concrete surface (not less than 600mm<sup>3</sup>) by means of four M16 bolts per leg.  
Ragged Height Restrictors require an excavated hole of at least 600mm<sup>3</sup> for casting into concrete per leg.  
It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.  
This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP

