







The VELOPA Stratford Cycle Shelter

The Stratford shelter is a free-standing, single sided cycle shelter designed for on site assembly, constructed from galvanised steel and PET sheet. The frame is made from 50mm galvanised mild steel square tube. The roof is 4mm clear sheet.

The Stratford shelter provides a core element of a compliant cyle parking solution.

| Options | | |
|-------------|---|---------|
| Order Code | Description | Weight |
| 138 204 020 | 2m Main Bay | 140.0kg |
| 138 204 030 | 3m Main Bay | 191.0kg |
| 138 204 040 | 4m Main Bay | 258.0kg |
| 138 204 048 | 5m Main Bay | 292.0kg |
| 138 204 025 | 2m Extension Bay | 140.0kg |
| 138 204 035 | 3m Extension Bay | 163.0kg |
| 138 204 045 | 4m Extension Bay | 213.0kg |
| 138 204 049 | 5m Extension Bay | 265.0kg |
| | Accessories & installation parts | |
| 138 101 010 | Pack of 16 16mm Expanding anchor bolts (for fixing 3-4m) | |
| 138 101 012 | Pack of 24 16mm Expanding anchor bolts (for fixing 6-8m) | |
| 138 101 016 | Pack of 32 16mm Expanding anchor bolts (for fixing 9-10m) | |

Product details

2,150mm (Height).
2,530mm (Depth).
3,000mm-10,000mm (Length).
50mm square galvanised steel tube.
4mm clear PET sheet.
Other options are available; please ask.

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 450mm x 450mm x 400mm) by means of 12mm anchor bolts.

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

