



The VELOPA Cambourne Cycle Shelter

The Cambourne shelter is a free-standing, single sided cycle shelter designed for on site assembly, constructed from galvanised steel and PET sheet. The frame is made entirely from galvanised mild steel; the uprights are 76mm round tube and the roof frame is 50mm square tube. The roof is 4mm clear sheet.

A variation of the classic VELOPA Cambridge style shelter, the Cambourne shelter provides a core element of a BREEAM compliant cycle parking solution.

| Options | | |
|-------------|----------------------------|---------|
| Order Code | Description | Weight |
| 138 204 261 | 2m Main Bay (Flanged) | 208.0kg |
| 138 204 251 | 3m Main Bay (Flanged) | 253.0kg |
| 138 204 254 | 4m Main Bay (Flanged) | 298.0kg |
| 138 204 263 | 5m Main Bay (Flanged) | 344.0kg |
| | | |
| 138 204 262 | 2m Extension Bay (Flanged) | 142.0kg |
| 138 204 252 | 3m Extension Bay (Flanged) | 187.0kg |
| 138 204 255 | 4m Extension Bay (Flanged) | 232.0kg |
| 138 204 264 | 5m Extension Bay (Flanged) | 278.0kg |
| | | |

Accessories & installation parts

| 138 101 010 | Pack of 16 16mm Expanding anchor bolts (for fixing 3-4m) |
|-------------|---|
| 138 101 012 | Pack of 24 16mm Expanding anchor bolts (for fixing 6-8m) |
| 138 101 014 | Pack of 32 16mm Expanding anchor bolts (for fixing 9-10m) |

Product details

Front Height: 2,150mm Rear Height: 1,350mm Depth: 2,700mm Width: 2m-10m 76mm round and 50mm square galvanised steel tube 4mm clear PET sheet

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 1,600mm x 500mm x 400mm) by means of eight 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).







AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP