







The VELOPA Fenstanton Cycle Shelter

The Fenstanton shelter is a free-standing, single sided cycle shelter designed for on site assembly, constructed from galvanised steel and PET sheet. The frame is made entirely from galvanised mild steel; the uprights are 76mm round tube and the roof frame is 50mm square tube. The roof is 4mm clear sheet.

A variation of the classic VELOPA Cambridge style shelter, the Fenstanton shelter provides a core element of a compliant cycle parking solution.

Options

•		
Order Code	Description	Weight
138 204 211	2m Main Bay (Flanged)	208.0kg
138 204 201	3m Main Bay (Flanged)	253.0kg
138 204 204	4m Main Bay (Flanged)	299.0kg
138 204 213	5m Main Bay (Flanged)	344.0kg
138 204 212	2m Extension Bay (Flanged)	142.0kg
138 204 202	3m Extension Bay (Flanged)	187.0kg
138 204 205	4m Extension Bay (Flanged)	233.0kg
138 204 214	5m Extension Bay (Flanged)	278.0kg
	Accessories & installation parts	
138 101 010	Pack of 16 16mm Expanding anchor bolts (for fixing 3-5m)	
138 101 012	Pack of 24 16mm Expanding anchor bolts (for fixing 6-8m)	
138 101 014	Pack of 32 16mm Expanding anchor bolts (for fixing 9-10m)	

Product details

Front Height: 2,300mm Rear Height: 1,450mm Depth: 2,750mm Width: 2m-10m

76mm round and 50mm square galvanised steel tube

4mm clear PET sheet

Installation & use

Each shelter leg requires bolting down to a suitable concrete surface (not less than 1,600mm x 500mm x 400mm) by means of eight 16mm anchor bolts.

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes.

On-site assembly requires construction skill.

This product is guaranteed for 12 months (if installed and used correctly).





