







The AUTOPA Trinity Stainless Fixed Post

The AUTOPA Trinity Stainless Steel Fixed Post is 900mm tall and is ideal for all modern developments where the clean and elegant appearance of stainless steel is desired.

The Posts are available in both Ragged (for casting in to concrete) and flanged (for bolting down) in a wide range of sizes; from 60mm to 204mm outside diameter.

_					
\mathbf{c}	n	+i	^	n	c
v	IJ	u	0	•	-

Order Code	Description	Weight
138 125 060	60mm (Ragged)	3.7kg
138 125 059	60mm (Flanged)	3.1kg
138 125 075	76mm (Ragged)	4.7kg
138 125 074	76mm (Flanged)	4.0kg
138 125 090	89mm (Ragged)	5.5kg
138 125 087	89mm (Flanged)	4.7kg
138 125 104	101mm (Ragged)	6.3kg
138 125 110	101mm (Flanged)	5.3kg
138 125 117	114mm (Ragged)	7.1kg
138 125 121	114mm (Flanged)	5.9kg
138 125 123	129mm (Ragged)	8.0kg
138 125 124	129mm (Flanged)	6.1kg
138 125 142	139mm (Ragged)	8.7kg
138 125 143	139mm (Flanged)	7.7kg
138 125 157	154mm (Ragged)	9.7kg
138 125 155	154mm (Flanged)	8.7kg
138 125 169	168mm (Ragged)	10.6kg
138 125 174	168mm (Flanged)	9.4kg
138 125 201	204mm (Ragged)	13.0kg
138 125 199	204mm (Flanged)	11.5kg

Product details

900mm above ground 300mm below ground (ragged only)

Installation & use

Ragged posts require an excavated hole of approximately 300mm^3 for installation. 2mm wall thickness Flanged posts up to 127mm in diameter require bolting down to a suitable concrete surface (no less then 300mm³) using four M12 bolts. Flanged posts with a diameter of more than 127mm require bolting down to a suitable concrete surface (no less then 300mm³) using four M16 bolts. AUTOPA recommends that posts are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).





www.autopa.co.uk