



**The AUTOPA Square RetractaPost 500**

The Square RetractaPost 500 is an effective means of preventing unauthorised vehicle access. When not in use, the post retracts into its integrated socket and is covered by the integral lid. The post can be raised to restrict vehicle access and secured with a padlock (available separately).

Simple and unobtrusive, the Square RetractaPost 500 is perfect for use on commercial car parks, vehicle forecourts and domestic driveways. The Square RetractaPost 500 is manufactured from galvanised mild steel and can be colour coated to any standard BS/RAL number (please state codes at time of order).

**Options**

Order Code	Description	Lift-up Weight	Weight
138 130 371	60mm x 60mm (Galvanised)	4.0kg	13.2kg
138 130 376	60mm x 60mm (Galvanised and Colour)	4.0kg	13.2kg
138 130 411	70mm x 70mm (Galvanised)	4.7kg	20.5kg
138 130 414	70mm x 70mm (Galvanised and Colour)	4.7kg	20.5kg

**Accessories & installation parts**

- 138 100 906 40mm Brass Padlock with 2 keys (Random Key)
- 138 100 907 40mm Brass Padlock with 2 keys (Identical Key)

**Product details**

- 500mm above ground (when raised)
- 800mm below ground
- 3mm wall thickness

**Installation & use**

AUTOPA recommends that posts are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. An excavated hole of at least 800mm deep and 300mm<sup>2</sup> is required for installation. Provision for suitable drainage must be made at the bottom of the hole. The uppermost 300 - 400mm must be set into concrete. The lid of the post should be no more than 10mm above finished ground level. Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar. This product is guaranteed for 12 months (if installed and used correctly).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP

