



### **The AUTOPA RetractaPost 745 FB**

The RetractaPost FB is a simple, cost effective, yet highly effective way to prevent unwanted vehicle access. The RetractaPost FB is raised and lowered vertically. When lowered the post is fully below ground and covered using the integral lid. The post is padlockable (padlock not supplied) in the raised position by first rotating the post 45° and then attaching the padlock between the post to the lid.

The RetractaPost FB is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways. The post is supplied without a padlock thus allowing the user to specify which FB padlock is required.

### **Product Range**

<b>Order Code</b>	<b>Description</b>	<b>Lift-up Weight</b>	<b>Weight</b>
138 130 400FB	90mm (Galvanised)	6.6kg	27.0kg
138 130 403FB	90mm (Galvanised and Black)	6.6kg	27.0kg
138 130 405BFB	90mm (Galvanised and Yellow)	6.6kg	27.0kg
138 130 405FB	90mm (Galvanised and Colour)	6.6kg	27.0kg
138 130 419	90mm (Stainless)	6.4kg	26.8kg

#### **Accessories & installation parts**

138 100 920	FB1 Fire Brigade Padlock (Excludes key)
138 100 924	FB14 Fire Brigade Padlock (Excludes key)
138 100 921	FB1 Fire Brigade Padlock Key
138 100 925	FB14 Fire Brigade Padlock Key
138 810 598	AUTOPA Red & White Chevron Reflective Label

### **Product details**

745mm Tall (When raised).

1010mm Below Ground.

Galvanised Steel or Stainless Steel finish.

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.

An excavated hole of approximately 1,200mm deep and 300mm diameter is required for installation.

Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete.

The lid of the post should be no more than 10mm above finished ground level.

This product is guaranteed for 12 months (*if installed and used correctly*).

### **Installation & use**