




Door Guard Galvanised










AUTOPA Door Guards are designed to protect walls from being damaged by swinging doors. An integrated rubber stopper acts as a shock absorber, preventing the door from hitting the steel frame. Ideal for commercial and industrial sites, they are suitable for internal and external use and can be installed either individually or in pairs.

Extremely durable, AUTOPA's Door Stops are manufactured from galvanised mild steel and available with flange plates for bolting down or extended legs for casting into concrete. Colour coated finishes are also available (please state BS/RAL number at time of order). To maximise visibility, infill plates can be added to the Door Stop (solid steel plate as standard, other materials are available upon request).



Part Number	<u>Description</u>	Weight (kg)
138 206 005	Door Guard (Concrete In)	11.0kg
138 206 001	Door Guard (Bolt Down)	11.0kg
138 206 015	Door Guard with steel infil panel (Concrete In)	25.0kg
138 206 011	Door Guard with steel infil panel (Bolt Down)	25.0kg
138 206025	Door Guard with perforated steel infil panel (Concrete In)	23.3kg
138 206 021	Door Guard with perforated steel infil panel (Bolt Down)	25.0kg
138 100 994	M12 Expanding Bolt (6 required per door guard)	
138 100 993	M12 Foundation Bolt (6 required per door guard)	
138 100 995	M12 Rawl Bolt (6 required per door guard)	

Product details

- 1100mm Tall
- 48mm diameter tube
- 3mm wall thickness (galvanised)

- 800mm wide
- Concrete In version 300mm below ground
- Rubber buffer can be positioned on either side

Installation & use

When fully open door stops should sit parallel to the door.

Ensure that door handles do not make contact with the door stop when opening to prevent damage.

Bolt down Door Guards require bolting to to a suitable concrete surface (no less than 300mm3 per leg) by means of six M12 bolts.

Concrete In Door Guards require an excavated hole (no less thatn 350mm3 deep per leg) for installation.

This product is guaranteed for 12 months (if installed and used correctly).

www.autopa.co.uk +44 (0)1788 550556



