



The AUTOPA GFC 2R Ornamental Bollard

The GFC 2R Ornamental Mild Steel Bollard from AUTOPA is suitable for a wide range of locations and purposes. The main post is constructed using mild steel, galvanised to ensure its longevity. Two cast iron rings are welded onto the steel tube to complete the design.

The bollards are available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order. Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Weight
138 120 151	Ragged (Galvanised)	12.9kg
138 120 152	Ragged (Galvanised and Black)	12.9kg
138 120 153	Ragged (Galvanised and Colour)	12.9kg
138 120 154	Flanged (Galvanised)	10.8kg
138 120 155	Flanged (Galvanised and Black)	10.8kg
138 120 156	Flanged (Galvanised and Colour)	10.8kg

Accessories and installation parts

138 100 994	M12 Expanding Bolt (3 required per bollard)
-------------	---

Product details

1000mm above ground
400 below ground (ragged only)
114mm diameter tube
3mm wall thickness

Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm³) by means of three M12 bolts.
Ragged bollards require a hole of at least 400mm deep for casting into concrete.
AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.
This product is guaranteed for 12 months (*if installed and used correctly*).

www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103