



Hammerite Special Metal Primer

About this product

A water-based primer to promote adhesion to stainless steel and non-ferrous metals including galvanised, aluminium, chrome, brass and copper

Key Benefits

- ✓ Provides a smooth even finish for ideal topcoat adhesion.
- ✓ Only one coat required
- ✓ Quick drying
- ✓ Can be used inside & outside
- ✓ Water-based

Special Features

- ✓ Quick and easy to use
- ✓ Topcoat can be applied after 1-2 hours

Technical Information

Touch dry	30 minutes
Recoatable	2 hours
Coverage	16m ² per litre

Product Information

Typical Use

All surfaces must be clean and dry. Remove loose rust, flaking paint and the gloss from old paintwork by wire brushing and/or rubbing down with coarse abrasive paper. Treat any rusted patches with

Hammerite Kurust. Degrease thoroughly with a detergent solution then rinse thoroughly with clean water and allow to dry

Composition

Water-based

Key Benefits

Provides a smooth even finish for ideal topcoat adhesion., Only one coat required, Quick drying, Can be used inside & outside, Water-based

Pack size

250ML, 500ML

System Information

Stir paint thoroughly. Do not apply when there is a risk of rain, frost or if the temperature falls below 5°C. Hammerite Special Metals Primer is touch dry in 30 minutes (depending on weather conditions) and can be overcoated after only 2 hours. Hammerite Special Metals Primer can be overcoated with most paints.

Application Method

Stir paint thoroughly. Do not apply when there is a risk of rain, frost or if the temperature falls below 5°C. Hammerite Special Metals Primer is touch dry in 30 minutes (depending on weather conditions) and can be overcoated after only 2 hours. Hammerite Special Metals Primer can be overcoated with most paints.