

Integral Concrete and Mortar Waterproofer

ADOPRUFÉ is a concentrated liquid solution of waterproofing chemicals.

When added to a concrete mix it firstly reacts physically to improve wetting properties and ensure uniform dispersion and full hydration of all cement particles.

Secondly it reacts chemically to deposit throughout the mix in all pores and capillaries an insoluble water repellent metallic stearate. The resulting concrete is not only more dense and stronger but is also water proof to withstand extremely high water pressures

Advantages

- ADOPRUFÉ added to a concrete or cement rendering mix, makes the concrete or render:
- Easier to place and compact
- Denser and stronger
- Waterproof to withstand extremely high water pressures
- More resistant to attack from aggressive waters

Application

The standard usage rate is 500ml ADOPRUFÉ to 50 kilos of Portland Cement added to the gauging water or the pre-wetted mix.

As a guide for estimating purposes the quantities of ADOPRUFÉ required to waterproof 1 cubic metre of concrete are as follows:

1 : 2 : 4 Mix – 3 litres ADOPRUFÉ

1 : 1.5 : 3 Mix – 4 litres ADOPRUFÉ

1 litre ADOPRUFÉ will waterproof approximately 16 sq. metres of 12mm thick rendering composed of 1 part cement to 3 parts sand.

Concrete designed to withstand hydrostatic pressure should never contain less than 300 kilos of cement per cubic metre.

Storage

ADOPRUFÉ should be protected from frost. Containers must be kept sealed after use. The product may require mild agitation before use if stored for more than 6 months.

Shelf Life

If stored in accordance as per the instructions above, shelf life is in excess of 12 months.

Specification

ADOPRUFÉ is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

Health and Safety

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged in common with the use of all chemicals. Where contact with skin occurs, the material should be removed with soap and water. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists, medical attention should be sought without delay.

See Safety Data Sheet for further information.