



Technical Specification

Bitumen Based Roofing Felt Adhesive Compound

Cold applied bituminous adhesive for bonding successive layers of roofing felt, also suitable for use as a lap cement and gritting adhesive.

For fixing roofing felt to roofing felt, concrete, metal and similar surfaces.

Ready to use

Contains bitumen/solvent blend

Suitable for binding mineral chippings to bituminous surfaces

Apply on a clean and dry surface for better results

Easy to apply with a brush, squeegee or mop

Ideal for bonding successive layers of roofing felt to wood, metal, asphalt and concrete

Application

All surfaces must be clean, dry and free from loose material

Dusty and porous surfaces should be primed with Bitumen Primer

Stir before and occasionally during use

As Roofing Felt Adhesive: Apply by brush or broom and when tacky (after approx. 15 minutes), roll roofing felt into position and press down firmly. When the adhesive is nearly dry (after approx. 6 hours) inspect the felt, any areas not adhered should be firmly pressed or rolled down.

NOTE: It is not advisable to stick roofing felt directly to timber. When fixing felt to boarded roofs, the first layer of felt should be nailed.

As Lap Cement: When nailing felt to wooden pitched roofs it is essential to seal laps to ensure they are watertight.

Working up the roof, position first sheet allowing a 40mm overlap to eaves and gables.

Fix by nailing at 600mm (2 ft.) centres, 20mm in from edge.

Carefully bend felt over gables and eaves and fix by nailing at 50mm centres.

Position second and successive sheets allowing a minimum 75mm overlap on lower sheets and fix in a similar way.

Hold back lower edge, apply to lap and press back into position and nail at 50mm centres along the lap.

As a Gritting Adhesive: Roofing felt adhesive can be used for fixing grit or chippings over asphalt or roofing felt to provide a solar reflective coating.

Coverage

Coverage as a Roofing Felt Adhesive: 0.25 m² - 2 m² per litre

Coverage as a lap adhesive: 20 linear metres @75mm per litre

Storage

Adomast Felt Adhesive is available in 5 and 25 litre containers. After use replace lid firmly and shake to ensure an airtight seal.

Shelf Life

Storage Life: Indefinite in undamaged, tightly sealed containers.

Containers must be kept sealed and stored away from sources of heat and ignition.

Specification

Adocoat Felt Adhesive is supplied by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department.

Health and Safety

Care should be taken to avoid splashes entering eyes. Contact with skin should be avoided and hands washed thoroughly in the event of accidental contact. ADOCOAT Felt Adhesive should not be ingested. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists medical attention should be sought without delay.

See separate Safety Data Sheet for further information.