



Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C8mm would have approximate adjustment range of +33mm - 66mm.



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	PIN	TH Dia.	C	T	MIN L	MAX L	ADJUSTMENT RANGE
C8-3mm	3mm	6.678	7.42	6mm	6.3mm	12.5mm	6.2mm	125mm	195mm	70mm
C8-4mm	4mm	18.54	13.2	8mm	7.9mm	17mm	7.9mm	150mm	228mm	78mm
C8-5DS	5mm	18.54	20.6	8mm	7.9mm	17mm	7.9mm	153mm	231mm	78mm
C8-5mm	5mm	26.73	20.6	9.5mm	9.1mm	19mm	9.9mm	184mm	284mm	100mm
C8-6DS	6mm	34.02	29.7	9.5mm	9.1mm	19mm	9.9mm	187mm	287mm	100mm
C8-6mm	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm	202mm	310mm	108mm
C8-7mm	7mm	44.46	37.8	12mm	14.3mm	25mm	12.7mm	236mm	368mm	132mm
C8-8DS	8mm	44.46	49.4	12mm	16.0mm	25mm	12.7mm	239mm	371mm	132mm
C8-8mm	8mm	44.46	49.4	14mm	16.0mm	28mm	15.8mm	300mm	455mm	155mm
C8-10mm	10mm	69.48	77.2	16mm	18.0mm	32mm	15.8mm	312mm	468mm	156mm
C8-12mm	12mm	93.6	104	19mm	21.4mm	38mm	17.8mm	361mm	532mm	171mm
C8-14mm	14mm	125.1	139	22mm	25.0mm	45mm	22mm	403mm	600mm	197mm
C8-16mm	16mm	162.9	181	25.4mm	28.2mm	50mm	22mm	472mm	711mm	239mm
C8-19mm	19mm	209.7	233	28mm	34.5mm	58mm	28.2mm	531mm	801mm	270mm
C8-22mm	22mm	269.1	299	32mm	40.3mm	64mm	31.8mm	575mm	859mm	284mm
C8-26mm	26mm	374.4	416	35mm	45.9mm	70mm	34.9mm	655mm	979mm	324mm

Compression/swageless terminals can be assembled on site safely and securely without the need for special tools.

Compression terminals are suited to applications where the exact final length are to determine or where the cable is designed to pass through intermediate steelwork such as balustrade posts or Solar shading screens.