



PETERSEN
STRUCTURAL RIGGING LTD

SYSTEM C1 SWAGE STUDS

Can be supplied with either RH threads both ends or LH and RH thread combination depending upon the application. Imperial Unf threads are also available.

Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C5-5mm would have approximate adjustment range of +33mm - 66mm.



PRODUCT CODE	W DIAMETER	CBL(KN) MBL *9	MBL	THREAD DIAMETER	OD	STUD LENGTH	THREAD LENGTH EACH END
C1-3mm	3mm	6.678	7.42	M6	6.3mm	97mm	47mm
C1-4mm	4mm	11.88	13.2	M6	7.5mm	105mm	47mm
C1-4mm M8	4mm	11.88	13.2	M8	7.5mm	113mm	54mm
C1-5mm	5mm	18.54	20.6	M8	9.1mm	122mm	54mm
C1-5mm M10	5mm	18.54	20.6	M10	9.1mm	135mm	68mm
C1-6mm	6mm	26.73	29.7	M10	12.5mm	154mm	75mm
C1-6mm M12	6mm	26.73	29.7	M12	12.5mm	170mm	90mm
C1-7mm	7mm	34.02	37.8	M12	14.3mm	177mm	90mm
C1-8mm	8mm	44.46	49.4	M12	16.0mm	190mm	90mm
C1-8mm M16	8mm	44.46	49.4	M16	16.0mm	201mm	100mm
C1-10mm	10mm	69.48	77.2	M16	18.0mm	223mm	100mm
C1-12mm	12mm	93.6	104	M20	21.4mm	277mm	120mm
C1-14mm	14mm	125.1	139	M22	25.0mm	325mm	140mm
C1-16mm	16mm	162.9	181	M27	28.2mm	371mm	160mm

P = Pin diameter. C = Fork depth from pin centre. T = Throat width

