



Adjustment range is the maximum range of adjustment. Cable lengths will be calculated with 1/3rd engagement allowing 2/3rd for shortening the length. E.g. C7-5mm would have approximate adjustment range of +33mm - 66mm.



PRODUCT CODE	W Dia	CBL(KN) MBL *9	MBL	PIN	TH Dia.	C	T	MIN L	MAX L	ADJUSTMENT RANGE
C7-3mm	3mm	6.678	7.42	6mm	6.3mm	12.5mm	6.2mm	116mm	186mm	70mm
C7-4mm	4mm	18.54	13.2	8mm	7.9mm	17mm	7.9mm	136mm	214mm	78mm
C7-5DS	5mm	18.54	20.6	8mm	7.9mm	17mm	7.9mm	142mm	220mm	78mm
C7-5mm	5mm	26.73	20.6	9.5mm	9.1mm	19mm	9.9mm	167mm	267mm	100mm
C7-6DS	6mm	34.02	29.7	9.5mm	9.1mm	19mm	9.9mm	173mm	273mm	100mm
C7-6mm	6mm	26.73	29.7	11mm	12.5mm	22mm	10.9mm	182mm	290mm	108mm
C7-7mm	7mm	44.46	37.8	12mm	14.3mm	25mm	12.7mm	214mm	346mm	132mm
C7-8DS	8mm	44.46	49.4	12mm	16.0mm	25mm	12.7mm	220mm	352mm	132mm
C7-8mm	8mm	44.46	49.4	14mm	16.0mm	28mm	15.8mm	274mm	430mm	155mm
C7-10mm	10mm	69.48	77.2	16mm	18.0mm	32mm	15.8mm	278mm	434mm	156mm
C7-12mm	12mm	93.6	104	19mm	21.4mm	38mm	17.8mm	322mm	493mm	171mm
C7-14mm	14mm	125.1	139	22mm	25.0mm	45mm	22mm	362mm	559mm	197mm
C7-16mm	16mm	162.9	181	25.4mm	28.2mm	50mm	22mm	426mm	665mm	239mm
C7-19mm	19mm	209.7	233	28mm	34.5mm	58mm	28.2mm	476mm	746mm	270mm
C7-22	22mm	269.1	299	32mm	40.3mm	64mm	31.8mm	515mm	800mm	284mm
C7-26	26mm	374.4	416	35mm	45.9mm	70mm	34.9mm	594mm	918mm	324mm