




altro

the future is safer with altro


Xtreme heavy
duty solution,
with NEW R11

Altro is the first safety
flooring manufacturer to
recycle traditional safety
flooring in-house


Altro Designer 25/D25 - R10




Storm D25903
WR82 / A1M82 / LRV 16



Fog D25153
WR81 / A1M81 / LRV 27




Twilight D25910
WR39 / A1M34 / LRV 8




Midnight D25421
WR72 / A1M72 / LRV 11




Jet D2501
WR100 / A1M100 / LRV 6




Skyline D25332
WR52 / A1M52 / LRV 25



Biscuit D25904
WR146 / A1M20 / LRV 30



Bone D25215
WR20 / A1M20 / LRV 37




Rust D25907
WR150 / A1M238 / LRV 10

Altro Legend Range

Altro Classic 25/X25 - R11 Altro Legend Range


Altro Classic 25/X25 is also available in Anvil, as shown in Altro Atlas 40/X40*.




Pewter Grey*
X2539R11/X4039
WR81 / A1M81 / LRV 26



Blue
X2541R11
WR71 / A1M71 / LRV 20



Mushroom*
X2542R11/X4042
WR24 / A1M27 / LRV 32



Quarry Red *
X2560R11/X4060
WR42 / A1M42 / LRV 13



Walnut*
X2586R11/X4086
WR62 / A1M62 / LRV 10

Altro Atlas 40/X40 - R10

Available in Anvil and the 4 colours shown in Classic 25/X25*.



Anvil*
X4094/X2594R11
WR101 / A1M72 / LRV 11

A+ BRE Generic Green Guide
Rating for Safety Flooring, full
details available at
www.thegreenguide.org.uk

Light Reflectance Values measured in accordance with BS8493:2008. Exact material match with samples cannot be guaranteed.
No podemos garantizar que el material del suelo de seguridad coincida exactamente con el de las muestras. Eine exakte
Übereinstimmung des Materials mit Mustern kann nicht garantiert werden.

Codes: **WR** = weld rod, **A1M** = mastic, **LRV** = light reflectance value.
Códigos: **WR** = Cordón de soldadura, **A1M** = Mástique, **LRV** = Valor de Reflectancia de la Luz.
Abkürzungen: **WR** = Schweißschnüre, **A1M** = Altro Mastic Dichtmasse, **LRV** = Lichtreflexionswert

For decorative PUR alternative,
see Altro Unity™ 25



Flooring Type Tipo de pavimento Belagsart		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use Areas de uso Einsatzbereiche		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance* Resistencia al deslizamiento* Rutschsicherheit*		TRRL EN 13845 EN 13893 DIN 51130	D25 X25 X40
Thickness Espesor Total Gesamtdicke		EN 428	2.5 mm 2.5 mm 4 mm
Wear Layer Capa de uso Nutzschicht		EN 429	2.5 mm 2.5 mm 4 mm
Weight Peso Flächengewicht		EN 430	2.9 kg/m² 2.9 kg/m² 4.5 kg/m²
Roll Dimensions Dimensiones del rollo Rollenabmessungen		EN 426	2 m x 20 m = 40 m² 2 m x 20 m = 40 m² 2 m x 12.5 m = 25 m²
Sound Insulation Aislamiento acústico Trittschal		ISO 140-8	7 dB 5 dB 7 dB
Flexibility Flexibilidad Flexibilität		EN 435	Pass Conforme bestanden
Light Fastness Resistencia a la luz Lichtechtheit		EN 20105-B02	≥6
Wear Resistance Abrasión Verschleißverhalten		EN 13845	≤10% particles lost over 50000 Cycles ≤10% de las partículas perdidas en 50.000 ciclos ≤10% Parkitel werden über 50000 Umdrehungen verloren
Indentation Punzonamiento Resteindruck		EN 433	≤ 0.10mm
Fire Performance Reacción al fuego Brandverhalten		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m² Pass Clase Bfl-s1 ≥8kW/m² Conforme Klasse Bfl-s1 ≥8kW/m² bestanden
Chemical Resistance** Resistencia a los productos químicos** Chemikalieneinwirkung**		EN 423	Good Buena beständig
Castor Chair Abrasion Huellas de sillas de ruedas Stuhlrollenbeanspruchung		EN 425	Pass Conforme geeignet
Under floor heating Calefacción por el suelo Fußbodenheizung		EN 12667	Suitable Apto geeignet
Electrical Behaviours Características eléctricas Elektrisches Verhalten		EN 1815	≤ 2kV Antistatic ≤ 2kV Antiestáticas ≤ 2kV antistatisch
VOC Emissions Emisiones de VOC VOC Emissionen		prEN 15052 Section 01350 AgBB/DiBt	Low/Pass/Approved Baja/Conforme/Aprobado gering/geeignet/zugelassen

These products have never contained phthalate plasticisers.

* We recommend the use of Altro Aquarius™ for combined shoe and barefoot use in wet and dry areas such as hospital bathrooms and

Altro Marine™ 20 / T20 for barefoot use in wet areas such as swimming pool surrounds.

** Caution Ketone/Aromatic Solvents. Please contact Altro for further technical advice regarding staining and chemical resistance. Certain chemicals may cause staining of vinyl. Traffic stain can be caused by oil residue, certain cleaning agents, asphalt and anti-oxidants in some types of rubber.

Installation and Maintenance

All Installations in accordance with Altro safety flooring instructions and Local Codes of Practice. Please refer to Altro Cleaning Card for maintenance advice. Failure to install and maintain Altro flooring in accordance with installation instructions can affect its performance and slip resistance.

Floors should be protected from other trades and thoroughly cleaned before handover.

All information is correct at the time of print and is subject to change without prior notice.

Visit us at www.altro.com for more information and updates.



Altro Limited a company certified by SGS to ISO 9001 and ISO 14001.



For further technical information please visit www.altro.com

Si desea obtener más información técnica, visite www.altroscandess.com

Weitere technische Informationen finden Sie auf unserer Website www.altro.de

EN13845