

Global leaders in flexible couplings,  
drainage & plumbing systems

# Pipe Seals

## Gully Seal



Flexseal universal gully seals are manufactured from EPDM Rubber conforming to EN681-1 and are designed to fit into the socket of Monolithic concrete road gullies.

Available in two sizes to connect lateral pipes with an outside diameter range of 160 - 180mm into a 200mm socket and lateral pipes with an outside diameter range of 170 - 190mm into a 210mm socket.

Product Ref	Pipe Range	Socket Size
GS200	160 - 180mm	200mm
GS210	170 - 190mm	210mm

DN150 Pipe Material	Pipe o/d range	GS200 160 -180mm	GS210 170 - 190mm
Salt Glazed / Vitrified Clay	185-190mm	✗	✓
Naylor Densleeve	188mm	✗	✓
Hepworth Supersleeve	178mm	✓	✓
Smooth PVC pipe	160mm	✓	✗
Ultra-Rib	170mm	✓	✓
Twinwall Pipe	175-178mm	✓	✓
Polypipe Polysewer	160mm	✓	✗
Marley Quantum	160mm	✓	✗
Ductile Iron (BSEN598)	170mm	✓	✓
Cast Iron (SMU/Ensign/SML)	162mm	✓	✗
Cast Iron (BS437)	173mm	✓	✓
Cast Iron (BS416)	165mm	✓	✗

V003JAN18