

## PRODUCT DATA

**tensid<sup>®</sup> uk ltd**

**ONECOAT<sup>®</sup> interior**

**Interior Coating**

### Description and use

**ONECOAT** Interior is a high performance single component, single application coating that can be used on most plastic, GRP, and other man made materials. It is a durable product with high resistance to peeling, flaking, abrasion, and chemical agents that will extend the service life of these surfaces. **ONECOAT** Interior reduces the rate of oxidation, cracking and discolouration. **ONECOAT** Interior will restore the gloss and colour on dull and worn surfaces. **ONECOAT** Interior “with easy to clean properties” result in the reduction of maintenance and replacement cost. **ONECOAT** Interior meets the high standards of Deutsche Bahn AG requirements for permanent graffiti protection, making it the natural choice for the mass transit market as well as in buildings. Permanent markers, spray paint and ink colour can easily be removed multiple times without damaging the coating.

### Product Highlights

- Ready to use formula
- Long term graffiti protection
- Easy to apply medium gloss finish
- Long service life
- Rejuvenate finish and colour
- One coat system
- High UV-Resistance
- Non-flammable
- VOC-compliant

### Application areas

Interior surfaces in buildings, buses, trains, trams, signs, and many other non-porous man made materials.

### Pretesting

Testing is advisable in an inconspicuous area of each surface to ascertain if the desired results are achieved.

### TECHNICAL DATA

<b>Solids:</b>	81.6%
<b>Coverage:</b>	90-110m <sup>2</sup> per litre
<b>Temperature resistance:</b>	140°C

### Application

Clean the surface thoroughly with **ONECLEAN** HD or **ONECLEAN** LD depending on level of soiling with a white Scotch Brite, rinse carefully and allow surface to dry completely. Apply **ONECOAT** Interior with Miracle wipe, **ONECOAT** Applicator or HVLP Sprayer in a single uniform thin uniform coat, approximately 10/m<sup>2</sup> at 5-micron dry film.

### Drying times

Touch dry.....	45 min at (+20°C)
Fully dry.....	2-3 hours at (+20°C)
Full cure.....	12 hours at (+20°C)

### Cleaning of protected surfaces

Due to the coatings easy to clean properties, water alone is normally sufficient together with suitable Microfiber cloth, mop or brush. A small amount of a mild detergent like **ONECLEAN** LD might be useful assisting with the cleaning.

### Graffiti Removal

Use **ONEWIPE** or similar cloth dampened with Graffi Green, dab on to the graffiti and wipe off and neutralise with clean water. For spray paint and heavier graffiti use Graffi Clean 300, brush on to the graffiti and leave to dwell for 5 to 20 min, wipe off and neutralise.

*This product information is compiled to be of assistance but without guarantee. Users are responsible for correct surface preparation and product application as well as safe working practices.  
Always refer to Safety Data Sheet SDS and technical data sheet prior to using this product.*

For more information and photos please visit:  
**www.tensid.com**

Share your project photos and news on the Tensid UK social media professional community pages:



**tensid<sup>®</sup> uk ltd**  
**ONECOAT<sup>®</sup> interior**  
Interior Coating

19 July 2016, No.1