

Ecogranite Aquaflow Permeable Block Paving

Data Sheet



Ecogranite Aquaflow permeable blocks are specially designed, incorporating a slot and chamfer, allowing water to disperse at a high rate. Available in 60mm and 80mm rectangular blocks, they sit effortlessly alongside our conventional Ecogranite Royal Forest paving. The textured surface exposes the sparkling granite offering excellent skid/slip resistance. The Ecogranite Aquaflow permeable block can be specified for all sites designed under BS7533-pt13.

Colours For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral



Tintagel †



Truro

UP TO 77% BY-PRODUCT MATERIAL

One of the most sustainable paving options currently available.

Specification

Block sizes (depth)	60mm	80mm
200 x 100mm (blocks per pack)	560	400
Coverage per pack (m²)	11.2	8.0
Weight per pack (tonne)	1.47	1.41
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa BBA certificate 97/3373	Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Extremely low	Finishes Bush hammered finish
		Applications 60mm thick for use on footpaths, domestic drives and 80mm thick for use on roads.

The Ecogranite Aquaflow permeable blocks are best used in combination with the Formpave Aquaflow® System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs.

* Colour purposes only. † Special order.