## Tactile Block Paving

**Data Sheet** 





Tactile paving provides a warning to visually impaired pedestrians, to differentiate between where the footway ends and the carriageway begins. Our unique sized high strength tactile pavers have been specially designed to overcome the breakage problems caused by accidental overrun experienced by local authorities with larger element tactile paving.

**Colours** For an accurate colour match please request a sample.

350	C		C	0	(6)	6	5	6	6	6
10	L				8.	6	6	4	6	0
	ic.		0	4	4	4	¢		4	6
100	0			0	6	L	0	(6)		
2	4	1	6	6	1		c	K		6
6	6	10		P		4	9	4	6	6
C	6	K.	0	0		6	£	C	E	6
15	4			4		6	é	60		4
161	6		4	6	4	4	4	(4)	4	
100			0	0	0	8		C	6	

Autumn Yellow

## **Specification**

Block Sizes (Depth)	60mm					
200 x 133mm (blocks per pack)	300					
Coverage per pack (m²)	7.98					
Weight per pack (tonne)	1.1					
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa	Slip/skid resistance Low					
Finishes	Standard finish					
Applications	Pedestrian crossings.					

Tel: 01594 836 999

Email: sales@formpave.co.uk

www.formpave.co.uk

Web: