Data Sheet






Ecogranite has a textured surface finish with non-slip properties, making it ideal for pavements, paths and driveways. Ecogranite cobbles are available in either 60mm or 80mm depths that can be traditionally coursed or laid in a more unusual pattern such as circles or Flanders fans. Ecogranite kerb system, edging and starter circles have been specially designed to complement the range.

			. 01	an	acc
		1.1.1			
100					
		14	-10-1		
		1		in de la	

**Colours** For an accurate colour match please request a sample.





Truro \*

**UP TO 77% BY-PRODUCTMATERIAL** One of the most sustainable paving options currently available.

## Specification

-					
Block Sizes (depth)	60mm	80mm	80mm		
100 x 100mm (blocks per pack)	1120	800			
Coverage per pack (m <sup>2</sup> )	11.2	8.0			
Weight per pack (tonne)	1.47	1.41			
Note: Ecogranite paving packs contain lay	ers of 12 separate paving blocks of 7 various si	zes giving a total quantity of 120 b	olocks.		
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa	Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Extremely low	<b>Finishes</b> Bush hammered finish	<b>Applications</b> 60mm for use on footpaths and domestic drives. 80mm for use on commercial sites and roads.		

\* Colour purposes only. † Special order.

Formpave

Tufthorn Avenue, Coleford Gloucestershire, GL16 8PR Fax: 01594 810 577

**Tel:** 01594 836 999 Web:

Email: sales@formpave.co.uk www.formpave.co.uk