

TECHNICAL DATA SHEET

HPC 91 NU-FLAME SP MULTI SURFACE PRIMER

DESCRIPTION:

Nu-Flame SP Multi Surface Primer is a smooth, non-toxic, water-soluble primer, used as part of the Nu-Flame Fire Upgrade System.

ADVANTAGES:

Nu-Flame SP Multi Surface Primer provides excellent adhesion to glazed tiles and smooth melamine surfaces prior to the application of Nu-Flame Heat Insulating Basecoat

USES:

Primes melamine, powder coating, glazed tiles, matt tiles, Quarry tiles and Glass.

COLOUR RANGE:

White

PACK SIZE:

Single component product, supplied in 10 litre units.

COVERAGE RATE:

13 m² per litre

VOLUME SOLIDS:

38%

DRYING TIME:

Touch: 1 Hour
Overcoat: 4 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS