

## TECHNICAL DATA SHEET – HPC 05 NU-GUARD HIGH SOLIDS FINISH

### DESCRIPTION:

Nu-Guard High Solids Finish is a polysiloxane-based coating with an excellent decorative appearance and outstanding resistance to solvents and chemicals, making it a first choice anti-graffiti coating for use on external surfaces.

### ADVANTAGES:

Efficient graffiti removal with AG3 Graffiti Remover.

### USES:

For use on a variety of substrates such as painted brickwork, render, concrete, metal and wood and vehicles.

### COLOUR RANGE:

Clear, Any BS4800 or RAL Shade.

### PACK SIZE:

Two component product, supplied in 5 litre units.

### VOLUME SOLIDS:

90%

### COVERAGE RATE:

20 m<sup>2</sup> / Litre  
30-40 microns WFT

### DRYING TIME:

Touch :..... 4 hours.  
Overcoat : .....6 hours.

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

### APPLICATION:

By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

### EQUIPMENT CARE:

All equipment should be cleaned with Nu-Guard HS Thinners. Conventional thinners and brush cleaners are not effective.

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS