
ENVIROSAFE

COMMERCIAL SEWAGE TREATMENT PLANT





ENVIROSAFE COMMERCIAL SEWAGE TREATMENT PLANT

ENVIROSAFE


as camp sites, hotels or industrial units. The plant employs a plug and flow

Air blower

Control Panel

FEATURES AND BENEFITS

- Minimal footprint area
- > Single piece tank, modular systems up to 1000 PE available
- ▶ Bespoke units available in almost any configuration
- > Flow management to both stabilise influent volume variations and to minimise hydraulic impact on the final settlement process



SPECIFICATION (Single piece unit shown)

Unit code	17	23		34	38	42	47	55	67	80
Maximum flow (m³/day)	8	11		15	20	25	30	40	50	60
Overall length (m)	7.4	9.2		7.4	8.1	8.9	9.7	11.2	13.5	15.8
Overall width (m)	1.9	1.9		2.8						
Height (m)* 500mm Inlet/ 600mm Outlet Invert 1000mm Inlet/ 1100mm Outlet Invert 1500mm Inlet/1600mm Outlet Invert 2000mm Inlet/2100mm Outlet Invert	2.28 2.78 3.28 3.75		Height (m)** 500mm Inlet/ 650mm Outlet Invert 1000mm Inlet/ 1150mm Outlet Invert 1500mm Inlet/1650mm Outlet Invert 2000mm Inlet/2150mm Outlet Invert	3.02 3.52 4.02 4.52						
Diameter (m)				2.6						
Inlet/Outlet Diameter (mm)	-			160						
Weight approx. (kg)**	1200	1450		3000	3200	3400	3800	4200	4700	5400
Blower rating (230V single phase) (kW)	0.27	0.27		2 x 0.25	2 x 0.25	2 x 0.25	1.5	1.5	1.5	1.5

Extension necks can be added to turrets

Carnbane Business Park Newry, Co.Down BT35 6QH Tel: 028 302 66799 Fax: 028 302 60046

Wardhead Park Stewarton Ayrshire, KA3 5LH Tel: 01560 486588 Fax: 01560 486589

College Road North, Aston Clinton, Aylesbury Buckinghamshire HP 22 5EW Tel: 01296 633 000 Fax: 01296 633 001 www.kingspanenviro.com/Envirosafe





- Designed in accordance with EN 12255
-) CE marked

to achieve deeper inverts Weights are dry weights.