

# INTERLUDE

INTERLUDE is a simple and elegant flat tube radiator. It is manufactured from quality steel and has a sleek and streamlined appearance. It is both practical and attractive and is available in selected RAL, metallic or special metallic finishes.



RAL 9016  
Traffic White

## GENERAL SPECIFICATION



### CERTIFICATION

Manufactured and tested to EN 442. Carries the BS Kitemark and CE Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.



### GUARANTEE

10 year guarantee from date of purchase against manufacturing defects.



### COLOUR

Finished in white (RAL 9016) or selected RAL, textured, metallic or shimmer metallic colours. Please see page 278.



### MATERIAL

Manufactured from steel.



### SYSTEM

2 pipe pumped indirect domestic and commercial heating applications.



### CONNECTIONS

2 x 1/2" BSP as standard.



### AIR VENTS

Included in the packaging.



### OPERATING PRESSURES

Tested to a pressure of 5.2 bar. Working pressure of up to 4 bar.



### DUAL FUEL

ECO450 dual fuel heater kit available for INT2 & INT3 only. Please see page 144.



### DELIVERY

Stocked items (white/RAL 9006): 2 - 5 working days. Non-stocked items (colour): 6 - 8 weeks.




### VALVES

Please see page 144.

For more general information, please see page 276.

## DIMENSIONS



\*For dual fuel +/- 70mm.

## WEIGHTS, WATER CONTENTS & n-COEFFICIENTS

Model	Weight (kg)	Water Content (l)	n-Coefficient
INT1	9.31	2.9	1.190
INT2	13.68	4.8	1.205
INT3	19.86	8.6	1.227

Order Code	Nominal Height (H) (mm)	Nominal Length (L) (mm)	Heat Outputs @ ΔT 50°C		Heat Outputs @ ΔT 30°C		Dual Fuel Rating
			Watts	Btu/h	Watts	Btu/h	
INT1	530	500	295	1007	161	549	-
INT2	905	500	470	1604	254	867	450
INT3	1655	500	817	2788	435	1484	450