

ULLSWATER

ULLSWATER adds a touch of traditional style for any bathroom. It has a timeless quality which exudes rustic charm and its simple, rectangular framed design can be enhanced with traditional look valves for a truly authentic feel. It is manufactured from quality brass and has a highly polished chrome plated finish.

DIMENSIONS Н 457

WEIGHT & n-COEFF	FICIENT			
Model	Weight (kg)	n-Coefficient		
B36/1	14.40	1.218		
	•	<u> </u>		

For more general information, please see page 276.

GENERAL SPECIFICATION



CERTIFICATION

Manufactured and tested to EN 442. Carries the BS Kitemark and CE Mark. Produced under a quality management system - ISO 9001:2015, environmental management system - ISO 14001:2015 and Occupational health and safety management system - OHSAS 18001.



10 year guarantee from date of purchase against manufacturing defects.

COLOUR Finished in chrome.

MATERIAL

Manufactured from brass.



SYSTEM (INDIRECT)

2 pipe pumped indirect domestic and commercial heating applications.



SYSTEM (DIRECT)

Suitable for direct systems. Please refer to page 277 for information on dezincification.



CONNECTIONS

2 x ½" BSP as standard.



AIR VENTS Integrated.



OPERATING PRESSURES

Tested to a pressure of 6.9 bar. Working pressure of up to 5.3 bar.



DUAL FUEL

PTC300 dual fuel heater kit available. Please see page 144.



APM® TECHNOLOGY

PTC heater kit comes with APM® technology. Please see page 277.



DELIVERY

2 - 5 working days.



VALVES

Please see page 144.

Order Code Nominal Height (H) (mm)	J , ,	Nominal Length (L) (mm)	Heat Outputs @ ∆T 50°C		Heat Outputs @ ∆T 30°C		Dual Fuel Rating
	(IIIII)	Watts	Btu/h	Watts	Btu/h	Watts	
B36/1	1302	540	350	1194	188	641	300