

SOUTH BANK

GLAZED CERAMIC | WALL TILES |  MADE IN THE UK

PLAIN COLOUR TILES



JOHNSON • TILES
Since 1901



www.johnson-tiles.com

SOUTH BANK


A sleek range of UK-manufactured ceramic wall tiles, fully stocked in the UK, available in eight on-trend colours, and a new slim size of 245x75mm. South Bank offers a transparent gloss finish possessing depth and variation of contemporary colour. The slim format allows for the creation of truly unique lay patterns to maximise the creative possibilities within any interior. Featuring the signature colours of Azure, Blossom and Dusk which are underpinned by a complementary, neutral palette ranging from the subtle, calming Snow to the warmer hue of Pearl, this range allows for the creation of diverse and harmonious colour combinations.





Colours & Product Codes

V3: Moderate to High Shade Variation



WINTER

SBK01A LRV: 86



PEARL

SBK02A LRV: 64



WHISPER

SBK03A LRV: 55



PEWTER

SBK04A LRV: 32



DOVE

SBK05A LRV: 26



AZURE

SBK06A LRV: 14



DUSK

SBK07A LRV: 17



BLOSSOM

SBK08A LRV: 32



Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	245x75mm	Gloss	All Colours Shown	8mm	54 Tiles	0.99 m ²	16.00 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
South Bank	All Sizes Shown	Internal Only	-	-	V3	Glazed Ceramic [BIII]

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\leq \pm 0.25\%$	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm ²	$\geq 25\text{N} / \text{mm}^2$
Thickness EN ISO 10545 - 2	$\pm 10\% \leq \pm 0.5\text{mm}$	$\pm 2.5\%$	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	$\pm 0.15\%$	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.4\%$	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A - B
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class A1 Non Combustible
Weight / M²	16.17 kg 8mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

Environmental Credentials



Each tiles contains up to 20% recycled ceramic materials.



All product boxes contain 100% recycled cardboard materials.



All product packaging is 100% free of single-use plastics.

Note: For more information about our Environmental Credentials, please visit our website - www.johnson-tiles.com/about/environment

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



For more information about South Bank or any of our other product ranges simply visit **www.johnson-tiles.com** |      

Where To Find Us

Johnson Tiles

Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

JOHNSON-TILES
Since 1901