

**[READY  
TO USE]**

# PATCH & REPAIR FILLER READY TO USE FOR GAPS, CRACKS, SCRATCHES AND HOLES

- ▶ EASY TO SAND
- ▶ MINIMAL SHRINKAGE
- ▶ NO NEED TO SPOT PRIME
- ▶ DOES NOT FLASH OR GRIN



## PURPOSE

Ready to use paste filler, interior use, manual application.

## SUBSTRATE

**PATCH & REPAIR FILLER READY TO USE** can be applied to any substrates either unpainted or painted.

- Gypsum plaster, plasterboards,
- Old painted surfaces,
- Cement, concrete, cellular concrete,
- Breeze blocks, bricks, stone.

## OVERCOATING

**PATCH & REPAIR FILLER READY TO USE** can be overcoated with any type of **TOUPRET** filler, all types of paints and wall coverings.

## Physical and technical FEATURES

**PATCH & REPAIR FILLER READY TO USE** : filler in paste form for interior use, made of mineral extracts and selected resin.

- Characterization (NFT 36-005): Family III class 2
- Codification (NFT 30-608):  $G_3E_5S_2V_0W_0A_0C_0$
- Application thickness: up to 1 cm
- Colour: white
- Adhesion filler/substrate (NFT 30-608): > 0.5Mp

## USE AND STORAGE CONDITIONS

- Tools: coating knife, smoothing blade.
- Tools cleaning: with water
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost

## PACKAGING

- Tub of 1.5 kg

## RECOMMENDATIONS and care for use

- Do not apply under a temperature < 8°C and > 35°C nor under a hygrometry rate over 70%.
- Do not apply on warm substrates.
- Do not apply on wet/damp substrates.
- Do not apply on polystyrene nor on wall paper nor on exterior substrates.

## SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

## NORMATIVE DOCUMENTS to be referred to

- NFT 30-608: Coating fillers for interior works and/or exterior .
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): Application procedures of wall

## HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of **PATCH & REPAIR FILLER READY TO USE** are provided in good faith and result from TOUPRET's experience and knowledge of the products

The product is required to be applied as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.