

READY MIXED FILLER

SNAGGING FILLER

[READY TO USE]

- ▶ **VERY EASY TO SAND DOWN WHEN OVERFILLED**
- ▶ **NO NEED TO SPOT PRIME**
- ▶ **WILL NOT FLASH OR GRIN**
- ▶ **RESISTS SLUMPING**



PURPOSE

Ready to use paste filler, interior use, manual application.

SUBSTRATE

READY MIXED FILLER can be applied on any substrates either unpainted or painted.

- Gypsum plaster, plaster tiles, plasterboards,
- Old painted surfaces,
- Cement, concrete, cellular concrete,
- Breeze blocks, bricks, stones.

OVERCOATING

READY MIXED FILLER can be coated by any type of **TOUPRET** fillers, all types of paints and wall coverings.

Physical and technical FEATURES

READY MIXED FILLER: filler in paste form for interior use, made of mineral extracts and selected resin.

- Characterization (NFT 36-005): Family III class 2
- Codification (NFT 30-608): $G_3E_3S_2V_0W_0A_0C_0$
- Application thickness: up to 1 cm
- Colour: white
- Adhesion filler/substrate (NFT 30-608): > 0.5 Mpa

USE AND STORAGE CONDITIONS

- Tools: coating knife, smoothing blade.
- Tools cleaning: with water
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from frost

PACKAGING

- Tube of 330 g
- Tub of 1.5 kg

RECOMMENDATIONS and care for use

- Do not apply under a temperature < 8°C and > 35°C nor under a hygrometry rate over 70%.
- Do not apply on warm substrates.
- Do not apply on wet/damp substrates.
- Do not apply on polystyrene nor on wall paper nor on exterior substrates.

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- NFT 30-608: Coating fillers for interior works and/or exterior .
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): Application procedures of wall papers and wall coatings.

HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on <http://www.toupretpro.co.uk> or on quickfds.com or toupret.com.

The data sheet information, especially the guidelines relevant to the application and final use of **READY MIXED FILLER** are provided in good faith and results from the knowledge of the products and experience of **TOUPRET** company. The product is required to be applied as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.