

# AIRSPRAY G

READY-TO-USE HIGH-BUILD BACKING AND LEVELLING  
SPRAY PLASTER

## EXCELLENT PRICE AND QUALITY PERFORMANCE

- ◆ SPRAYABLE
- ◆ EXCELLENT LEVELLING CHARACTERISTICS
- ◆ LONG OPEN TIME
- ◆ EASY TO SAND



### PURPOSE

Levelling filler in ready mixed form for Airless spraying and interior use.

### SUBSTRATES

Airspray® G can be applied to any substrates either new or renovated, unpainted or painted:

- Gypsum plaster, plasterboards/drywall lining, honeycomb, concrete, breeze blocks, cellular concrete, bricks
- Cement, old painted surfaces, fibreglass cloth, old textured surfaces (i.e Artex) and limewash mortar.

### OVERCOATING

Airspray® G can be coated with any type of paints, filler and wall coverings.

### Physical and technical FEATURES

- Airspray® G: filler in ready mixed form for interior use, made of calcium carbonates loads and resins.
- Characterization (NFT 36-005): Family III - class 2.
- Codification (EN 16566): G<sub>3</sub>S<sub>1</sub>V<sub>0</sub>W<sub>0</sub>A<sub>0</sub>C<sub>0</sub>R<sub>0</sub>.
- Mixing rate: ready to use.
- Application thickness: up to 5 mm.
- Coverage: 1.7 kg/m<sup>2</sup>/mm.
- Setting time: second coat as soon as the filler is hard and dry to the touch.
- Overcoating: can be painted in 24 to 48 hours average time (after completely dry)
- Color: white
- Adhesion: filler/substrate (EN 16566): > 0.5 Mpa.

### USE AND STORAGE CONDITIONS

- Application tools: any type of Airless piston machine with minimum flow of 5L/min. For optimum use, we recommend the following nozzles: 5.31, 5.35, 6.31 or 6.35.
- Tool cleaning: with water.
- Preservation: product guaranteed 12 months. Stored away from sunlight and frost. If found to be faulty within the guarantee period, we will arrange a replacement on proof of purchase.

### PACKAGING

- Bag of 25kg.

### RECOMMENDATIONS and care for use

The times mentioned are indicative and depend on the substrate, coat thickness, and the ambient conditions.  
Do not apply at a temperature below 8°C or above 35°C nor at a relative humidity over 70%.

Do not apply on overheated surfaces or damp substrates.

Do not apply on polystyrene, nor on wall paper, nor on exterior substrates.

### SUBSTRATES PREPARATION

Substrates to be prepared as per the current trade practices.  
Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- EN 16566: Coating Fillers for interior and/or exterior works.
- NFT 36-005: Characterization of paint products.
- DTU 59.1 (NFP 74-201): Building paint works.
- DTU 59.4 (NFP 74-204): Wall papers and wall coverings processing.
- NF Environment – Paint fillers (NF446).
- BS EN 13963 : 2014 - Jointing materials for gypsum boards.

### HEALTH AND SAFETY

It is recommended to wear gloves and glasses while applying Airspray® G.

Dispose of unused product and packaging responsibly at your local waste collection centre.

Preservatives: Contains 1,2-benzisothiazolin-3-one; C(M)IT / MIT (3:1); MBIT. May produce an allergic reaction.  
Safety data sheet available at [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of the product are provided in good faith and result from TOUPRET's experience and knowledge of the products. The product should be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed at a temperature of 20°C, a relative humidity of 50% and on average absorbency substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.



\* Information on the emission level of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on a scale from A+ (very low emissions) to C (high emissions).