

HALFEN HIT INSULATED CONNECTION STEEL TO CONCRETE CONNECTOR

Technical Product Information

YOUR BEST CONNECTIONS



EXTREMELY ADAPTABLE

Did you know that squids adapt to their environment extremely well? They can pass through the smallest gaps, and thanks to their long tentacles, they can cling to anything, anywhere on the seabed. The HIT Steel to concrete insulated connection prefers to use its long rebars as reliable anchors in concrete. But the HIT is also very adaptable – especially when it involves tolerances in building!



Find out more at
www.halfen.com!


YOUR BEST CONNECTIONS

NEW: HIT INSULATED CONNECTIONS FOR STEEL TO CONCRETE CONNECTION

The new HALFEN HIT Steel to concrete connector is now available for connection of filigree steel components to concrete structures. This reduces thermal bridges while simultaneously ensuring high load transfer. The insulated connection elements are also freely height adjustable for easy compensation of construction tolerances.



CONTENTS

HALFEN HIT Insulated connection – Steel to concrete connection	4	
Overview of benefits	5	
Building materials/Test certificates	7	
Notes on calculation	8	
Verifying correct installation	11	
Using the installation aid	12	
1 HIT-HP SDV / HIT-SP SDV	13	
Load capacity range	14	
Load capacity values	15	
Product specifications	20	
On-site reinforcement	22	
Deformation	24	
Axial spacing, edge distance	25	
Installation instructions	27	
		
		NEW
2 HIT-HP SMV / HIT-SP SMV	29	
Load capacity range	30	
Load capacity values	31	
Product specifications	33	
On-site reinforcement	34	
Deformation	35	
Axial spacing	36	
Installation instructions	38	
		
		NEW
3 HIT-HP SZV / HIT-SP SZV	40	
Load capacity range	41	
Load capacity values	42	
Product specifications	43	
On-site reinforcement	44	
Axial spacing	45	
Installation instructions	47	
		
		NEW
4 Construction and installation of connecting components	49	
On-site facing plate with notch	50	
Connecting supports	52	
Installation and height adjustment	53	
Installation, structural steel	54	
Expansion joint spacings	55	
5 Building physics	56	
Characteristic values for thermal bridges	57	
Characteristic thermal values according to Building Authority Approval	58	
Characteristic thermal values for HIT-HP Insulated connections	62	
Characteristic thermal values for HIT-SP Insulated connections	63	
Addresses / Technical support	64	

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Introduction

HALFEN HIT Steel to concrete connector

Steel structures; steel balconies, steel canopies or solar shading systems are generally connected to reinforced concrete components. Because of the high thermal conductivity of steel, an efficient thermal separation in the connection is essential to prevent thermal bridges as these cause higher energy consumption, and to avoid structural damage caused by condensation and mould. HALFEN HIT Steel to concrete connectors reduce thermal bridges to a minimum with simultaneous high load transfer capabilities.

The core of the elements consists of a statically effective system of compression, tension and shear bars, which are anchored on-site in load-bearing concrete components. Tension and compression rods with metric connection threads are provided on the (exterior) balcony side. The system has an angled slotted bracket for freely height adjustment of connected components.

The load-bearing elements are tightly enclosed in a non-flammable mineral wool insulation; this significantly improves thermal separation. A robust housing encases and protects the insulation material from mechanical damage and the effects of weather. All load relevant elements in the connection and on the (exterior) balcony side are stainless steel to protect from corrosion and to ensure durability.


The following types of insulated connection are available:

- **SDV** as connection for freely cantilevered steel elements to transfer positive and negative bending moments and positive shear loads
- **SMV** as connection for freely cantilevered steel elements to transfer negative bending moments and positive shear loads
- **SZV** as connection for simply supported elements to reinforced concrete slabs to transfer positive shear loads
- all types are available with 80mm (HIT-HP) and 120mm (HIT-SP) thick insulation.

The HIT-SMV and HIT-SZV, with intelligent bar layout, are ideal for use with semi-precast filigree slabs, the short anchor heads do not come into contact with the reinforcement of the semi-precast slabs.

All types are delivered with an pre-fitted installation aid, these allow easy adjustment to facilitate installation in the formwork.

HIT-HP SMV-2M16



HALFEN HIT STEEL TO CONCRETE CONNECTOR


Benefits in Planning and Installation

The benefits at a glance

► Reliable design and planning


- Building Authority Approval including determination of the equivalent thermal conductivity (λ_{eq})
- type tested
- chi-values for masonry with *ETICS available, other values on request

*ETICS External Thermal Insulation Composite System.




► Robust box

- reliable and sturdy box for installation in construction site conditions
- weather-resistance, reliable protection of the insulation material
- robust box ensures reliable connection of attached steel components




► Pre-fitted installation aid

- installation aid is pre-fitted as standard
- facilitates installation and adjustment in the formwork
- everything required is included in delivery; no additional costs




► Vertical adjustment of the steel with an angled slotted bracket

- pre-fitted steel bracket with angled slots, lateral movement provides vertical adjustment
- freely adjustable
- robust design, suitable for building site conditions



► Reliable notched support

- angled slotted bracket with bevelled edge, ensures support surface for the connecting notched is flat.
- no unintentional movement or twisting
- reliable, force-locked transfer of loads





HALFEN HIT STEEL TO CONCRETE CONNECTOR

Product Overview – Thermally Insulated Connections

1 Cantilevered balcony slabs

HIT-HP SDV / HIT-SP SDV



Transfer of bi-directional bending moments and positive shear loads
 • insulation thickness 80 mm / 120 mm
 → page 13



2 Cantilevered balcony slabs

HIT-HP SMV / HIT-SP SMV



Transfer of negative bending moments and positive shear loads
 • insulation thickness 80 mm / 120 mm
 → page 29



3 Simply supported balcony slabs on columns

HIT-HP SZV / HIT-SP SZV

Only for shear load transfer in positive direction
 • insulation thickness 80 mm / 120 mm
 → page 40



4 Construction

HIT-HP/SP SDV, SMV, SZV

• Design and installation of connected components
 → page 49

5 Building physics

HIT-HP/SP SDV, SMV, SZV

• Building physics, characteristic values
 → Page 56

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Material Specification and Test Certificates

Materials; HIT Elements

Tension/compression rods	Flash butt welded bar connection, consisting of a combination of two reinforcing steel bars B500 according to DIN 488, and stainless steel bars of strength class S690 or stainless steel B500NR with partial or full metric threads, for connection of steel components to the (exterior) side of the HIT element.
Load-bearing support	Stainless steel bars, strength class S 690 with partial or full metric threads on the steel connection side of the element, and anchor heads on the concrete side.
Shear load rebar	Stainless steel bars in strength class B500NR or flash butt welded bar connection, consisting of a combination of stainless steel bar B500NR and reinforcing steel bars B500
Installation bracket	Stainless steel, strength class S460
Angled slotted bracket	Stainless steel, strength class S235
Accessories	Stainless steel washers in strength class S460, Stainless steel bolt-nuts in strength class A4-80
Box	PVC plastic according to EN ISO 1163
Insulation material	Mineral wool (WLG 035) Building Material Class A1 – non-flammable insulation according to DIN 4102-14 or Euroclass A1 in accordance with EN 13501-1

Materials; load bearing concrete components

Concrete	Suitable for concrete strength $\geq$ C20/25
On-site reinforcement	B500 Reinforcement steel

Materials; connected steel components

Steel	Steel according to EN 1993 or stainless steel according to approval Z-30.3-6 Required minimum strength class of steel on the balcony side: S 235
--------------	---

Test certificates

Building Authority Approvals	
HIT-HP/SP SDV	DIBT* Berlin: Approval no. Z-15.7-336
HIT-HP/SP SMV	
HIT-HP/SP SZV	*(German Institute of Building Technology)
Type tests	
Type tested by the LGA Landesgewerbeanstalt Bayern	Test no. S-WUE/100358 (German certification institute)



Approvals and type tests on the internet

The approvals and type tests can be found at www.halfen.com/downloads/brochures.
Or simply scan the code and then select the document to download the PDF file.



HALFEN HIT STEEL TO CONCRETE CONNECTOR Calculation

Notes on calculation

The connection is used as a thermally insulated, load-bearing connection of steel components to load-bearing reinforced concrete components.


The load-bearing structure requires a reinforced concrete element according to EN 1992-1-1 (minimum concrete strength C20/25; density $2,000 \text{ kg/m}^3 - 2,600 \text{ kg/m}^3$). Connected steel component must be in accordance with EN 1993 (e.g. balconies, canopies). The element is used for predominantly static loads.

The load-bearing concrete and the connected steel components must be verified by a structural engineer in accordance with current applicable standards. Design and static verification according to EN 1992-1-1 for the load-bearing component, and according to EN 1993 for the connected component. For verification, the loads on the connected structure must be calculated in accordance with EN 1991.

HALFEN HIT-HP HALFEN HIT-SP	SDV 2M16 SMV 2M16 SZV 2M16	SDV 2M22
HIT Height h [mm]	Inner cantilever z_i [mm]	Inner cantilever z_i [mm]
180	113	108
200	133	128
220	153	148
240	173	168
260	193	188
280	213	208

For indirect support of the HIT element, the transfer of loads from the connected element to the load-bearing component must be verified separately by the structural engineer. The insulation element is not designed for transfer of torsion loads; therefore, torsion-free installation must be ensured. Any torsion interaction between adjacent insulation elements must be prevented.

The load capacities are provided for the standard element height. Slabs thicknesses greater than the specified standard concrete coverings are possible, the element load capacities must always be selected for the possible internal cantilever z_i .



Inner cantilever and component height



Corrosion protection

The stainless steels used comply with corrosion resistance class III/medium. Using the HALFEN HIT Steel to Concrete connectors in combination with galvanized or facing plates treated with corrosion protection coatings (i.e. paint) is non critical when considering galvanic corrosion, as the area of the facing plate is considerably larger than the surface area of

the stainless steel. Consequently, a failure of the connection caused by contact corrosion is prevented.

Shortening the threaded connections

The threaded connection rods may be shortened as required; at least two thread must remain visible after final installation of steel components.

HALFEN HIT STEEL TO CONCRETE CONNECTOR Calculation

Connection details HIT-SDV / HIT-SMV


The elements are delivered with a standard width of $b = 250$ mm.
Smaller widths, from $220 \leq b \leq 250$ mm are available as custom lengths on request.

The structural engineer has to verify that the design values of the loads in the selected section do not exceed the specified resistance.


The horizontal and vertical axial spacings of the tension and compression elements are decisive for the design of the connected component. The axial spacing of the tension bars is 70 mm for all elements, for the compression rods 115 mm. The vertical spacing results from the selected element height h :

$$M16: z_i = h - 67$$

$$M22: z_i = h - 72$$



Spacings with HIT-SDV and HIT-SMV with M16 thread




Dimensions in [mm]


Spacings with HIT-SDV with M22 thread

For HIT-SDV and HIT-SMV elements, the design values for resistance at ultimate load capacity are shown for two sections:

Section A-A Design section according to Z-15.7-336
(section in axis of tension and shear load bars)



Section B-B Design section at connection surface of steel component (surface of the facing plate to the connected component)



HALFEN HIT STEEL TO CONCRETE CONNECTOR Calculation

With HIT-SDV and HIT-SMV elements there is a dependency between the moment load capacity and the shear load in section B-B.

Therefore the tables show four value pairs V_{Rd}/M_{Rd} .

- Intermediate values may be linearly interpolated.
- Extrapolation for larger shear load values ($V_{Ed} > V_{Rd,4}$) is not possible.




Figure: Dependency of moments and shear forces in section B-B

HIT-SZV Connection details

The HIT-SZV element is delivered with a standard width of $b = 250$ mm. Smaller widths, $220 \leq b \leq 250$ mm, are possible on request. Decisive for the design of the connected component are the axial spacings (horizontal and vertical) of the compression elements – the axial spacings of the compression bars is 115 mm for all elements.





Figure: Spacings for HIT-SZV with M16 thread


The provided design values for load carrying capacity apply for the rear-most surface of the facing plate of the connected element. See section A-A.




HALFEN HIT STEEL TO CONCRETE CONNECTOR

Verifying correct installation


Verifying correct installation




✗ incorrect rotated horizontal orientation




✗ incorrect twisted horizontal orientation




✗ incorrect tilted vertically!




✓ correct!





✗ incorrect: elements askew, horizontal to the concrete edge, towards the front or back



✓ correct: element aligned along axis



✗ incorrect tilted vertically



✓ correct: vertically aligned

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Installation aid

Using the installation aid





Figure: HIT-HP SDV and installation aid

Transport protection doubles as installation aid

Each HIT element connection steel to concrete is delivered with a fitted transport protection, which is also used as an installation aid.

Primarily, the transport protection board shields the insulation box and connection bolts from damage; the connection bolts' orientation is also protected. The orientation of the bolts is critical and therefore requires special protection during concreting. The protection boards should remain in position during concreting or matching holes must be provided in the on-site formwork.

If the installation aids are not removed from the elements, they can be used for alignment and connection to the on-site formwork. The excess ends of the installation aids can be used as required to fix the element to the formwork. If the elements are to be inserted directly through the formwork or using the installation aids, these can be removed and used as templates to set the drill holes and element spacings.



Figures: above: Installation aid on formwork using drill templates
below: Installation aid on formwork – aligned



Please note: Ensure the *Actual size* option is active in the *Print* menu when printing the drilling templates. Check the printed templates for correct dimensions!



HALFEN Drill template are available for download.

Alternatively, Drill templates are available as PDF files for free download. The templates can be printed and attached to the formwork for measuring and drilling.

When printing the files, ensure the correct scale is set:

Page setting should be “*actual size*” or 100%.

The control grid (2×2 cm) should also be checked for correct size after printing the template.



A free drilling template (.pdf file) is available at:

► www.halfen.com ► Product Ranges ► Construction
► Reinforcement systems ► HIT Steel to Concrete Connector ► Product Information ► Installation Instructions



HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV

1

- > Connection system for attaching steel elements to reinforced concrete structures
- > Transfer of bi-directional bending moments and positive shear loads

TYPE TESTED



Application: Cantilevered balcony

HIT-HP SDV – High Performance with 80 mm insulation
HIT-SP SDV – Superior Performance with 120 mm insulation

Contents	Type	Page
Load range	HIT-HP SDV, HIT-SP SDV	14
Load capacity values	HIT-HP SDV, HIT-SP SDV	15
Product description	HIT-HP SDV, HIT-SP SDV	20
On-site connecting reinforcement	HIT-HP SDV, HIT-SP SDV	22
Deformation	HIT-HP SDV, HIT-SP SDV	24
Axial spacings	HIT-HP SDV, HIT-SP SDV	25
Installation instructions	HIT-HP SDV, HIT-SP SDV	27

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV

Load capacity ranges

Combinations of two moment and three shear load capacities are available. The following combinations of tension and shear bars are available for HIT-HP (80 mm thick insulation) and HIT-SP (120 mm thick insulation).

Element width B = 25 cm

Number and diameter of balcony side connection threads	Number and diameter of tension and compression bars on slab side	Number and diameter of the shear load bars		
		2 Ø8	2 Ø10	2 Ø12
2M16	2Ø14	•	•	
2M22	2Ø20	•	•	•

Design values for selected elements can be found on the following pages • = HP and SP

Basic types – Ordering example

Ordering example

HIT-HP	SDV	- 2M16	- 0208	- 18
HIT-SP	SDV	- 2M22	- 0212	- 28
↓	↓	↓	↓	↓
①	②	③	④	⑤



CUSTOM SOLUTIONS

HALFEN HIT Insulated connections

Our technical support team is available if a custom solution is required for your project.

Contact details: → see back cover of catalogue

Type designation

- ① Product group
- ② Joint spacing 80 mm (HP) or 120 mm (SP)
- ③ Connection type
- ④ Moment load range
- ⑤ Shear load range
- ⑥ Element height [cm]

Technical specifications

Element designation HIT-HP/HIT-SP	Possible element heights h [cm]	Balcony connection Thread	Main slab			min. concrete cover, slab [mm]	
			Tension rod [mm]	Compression rod [mm]	Shear load rod [mm]	C _{v,top}	C _{v,bottom}
SDV-2M16-0208	18–28	2 M16	2 Ø14	2 Ø14	2 Ø 8	20	33
SDV-2M16-0210		2 M16	2 Ø14	2 Ø14	2 Ø10	20	33
SDV-2M22-0208		2 M22	2 Ø20	2 Ø20	2 Ø 8	26	26
SDV-2M22-0210		2 M22	2 Ø20	2 Ø20	2 Ø10	26	26
SDV-2M22-0212		2 M22	2 Ø20	2 Ø20	2 Ø12	26	26

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-HP SDV 2M16-0208	Section A-A V _{Rd,A} [kN]		Section B-B for selected shear load V _{Rd,B} [kN]								M16
Design values	33.5	33.5	10.0	10.0	20.0	20.0	30.0	30.0	33.5	33.5	
Element height [mm]	M _{Rd,A} [kNm]		M _{Rd,B} [kNm]								
180	-13.9 12.5	-15.1 14.7	-12.5 12.5	-13.7 14.7	-11.1 12.5	-12.3 14.7	-9.7 12.5	-10.9 14.7	-9.2 12.5	-10.5 14.7	
200	-16.0 14.6	-17.8 17.1	-14.4 14.6	-16.2 17.1	-12.8 14.6	-14.7 17.1	-11.3 14.6	-13.1 17.1	-10.7 14.6	-12.6 17.1	
220	-18.1 16.7	-20.5 19.5	-16.3 16.7	-18.8 19.5	-14.6 16.7	-17.0 19.5	-12.9 16.7	-15.3 19.5	-12.3 16.7	-14.7 19.5	
240	-20.2 18.8	-23.2 22.0	-18.3 18.8	-21.3 22.0	-16.4 18.8	-19.4 22.0	-14.5 18.8	-17.5 22.0	-13.8 18.8	-16.8 22.0	
260	-22.3 20.9	-25.8 24.4	-20.2 20.9	-23.8 24.4	-18.1 20.9	-21.7 24.4	-16.1 20.9	-19.6 24.4	-15.3 20.9	-18.9 24.4	
280	-24.4 23.0	-28.4 26.9	-22.1 23.0	-26.2 26.9	-19.9 23.0	-24.0 26.9	-17.7 23.0	-21.7 26.9	-16.9 23.0	-21.0 26.9	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-HP SDV 2M16-0210	Section A-A V _{Rd,A} [kN]		Section B-B for selected shear load V _{Rd,B} [kN]								M16
	52.3	52.3	30.0	30.0	40.0	40.0	50.0	50.0	52.3	52.3	
Element height [mm]	M _{Rd,A} [kNm]		M _{Rd,B} [kNm]								
180	-13.9 12.5	-15.1 14.7	-9.7 12.5	-10.9 14.7	-8.3 12.5	-9.6 14.7	-6.9 12.5	-8.2 14.7	-6.6 12.5	-7.8 14.7	
200	-16.0 14.6	-17.8 17.1	-11.3 14.6	-13.1 17.1	-9.7 14.6	-11.6 17.1	-8.1 14.6	-10.0 17.1	-7.8 14.6	-9.6 17.1	
220	-18.1 16.7	-20.5 19.5	-12.9 16.7	-15.3 19.5	-11.1 16.7	-13.6 19.5	-9.4 16.7	-11.8 19.5	-9.0 16.7	-11.4 19.5	
240	-20.2 18.8	-23.2 22.0	-14.5 18.8	-17.5 22.0	-12.6 18.8	-15.6 22.0	-10.7 18.8	-13.7 22.0	-10.2 18.8	-13.2 22.0	
260	-22.3 20.9	-25.8 24.4	-16.1 20.9	-19.6 24.4	-14.0 20.9	-17.6 24.4	-11.9 20.9	-15.5 24.4	-11.5 20.9	-15.0 24.4	
280	-24.4 23.0	-28.4 26.9	-17.7 23.0	-21.7 26.9	-15.4 23.0	-19.5 26.9	-13.2 23.0	-17.3 26.9	-12.7 23.0	-16.8 26.9	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-HP SDV 2M22-0208	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M22
	Design values		10.0	10.0	20.0	20.0	30.0	30.0	33.5	33.5	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-27.4	-29.5	-26.0	-28.1	-24.7	-26.8	-23.3	-25.4	-22.9	-24.9	
	16.1	18.8	16.1	18.8	16.1	18.8	16.1	18.8	16.1	18.8	
200	-32.5	-35.0	-31.0	-33.4	-29.4	-31.9	-27.9	-30.4	-27.4	-29.9	
	18.7	22.0	18.7	22.0	18.7	22.0	18.7	22.0	18.7	22.0	
220	-37.1	-40.4	-35.4	-38.7	-33.7	-37.0	-32.0	-35.3	-31.4	-34.8	
	21.5	25.2	21.5	25.2	21.5	25.2	21.5	25.2	21.5	25.2	
240	-41.4	-45.7	-39.5	-43.9	-37.7	-42.0	-35.8	-40.1	-35.2	-39.5	
	24.2	28.4	24.2	28.4	24.2	28.4	24.2	28.4	24.2	28.4	
260	-45.6	-50.3	-43.6	-48.2	-41.5	-46.2	-39.5	-44.2	-38.8	-43.5	
	26.9	31.6	26.9	31.6	26.9	31.6	26.9	31.6	26.9	31.6	
280	-49.7	-54.7	-47.5	-52.5	-45.4	-50.4	-43.2	-48.2	-42.5	-47.5	
	29.7	34.8	29.7	34.8	29.7	34.8	29.7	34.8	29.7	34.8	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-HP SDV 2M22-0210	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M22
	Design values		30.0	30.0	40.0	40.0	50.0	50.0	52.3	52.3	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-27.4	-29.5	-23.3	-25.4	-22.0	-24.1	-20.6	-22.7	-20.3	-22.4	
	16.1	18.8	16.1	18.8	16.1	18.8	16.1	18.8	16.1	18.8	
200	-32.5	-35.0	-27.9	-30.4	-26.4	-28.9	-24.8	-27.3	-24.5	-27.0	
	18.7	22.0	18.7	22.0	18.7	22.0	18.7	22.0	18.7	22.0	
220	-37.1	-40.4	-32.0	-35.3	-30.3	-33.6	-28.6	-32.0	-28.2	-31.6	
	21.5	25.2	21.5	25.2	21.5	25.2	21.5	25.2	21.5	25.2	
240	-41.4	-45.7	-35.8	-40.1	-33.9	-38.3	-32.1	-36.4	-31.6	-36.0	
	24.2	28.4	24.2	28.4	24.2	28.4	24.2	28.4	24.2	28.4	
260	-45.6	-50.3	-39.5	-44.2	-37.5	-42.1	-35.4	-40.1	-35.0	-39.6	
	26.9	31.6	26.9	31.6	26.9	31.6	26.9	31.6	26.9	31.6	
280	-49.7	-54.7	-43.2	-48.2	-41.0	-46.1	-38.9	-43.9	-38.4	-43.4	
	29.7	34.8	29.7	34.8	29.7	34.8	29.7	34.8	29.7	34.8	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-HP SDV 2M22-0212	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M22
Design values	75.3	75.3	50.0	50.0	60.0	60.0	70.0	70.0	75.3	75.3	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-27.4 16.1	-29.5 18.8	-20.6 16.1	-22.7 18.8	-19.2 16.1	-21.3 18.8	-17.9 16.1	-20.0 18.8	-17.2 16.1	-19.3 18.8	
200	-32.5 18.7	-35.0 22.0	-24.8 18.7	-27.3 22.0	-23.3 18.7	-25.8 22.0	-21.8 18.7	-24.3 22.0	-21.0 18.7	-23.5 22.0	
220	-37.1 21.5	-40.4 25.2	-28.6 21.5	-32.0 25.2	-26.9 21.5	-30.3 25.2	-25.2 21.5	-28.6 25.2	-24.3 21.5	-27.7 25.2	
240	-41.4 24.2	-45.7 28.4	-32.1 24.2	-36.4 28.4	-30.2 24.2	-34.5 28.4	-28.3 24.2	-32.7 28.4	-27.4 24.2	-31.7 28.4	
260	-45.6 26.9	-50.3 31.6	-35.4 26.9	-40.1 31.6	-33.4 26.9	-38.1 31.6	-31.4 26.9	-36.1 31.6	-30.3 26.9	-35.0 31.6	
280	-49.7 29.7	-54.7 34.8	-38.9 29.7	-43.9 34.8	-36.7 29.7	-41.7 34.8	-34.6 29.7	-39.6 34.8	-33.4 29.7	-38.4 34.8	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-SP SDV 2M16-0208	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M16
Design values	28.1	28.1	10.0	10.0	20.0	20.0	25.0	25.0	28.1	28.1	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-13.9 12.5	-15.1 14.7	-12.0 12.5	-13.3 14.7	-10.2 12.5	-11.5 14.7	-9.3 12.5	-10.6 14.7	-8.7 12.5	-10.0 14.7	
200	-16.0 14.6	-17.8 17.1	-13.9 14.6	-15.7 17.1	-11.8 14.6	-13.7 17.1	-10.8 14.6	-12.6 17.1	-10.2 14.6	-12.0 17.1	
220	-18.1 16.7	-20.5 19.5	-15.8 16.7	-18.2 19.5	-13.5 16.7	-15.9 19.5	-12.3 16.7	-14.7 19.5	-11.6 16.7	-14.0 19.5	
240	-20.2 18.8	-23.2 22.0	-17.6 18.8	-20.6 22.0	-15.1 18.8	-18.1 22.0	-13.8 18.8	-16.8 22.0	-13.0 18.8	-16.0 22.0	
260	-22.3 20.9	-25.8 24.4	-19.5 20.9	-23.1 24.4	-16.7 20.9	-20.3 24.4	-15.3 20.9	-18.9 24.4	-14.5 20.9	-18.0 24.4	
280	-24.4 23.0	-28.4 26.9	-21.3 23.0	-25.4 26.9	-18.3 23.0	-22.4 26.9	-16.8 23.0	-20.9 26.9	-15.9 23.0	-20.0 26.9	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-SP SDV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-SP SDV 2M16-0210	Section A-A V _{Rd,A} [kN]		Section B-B for selected shear load V _{Rd,B} [kN]								M16
Design values	43.9	43.9	25.0	25.0	30.0	30.0	40.0	40.0	43.9	43.9	
Element height [mm]	M _{Rd,A} [kNm]		M _{Rd,B} [kNm]								
180	-13.9 12.5	-15.1 14.7	-9.3 12.5	-10.6 14.7	-8.4 12.5	-9.7 14.7	-6.6 12.5	-7.8 14.7	-5.8 12.5	-7.1 14.7	
200	-16.0 14.6	-17.8 17.1	-10.8 14.6	-12.6 17.1	-9.8 14.6	-11.6 17.1	-7.7 14.6	-9.6 17.1	-6.9 14.6	-8.7 17.1	
220	-18.1 16.7	-20.5 19.5	-12.3 16.7	-14.7 19.5	-11.2 16.7	-13.6 19.5	-8.9 16.7	-11.3 19.5	-8.0 16.7	-10.4 19.5	
240	-20.2 18.8	-23.2 22.0	-13.8 18.8	-16.8 22.0	-12.5 18.8	-15.5 22.0	-10.0 18.8	-13.0 22.0	-9.0 18.8	-12.0 22.0	
260	-22.3 20.9	-25.8 24.4	-15.3 20.9	-18.9 24.4	-13.9 20.9	-17.5 24.4	-11.1 20.9	-14.7 24.4	-10.1 20.9	-13.6 24.4	
280	-24.4 23.0	-28.4 26.9	-16.8 23.0	-20.9 26.9	-15.3 23.0	-19.4 26.9	-12.3 23.0	-16.4 26.9	-11.1 23.0	-15.2 26.9	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-SP SDV 2M22-0208	Section A-A V _{Rd,A} [kN]		Section B-B for selected shear load V _{Ed,B} [kN]								M22
Design values	28.1	28.1	10.0	10.0	20.0	20.0	25.0	25.0	28.1	28.1	
Element height [mm]	M _{Rd,A} [kNm]		M _{Rd,B} [kNm]								
180	-27.4 16.1	-29.5 18.8	-25.6 16.1	-27.7 18.8	-23.9 16.1	-26.0 18.8	-23.0 16.1	-25.1 18.8	-22.4 16.1	-24.5 18.8	
200	-32.5 18.7	-35.0 22.0	-30.5 18.7	-33.0 22.0	-28.4 18.7	-30.9 22.0	-27.4 18.7	-29.9 22.0	-26.8 18.7	-29.3 22.0	
220	-37.1 21.5	-40.4 25.2	-34.8 21.5	-38.2 25.2	-32.6 21.5	-35.9 25.2	-31.4 21.5	-34.8 25.2	-30.7 21.5	-34.1 25.2	
240	-41.4 24.2	-45.7 28.4	-38.9 24.2	-43.2 28.4	-36.4 24.2	-40.7 28.4	-35.2 24.2	-39.5 28.4	-34.4 24.2	-38.7 28.4	
260	-45.6 26.9	-50.3 31.6	-42.9 26.9	-47.5 31.6	-40.1 26.9	-44.8 31.6	-38.8 26.9	-43.4 31.6	-37.9 26.9	-42.6 31.6	
280	-49.7 29.7	-54.7 34.8	-46.8 29.7	-51.8 34.8	-43.9 29.7	-48.9 34.8	-42.4 29.7	-47.4 34.8	-41.5 29.7	-46.5 34.8	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-SP SDV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 ≥ C25/30



HIT-SP SDV 2M22-0210	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M22
Design values	43.9	43.9	25.0	25.0	30.0	30.0	40.0	40.0	43.9	43.9	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-27.4 16.1	-29.5 18.8	-23.0 16.1	-25.1 18.8	-22.1 16.1	-24.2 18.8	-20.3 16.1	-22.4 18.8	-19.6 16.1	-21.7 18.8	
200	-32.5 18.7	-35.0 22.0	-27.4 18.7	-29.9 22.0	-26.4 18.7	-28.9 22.0	-24.4 18.7	-26.9 22.0	-23.6 18.7	-26.1 22.0	
220	-37.1 21.5	-40.4 25.2	-31.4 21.5	-34.8 25.2	-30.3 21.5	-33.7 25.2	-28.0 21.5	-31.4 25.2	-27.2 21.5	-30.5 25.2	
240	-41.4 24.2	-45.7 28.4	-35.2 24.2	-39.5 28.4	-33.9 24.2	-38.3 28.4	-31.4 24.2	-35.8 28.4	-30.5 24.2	-34.8 28.4	
260	-45.6 26.9	-50.3 31.6	-38.8 26.9	-43.4 31.6	-37.4 26.9	-42.1 31.6	-34.7 26.9	-39.4 31.6	-33.6 26.9	-38.3 31.6	
280	-49.7 29.7	-54.7 34.8	-42.4 29.7	-47.4 34.8	-41.0 29.7	-46.0 34.8	-38.0 29.7	-43.1 34.8	-36.9 29.7	-41.9 34.8	

Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-SP SDV 2M22-0212	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M22
Design values	59.0	59.0	40.0	40.0	50.0	50.0	55.0	55.0	59.0	59.0	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-27.4 16.1	-29.5 18.8	-20.3 16.1	-22.4 18.8	-18.5 16.1	-20.6 18.8	-17.6 16.1	-19.7 18.8	-16.9 16.1	-19.0 18.8	
200	-32.5 18.7	-35.0 22.0	-24.4 18.7	-26.9 22.0	-22.4 18.7	-24.9 22.0	-21.4 18.7	-23.9 22.0	-20.6 18.7	-23.1 22.0	
220	-37.1 21.5	-40.4 25.2	-28.0 21.5	-31.4 25.2	-25.8 21.5	-29.2 25.2	-24.7 21.5	-28.0 25.2	-23.8 21.5	-27.1 25.2	
240	-41.4 24.2	-45.7 28.4	-31.4 24.2	-35.8 28.4	-28.9 24.2	-33.3 28.4	-27.7 24.2	-32.0 28.4	-26.7 24.2	-31.0 28.4	
260	-45.6 26.9	-50.3 31.6	-34.7 26.9	-39.4 31.6	-32.0 26.9	-36.6 31.6	-30.6 26.9	-35.3 31.6	-29.5 26.9	-34.2 31.6	
280	-49.7 29.7	-54.7 34.8	-38.0 29.7	-43.1 34.8	-35.1 29.7	-40.1 34.8	-33.7 29.7	-38.7 34.8	-32.5 29.7	-37.5 34.8	


Load bearing capacity values for further types can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV

Product specifications HIT-HP/SP SDV-2M16


HIT-HP/SP SDV-2M16-0208 with installation aid

Section



- ① Tension bar
- ② Compression bar
- ③ Shear bar
- ④ Constructive installation rebar
- ⑤ Installation aid


Plan view



Dimensions in [mm]


HIT-HP/SP SDV-2M16-0210 with installation aid

Section



- ① Tension bar
- ② Compression bar
- ③ Shear bar
- ④ Constructive installation rebar
- ⑤ Installation aid

Plan view



Dimensions in [mm]


HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV


Product specifications HIT-HP/SP SDV-2M22

HIT-HP/SP SDV-2M22-0208 and HIT-HP/SP SDV-2M22-0210 with installation aid

Section




Plan view




HIT-HP/SP SDV-2M22-0212 with installation aid

Section




Plan view



HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV


On-site reinforcement HIT-HP/SP SDV-2M16

Section



Plan view

Figure: Overlap with on-site reinforcement



Position ①: $\geq 2\phi 14$; The length of the bars is derived from the tension bar overlap according to the structural design plans.

Position ②: $\geq 2\phi 14$; Only required for lifting moments.

The length of the bars is derived from the tension bar overlap according to the structural design plans.



On-site reinforcement according to the structural engineer's specifications.




Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV


On-site reinforcement HIT-HP/SP SDV-2M22

Section



Plan view

Figure: Overlap with on-site reinforcement




Position ①: $\geq 4\phi 14$; The length of the bars is derived from the tension bar overlap according to the structural design plans.

Position ②: $\geq 4\phi 14$; Only required for lifting moments.

Number, diameter and length of the bars according to the structural design plans.

Position ③: Stirrups $\geq 20\phi 6$; spacing $s = 80$ mm



Dimensions, stirrups (20 at $\phi 6$ mm)
Dimensions in [mm]



Stirrup layout according to EN 1992-1-1; 8.7.4.2



Constructive reinforcement for the free slab edge
in accordance with EN 1992-1-1

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV


Deformation

For the HIT-HP/SP SDV elements, the torsional deformations resulting from elastic formwork deformation in the insulation/load inducement joint area α_M are assumed due to a standard effective moment of $M_{Ed} = 1 \text{ kNm}$.

The required camber to compensate for elastic deformations of the connected steel structure can be approximated as follows:

$$\ddot{u} = \alpha_M \cdot l_k \cdot M_{Ed}$$

with $\ddot{u}$ = Camber [mm]
 α_M = Torque resulting from $M_{Ed} = 1 \text{ kNm}$;
 Table values in [%/kNm]
 l_k = Span distance, cantilever beam [m]
 M_{Ed} = Design value of the effective moments [kNm]
 at serviceability limit state (SLS)



L = cantilever length [m]

l_k = Span distance, cantilever beam [m]


Other deformation factors resulting from deformation of the connected steel structure must be considered by the structural engineer when determining the overall camber. The α_M values [%/kNm] in the following table are in accordance with approval no. Z-15.7-336

HIT-HP SDV		
Element height h [mm]	HP SDV-2M16-0208 HP SDV-2M16-0210	HP SDV-2M22-0208 HP SDV-2M22-0210 HP SDV-2M22-0212
180	0.885	0.572
200	0.639	0.407
220	0.483	0.305
240	0.378	0.236
260	0.304	0.189
280	0.249	0.154

HIT-SP SDV		
Element height h [mm]	SP SDV-2M16-0208 SP SDV-2M16-0210	SP SDV-2M22-0208 SP SDV-2M22-0210 SP SDV-2M22-0212
180	1.003	0.639
200	0.724	0.455
220	0.547	0.340
240	0.428	0.264
260	0.344	0.211
280	0.282	0.172

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV


Axial spacing



HIT Type	axial spacing $e_a \geq$ [mm]
HIT-HP SDV	250*
HIT-SP SDV	250*

*Custom elements with smaller spacings on request


Edge distance



HIT Type	Distance e_R [mm]
HIT-HP SDV-2M16-0208	11
HIT-HP SDV-2M16-0210	22
HIT-HP SDV-2M22-0208	11
HIT-HP SDV-2M22-0210	22
HIT-HP SDV-2M22-0212	33
HIT-SP SDV-2M16-0208	11
HIT-SP SDV-2M16-0210	22
HIT-SP SDV-2M22-0208	11
HIT-SP SDV-2M22-0210	22
HIT-SP SDV-2M22-0212	33

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV



Distance from an outer corner



HIT Type	Distance e_E [mm]
HIT-HP SDV-2M16-0208	11
HIT-HP SDV-2M16-0210	22
HIT-HP SDV-2M22-0208	11
HIT-HP SDV-2M22-0210	22
HIT-HP SDV-2M22-0212	33
HIT-SP SDV-2M16-0208	11
HIT-SP SDV-2M16-0210	22
HIT-SP SDV-2M22-0208	11
HIT-SP SDV-2M22-0210	22
HIT-SP SDV-2M22-0212	33

Height-offset for an outer corner

To install the HIT-SDV elements at an external corner, it is necessary to offset the installation height of the elements. The required height offset is achieved using 20 mm insulation strips (not included).




HIT-SDV 2M22: No tolerances are considered in the 20 mm height offset. We therefore recommend an offset of 25 mm for these types.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SDV, HIT-SP SDV


Installation instructions concrete



- 1 Installing the bottom reinforcement layer**
(example, mesh reinforcement).
Installing the HIT Element from above.



Install the HIT Element with increased accuracy as the steel construction is post-installed!




- 2 Accurate installation**



Ensure installation is exactly horizontal and vertical!




Ensure the formwork is installed at the correct height!



- 3 Checking horizontal and vertical alignment**


The included (wood) templates are used to precisely align the elements; the overhanging edges can be used to fix to the on-site formwork as required.

Alternative: Make installation aids on-site (for example, in wood or U-profiles). Use the supplied installation aids or alternatively the HALFEN drilling templates to transfer the drill hole sizes and element distances to the on-site made installation aids.



- 4 Installing the formwork**

- a** Concreting directly against the formwork



- b** Concreting directly against the insulation



A free drilling template (.pdf file) is available at:

► www.halfen.com ► Product Ranges ► Construction
► Reinforcement systems ► HIT Steel to Concrete Connector ► Product Information ► Installation Instructions


HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SDV, HIT-SP SDV

Installation in concrete


5a HIT-HP/SP SDV-2M16



Section view



Plan view



5 Installing the on-site reinforcement

a Installing the on-site reinforcement for HIT-HP/SP SDV-2M16



On-site reinforcement must be placed as specified by the structural engineer.




Structural reinforcement of the slab free edge according to EN 1992-1-1


5b HIT-HP/SP SDV-2M22



Section view



Plan view



b Installing the on-site reinforcement for HIT-HP/SP SDV-2M22



On-site reinforcement must be placed as specified by the structural engineer.




Structural reinforcement of the slab free edge according to EN 1992-1-1



Stirrup layout in accordance with EN 1992-1-1; 8.7.4.2

6



6 Pouring the concrete




To ensure the HIT units are not displaced, ensure the concrete is poured and compacted evenly.

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV


2

- › Element for connecting steel constructions to reinforced concrete structures
- › Transfer of negative bending moments and positive shear loads

TYPE TESTED



HIT-HP SMV – High Performance with 80 mm insulation
HIT-SP SMV – Superior Performance with 120 mm insulation



Application: Cantilever balcony

Contents	Type	Page
Load capacity range	HIT-HP SMV, HIT-SP SMV	30
Load capacity values	HIT-HP SMV, HIT-SP SMV	31
Product description	HIT-HP SMV, HIT-SP SMV	33
On-site connecting reinforcement	HIT-HP SMV, HIT-SP SMV	34
Deformation	HIT-HP SMV, HIT-SP SMV	35
Axial spacing	HIT-HP SMV, HIT-SP SMV	36
Installation instructions	HIT-HP SMV, HIT-SP SMV	38

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV

Load capacity range

Combinations of one moment and two shear load ranges are available. The following combinations of tension bars, anchor head compression bars and shear load bars are available for HIT-HP 80 mm and HIT-SP 120 mm insulation thickness.

Element width B = 25 cm

Number and diameter of the connection bolts; balcony side	Number and diameter of the tension bars; main slab	Number and diameter of the shear load bars	
		2 Ø8	2 Ø10
2M16	2Ø14	•	•

See the following pages for load capacity values for selected elements

• = HP and SP

Basic types – ordering examples

Ordering example

HIT-HP	SMV	-	2M16	-	0208	-	18
HIT-SP	SMV	-	2M16	-	0210	-	28
↓	↓	↓	↓	↓	↓	↓	↓
①	②	③	④	⑤	⑥		

Type designation

- ① Product group
- ② Joint spacing 80 mm (HP) or 120 mm (SP)
- ③ Connection type
- ④ Moment load range
- ⑤ Shear load range
- ⑥ Element height [cm]



CUSTOM SOLUTIONS

HALFEN HIT Insulated connections

Our technical support team is available if a custom solution is required for your project.
Contact details: → see back cover of catalogue

Technical data

Element description HIT-HP/HIT-SP	Possible Element height h [mm]	Balcony side	Main slab side				min. concrete cover slab side [mm]	
		Thread	Tension rods [mm]	Compression rods	Shear load rods [mm]	Stirrups [mm]	C _{v,top}	C _{v,bottom}
SMV-2M16-0208	180–280	2 M16	2 Ø14	Anchor head	2 Ø 8	2 Ø 8	20	33
SMV-2M16-0210		2 M16	2 Ø14	Anchor head	2 Ø10	2 Ø 8	20	33

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 $\geq$ C25/30



HIT-HP SMV 2M16-0208	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M16
Design values	33.5	33.5	10.0	10.0	20.0	20.0	30.0	30.0	33.5	33.5	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-13.6	-15.1	-12.2	-13.7	-10.8	-12.3	-9.4	-10.9	-9.0	-10.5	
200	-16.0	-17.8	-14.4	-16.2	-12.8	-14.7	-11.3	-13.1	-10.7	-12.6	
220	-18.1	-20.5	-16.3	-18.8	-14.6	-17.0	-12.9	-15.3	-12.3	-14.7	
240	-20.2	-23.2	-18.3	-21.3	-16.4	-19.4	-14.5	-17.5	-13.8	-16.8	
260	-22.3	-25.8	-20.2	-23.8	-18.1	-21.7	-16.1	-19.6	-15.3	-18.9	
280	-24.4	-28.4	-22.1	-26.2	-19.9	-24.0	-17.7	-21.7	-16.9	-21.0	

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-HP SMV 2M16-0210	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M16
Design values	52.3	52.3	30.0	30.0	40.0	40.0	50.0	50.0	52.3	52.3	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-13.6	-15.1	-9.4	-10.9	-8.1	-9.6	-6.7	-8.2	-6.3	-7.8	
200	-16.0	-17.8	-11.3	-13.1	-9.7	-11.6	-8.1	-10.0	-7.8	-9.6	
220	-18.1	-20.5	-12.9	-15.3	-11.1	-13.6	-9.4	-11.8	-9.0	-11.4	
240	-20.2	-23.2	-14.5	-17.5	-12.6	-15.6	-10.7	-13.7	-10.2	-13.2	
260	-22.3	-25.8	-16.1	-19.6	-14.0	-17.6	-11.9	-15.5	-11.5	-15.0	
280	-24.4	-28.4	-17.7	-21.7	-15.4	-19.5	-13.2	-17.3	-12.7	-16.8	

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-SP SMV

Resistance at ultimate load capacity



Shear capacity / Moment bearing capacity

Concrete strength: C20/25 $\geq$ C25/30



HIT-SP SMV 2M16-0208	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M16
Design values	28.1	28.1	10.0	10.0	20.0	20.0	25.0	25.0	28.1	28.1	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-13.6	-15.1	-11.8	-13.3	-10.0	-11.5	-9.1	-10.6	-8.5	-10.0	
200	-16.0	-17.8	-13.9	-15.7	-11.8	-13.7	-10.8	-12.6	-10.2	-12.0	
220	-18.1	-20.5	-15.8	-18.2	-13.5	-15.9	-12.3	-14.7	-11.6	-14.0	
240	-20.2	-23.2	-17.6	-20.6	-15.1	-18.1	-13.8	-16.8	-13.0	-16.0	
260	-22.3	-25.8	-19.5	-23.1	-16.7	-20.3	-15.3	-18.9	-14.5	-18.0	
280	-24.4	-28.4	-21.3	-25.4	-18.3	-22.4	-16.8	-20.9	-15.9	-20.0	

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.

HIT-SP SMV 2M16-0210	Section A-A $V_{Rd,A}$ [kN]		Section B-B for selected shear load $V_{Rd,B}$ [kN]								M16
Design values	43.9	43.9	25.0	25.0	30.0	30.0	40.0	40.0	43.9	43.9	
Element height [mm]	$M_{Rd,A}$ [kNm]		$M_{Rd,B}$ [kNm]								
180	-13.6	-15.1	-9.1	-10.6	-8.2	-9.7	-6.3	-7.8	-5.6	-7.1	
200	-16.0	-17.8	-10.8	-12.6	-9.8	-11.6	-7.7	-9.6	-6.9	-8.7	
220	-18.1	-20.5	-12.3	-14.7	-11.2	-13.6	-8.9	-11.3	-8.0	-10.4	
240	-20.2	-23.2	-13.8	-16.8	-12.5	-15.5	-10.0	-13.0	-9.0	-12.0	
260	-22.3	-25.8	-15.3	-18.9	-13.9	-17.5	-11.1	-14.7	-10.1	-13.6	
280	-24.4	-28.4	-16.8	-20.9	-15.3	-19.4	-12.3	-16.4	-11.1	-15.2	

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.


HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SMV, HIT-SP SMV


Product description

HIT-HP/SP SMV-2M16-0208 with installation aid

Section




Plan view




Dimensions in [mm]

HIT-HP/SP SMV-2M16-0210 with installation aid

Section



Plan view




Dimensions in [mm]


HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV

On-site connecting reinforcement


Section – On-site cast concrete



Section – Semi-precast slab



Plan view – On-site cast concrete



Position ①: $\geq \varnothing 14$; The bar lengths are defined by the tension bar overlap as specified in the structural design plans

Position ②: $2\varnothing 8$; included in the element

Figures: Overlap with the on-site connecting reinforcement



On-site reinforcement according to the structural engineer's specifications.



Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal min. 1 $\varnothing 8$ mm close to the anchor heads

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV


Deformation

For the HIT-HP/SP SDV elements, the torsional deformations resulting from elastic girder deformation in the insulation/load inducement joint area α_M are assumed due to a standard effective moment $M_{Ed} = 1 \text{ kNm}$.

The required camber to compensate for elastic deformations of the connected steel structure can be approximated as follows:

$$\ddot{u} = \alpha_M \cdot l_k \cdot M_{Ed}$$

with $\ddot{u}$ = Camber [mm]
 α_M = Torque resulting from $M_{Ed} = 1 \text{ kNm}$;
 Table values in [%/kNm]
 l_k = Span distance of cantilever [m]
 M_{Ed} = Design value of the effective moment [kNm]
 at serviceability limit state (SLS)



Other deformation factors resulting from deformation of the connected steel structure must be considered by the structural engineer when determining the overall camber.

The α_M values [%/kNm] in the following table are in accordance with approval no. Z-15.7-336.

HIT-HP SMV


α_M [%/kNm] for element height h [mm]	HP SDV-2M16-0208	HP SDV-2M16-0210
180	0.604	0.604
200	0.436	0.436
220	0.330	0.330
240	0.258	0.258
260	0.207	0.207
280	0.170	0.170

HIT-SP SMV

α_M [%/kNm] for element height h [mm]	SP SMV-2M16-0208	SP SMV-2M16-0210
180	0.722	0.722
200	0.521	0.521
220	0.394	0.394
240	0.308	0.308
260	0.248	0.248
280	0.203	0.203


HALFEN HIT STEEL TO CONCRETE CONNECTOR
HIT-HP SMV, HIT-SP SMV

Axial spacing



HIT Type	Axial spacing $e_a \geq$ [mm]
HIT-HP SMV-2M16-0208	295
HIT-HP SMV-2M16-0210	295
HIT-SP SMV-2M16-0208	295
HIT-SP SMV-2M16-0210	295


Edge distance



HIT Type	Edge distance e_R [mm]
HIT-HP SMV-2M16-0208	22.5
HIT-HP SMV-2M16-0210	22.5
HIT-SP SMV-2M16-0208	22.5
HIT-SP SMV-2M16-0210	22.5

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV



Distance from an outer corner



HIT Type	Axial spacing e_E [mm]
HIT-HP SMV-2M16-0208	22.5
HIT-HP SMV-2M16-0210	22.5
HIT-SP SMV-2M16-0208	22.5
HIT-SP SMV-2M16-0210	22.5


Height offset for an outer corner

To install the HIT-SMV elements at an external corner, it is necessary to offset the installation height of the elements. The required height offset is achieved using 20 mm insulation strips (not included).



HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV


Installation in concrete



- 1 Installing the bottom reinforcement layer**
(example, mesh reinforcement).
Installing the HIT-Element from above.



Install the HIT Element with increased accuracy
for post-installed steel elements!




- 2 Accurate installation**



Ensure installation is exactly horizontal and vertical!




Ensure the formwork is installed at the correct
height!



- 3 Checking horizontal and vertical alignment**


The included (wood) installation aids are used to precisely align the elements; the overhanging edges can be used to fix to the on-site formwork as required.

Alternative: Make installation aids on-site (for example, in wood or U-profiles). Use the supplied installation aids or alternatively the HALFEN drilling templates to transfer the drill hole sizes and element distances to the on-site made installation aids.



- 4 Installing the formwork**

- a** Concreting directly against the formwork



- b** Concreting directly against the insulation




A free drilling template (.pdf file) is available at:

► www.halfen.com ► Product Ranges ► Construction
► Reinforcement systems ► HIT Steel to Concrete Connector ► Product Information ► Installation Instructions

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SMV, HIT-SP SMV

Installation in concrete




5 Installing the on-site reinforcement



On-site reinforcement must be placed as specified by the structural engineer.



Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal, min. 1 Ø8 mm, close to the anchor heads




6 Installing the on-site reinforcement for semi-precast elements



On-site reinforcement must be placed as specified by the structural engineer.



Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal, min. 1 Ø8 mm, close to the anchor heads



7 Pouring the concrete





To ensure the HIT units are not displaced, ensure the concrete is poured and compacted evenly.


HALFEN HIT STEEL TO CONCRETE CONNECTOR **HIT-HP SZV, HIT-SP SZV**

- 3
- Element for connecting supported steel constructions to reinforced concrete components
 - Transfer of positive shear loads

TYPE TESTED



HIT-HP SZV - High Performance with 80 mm insulation
HIT-SP SZV - Superior Performance with 120 mm insulation



Application: Simply supported balcony slabs on columns

Contents	Type	Page
Load capacity range	HIT-HP SZV, HIT-SP SZV	41
Load capacity values	HIT-HP SZV, HIT-SP SZV	42
Product description	HIT-HP SZV, HIT-SP SZV	43
On-site connecting reinforcement	HIT-HP SZV, HIT-SP SZV	44
Axial spacing	HIT-HP SZV, HIT-SP SZV	45
Installation instructions	HIT-HP SZV, HIT-SP SZV	47

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SZV, HIT-SP SZV

Load capacity range

Combinations of three shear load capacities are available. Anchor headed compression elements are used in the concrete slab. Following combinations of shear load bars are possible for insulation thicknesses of HIT-HP 80mm and HIT-SP 120mm.

Element width B = 25 cm			
Number and diameter of the connection bolts, balcony side	Number and diameter of the shear load bars		
	2 Ø8	2 Ø10	2 Ø12
2M16	•	•	•

See the following pages for load capacity values for selected elements. • = HP and SP

Basic types – Ordering example

Ordering example

HIT-HP	SZV	- 0208	- 18
HIT-SP	SZV	- 0212	- 28
↓	↓	↓	↓
①	②	③	④

Type designation

- ① Product group
- ② Joint spacing 80 mm (HP) or 120 mm (SP)
- ③ Connection type
- ④ Shear load range
- ⑤ Element height [cm]



CUSTOM SOLUTIONS

HALFEN HIT Insulated connections

Our technical support team is available if a custom solution is required for your project.

Contact details: → see back cover of catalogue

Technical data

Element description HIT-HP/HIT-SP	Possible element height h [mm]	Balcony side	Main slab side			min. concrete cover slab side [mm]	
		Thread	Compression bars	Shear load bars [mm]	Stirrups [mm]	C _{v,top}	C _{v,bottom}
SZV-0208	180–280	2M16	Anchor head	2 Ø 8	2 Ø8	≥ 20	33
SZV-0210		2M16	Anchor head	2 Ø10	2 Ø8	≥ 20	33
SZV-0212		2M16	Anchor head	2 Ø12	2 Ø8	≥ 20	33

HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SZV, HIT-SP SZV

Resistance at ultimate load capacity



Shear load capacity

Concrete strength: C20/25 $\geq$ C25/30



HIT-HP SZV	Section A-A $V_{Rd,A}$ [kN]				M16
Design values	HP SZV-0208		HP SZV-0210		HP SZV-0212
Element height 180–280 mm	33.5	33.5	52.3	52.3	75.3

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.



Shear load capacity

Concrete strength: C20/25 $\geq$ C25/30



HIT-SP SZV	Section A-A $V_{Rd,A}$ [kN]				M16
Design values	SP SZV-0208		SP SZV-0210		SP SZV-0212
Element height 180–280 mm	28.1	28.1	43.9	43.9	56.8

Load bearing capacity values for concrete strength C30/37 can be found in the type tests at www.halfen.com or on request. See back cover for contact information.


HALFEN HIT STEEL TO CONCRETE CONNECTOR

HIT-HP SZV, HIT-SP SZV


Product description

HIT-HP/SP SZV-2M16-0208 with installation aid

Section



Plan view




- ① Shear load bars
- ② Pressure bearing
- ③ Stirrups
- ④ Constructive installation rebar
- ⑤ Installation aid


Dimensions in [mm]

HIT-HP/SP SZV-2M16-0210 with installation aid

Section



Plan view




- ① Shear load bars
- ② Pressure bearing
- ③ Stirrups
- ④ Constructive installation rebar
- ⑤ Installation aid

Dimensions in [mm]

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SZV, HIT-SP SZV


On-site reinforcement

Section – On-site cast concrete




Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal, min. 1 Ø8 mm, close to the anchor heads

Section – semi-precast element




On-site reinforcement according to the structural engineer's specifications.

Plan view – On-site cast concrete




HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SZV, HIT-SP SZV

Axial spacing



HIT Type	Axial spacing e_a [mm]
HIT-HP SZV-0208	250
HIT-HP SZV-0210	
HIT-HP SZV-0212	
HIT-SP SZV-0208	
HIT-SP SZV-0210	
HIT-SP SZV-0212	


Edge distance



HIT Type	Distance e_R [mm]
HIT-HP SZV-0208	11
HIT-HP SZV-0210	22
HIT-HP SZV-0212	22
HIT-SP SZV-0208	11
HIT-SP SZV-0210	22
HIT-SP SZV-0212	22

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SZV, HIT-SP SZV



Distance from a outer corner



HIT Type	Distance $e_E \geq$ [mm]
HIT-HP SZV-0208	11
HIT-HP SZV-0210	22
HIT-HP SZV-0212	22
HIT-SP SZV-0208	11
HIT-SP SZV-0210	22
HIT-SP SZV-0212	22


Height-offset for an outer corner

To install the HIT-SZV elements at an external corner, it is necessary to offset the installation height of the elements. The required height offset is achieved using 20 mm insulation strips (not included).



HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SZV, HIT-SP SZV


Installation in concrete



1 Installing the bottom reinforcement layer (example, mesh reinforcement). Installing the HIT-Element from above.



Install the HIT Element with increased accuracy if the steel construction is to be post-installed!




2 Accurate installation



Ensure installation is exactly horizontal and vertical!




Ensure the formwork is installed at the correct height!



3 Checking horizontal and vertical alignment


The included (wood) templates are used to precisely align the elements; the overhanging edges can be used to fix to the on-site formwork as required.

Alternative: Make installation aids on-site (for example, in wood or U-profiles). Use the supplied installation aids or alternatively the HALFEN drilling templates to transfer the drill hole sizes and element distances to the on-site made installation aids.



4 Installing the formwork

a Concreting directly against the formwork



b Concreting directly against the insulation




A free drilling template (.pdf file) is available at:

► www.halfen.com ► Product Ranges ► Construction
► Reinforcement systems ► HIT Steel to Concrete Connector ► Product Information ► Installation Instructions

HALFEN HIT STEEL TO CONCRETE CONNECTOR HIT-HP SZV, HIT-SP SZV

Installation in concrete




5 Installation of the on-site reinforcement



On-site reinforcement according to the structural engineer's specifications.



Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal, min. 1 Ø8 mm, close to the anchor heads.




6 Installing the on-site reinforcement for a semi-precast slab



On-site reinforcement according to the structural engineer's specifications.



Constructive reinforcement for the free slab edge in accordance with EN 1992-1-1, horizontal, min. 1 Ø8 mm, close to the anchor heads.



7 Pouring the concrete



To ensure the HIT elements are not displaced, ensure the concrete is poured and compacted evenly.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements

4

› Design and installation of connected elements



Contents	Page
On-site facing plate with notch	50
Connecting support elements	52
Installation and height adjustment	53
Installation of structural steel elements	54
Expansion joint spacings	55



HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements

On-site facing plate with notch

On-site facing plates with notch are required to fasten and support connected elements to the HIT Insulated connection. The facing plates thickness t_s is specified by the

structural engineer keeping within the stipulated limits. The maximum thickness $t_{s,max}$ of the facing plates depends on the available clamping length of the HIT element.



Dimensions in [mm]


Connection thread	Clamp length
M16	≤30 mm
M22	≤40 mm

On-site welded notch



Shear loads are transferred from the on-site facing plate through an on-site welded notch.

Specifications for the notch:

- $h_{min.notch} = 30 \text{ mm}$
- $b_{min.notch} = 50 \text{ mm}$
- $t_{notch} = 15 \text{ mm}$
- Steel grade, minimum strength $f_{yk} = 235 \text{ N/mm}^2$
- Weld seam $a_{w,min} = 4 \text{ mm}$, closed weld seam



Facing plate with welded notch




HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements

On-site facing plate with notch

Hole layout for HIT-SDV and HIT-SMV with M16 thread
(HIT-HP/SP SDV-2M16, HIT-HP/SP SMV-2M16)




The holes layout in the facing plate depends on the bar diameter and the height of the HIT element.


The slots allow the plate to move vertically by up to 10 mm. The facing plate dimensions are specified by the structural engineer, the distances between the slots and the outer edge of the facing plate must be verified.

The facing plate with its central notch is not designed for lifting-loads. The actual dimensions of the embedded HIT elements must be checked before manufacturing the facing plate to ensure a precise fit. On-site corrosion protection is only applied after all welding work has been finished.

Hole layout for HIT-SZV with M16 thread
(HIT-HP/SP SZV-2M16)



Hole layout for HIT-SMV with M22 thread
(HIT-HP/SP SDV-2M22, HIT-HP/SP SMV-2M22)



HIT-HP/SP	Connecting thread M16					
HIT Height h [mm]	180	200	220	240	260	280
z_i = hole spacing [mm]	113	133	153	173	193	213

HIT-HP/SP	Connecting thread M22					
HIT Height h [mm]	180	200	220	240	260	280
z_i = hole spacing [mm]	108	128	148	168	188	208

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements


Connected steel components

The shape and dimensions of the connected steel components are specified by the structural engineer.

Steel components; a minimum distance h_{LF} must be observed in the facing plate from the top flange to the upper-edge of

the upper slotted hole and from the lower-edge of the bottom slotted holes to the bottom flange.

The minimum spacing h_{LF} and a height tolerance of 10 mm provide the minimum dimension of the steel profiles.



Depending on the connection thread, the following min. steel profile sizes are recommended for the various HIT Element heights:

HIT-HP/SP	min h_{LF} = 25 mm			
SDV-2M16 SMV-2M16	IPE	HEA	HEB	HEM
180	200	220	220	220
200	220	240	240	240
220	240	260	260	260
240	270	280	280	280
260	300	300	300	300
280	300	320	320	320

HIT-HP/SP	min h_{LF} = 30 mm			
SDV-2M22	IPE	HEA	HEB	HEM
180	200	220	220	220
200	220	240	240	240
220	240	260	260	280
240	270	280	280	280
260	300	300	300	300
280	300	320	320	320

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements

Installation and height adjustment

Check the dimensions and positions of the connection threads (HIT Elements) on-site before attempting to install connected components. Checking the dimensions before manufacture, and before delivery of elements if these were constructed off-site is also recommended.

The facing plate design as in the figure on page 50 provides a vertical tolerance up to 10 mm in both direction.

Height adjustment is achieved using the pre-fitted angled slotted bracket; moving the facing plate horizontally (tap lightly with a hammer) causes a vertical movement of the facing plate.

To ensure a tolerance in both directions, a central alignment is recommended; see figure B.



The following should be checked before connecting steel elements to the HIT component:

- are the sizes and positions of the connection holes as specified?
- is the notch present on the facing plate?
- is the size and position of the notch as specified?

Figure A: Bolzen oben im Langloch ausgerichtet




Figure A: Threaded bolt positioned at the bottom of the slot




Figure A: Threaded bolt positioned at the centre of the slot







Figure A: Threaded bolt positioned at the top of the slot





The screw threads may be shortened; a minimum of two turns of the threads must remain visible after fixing any components.



Angled slotted bracket for M16 thread



Angled slotted bracket for M22 thread




Please observe the information on the label

Correct installation of the angled slotted bracket: bevelled edge at the top, HALFEN logo on the front.

HALFEN HIT STEEL TO CONCRETE CONNECTOR



Design and installation of the connected elements

Installing of steel components




1 Fixing of steel girders

Only use on-site end plates with notch




2 Please observe the information on the label

Correct orientation of the angled slotted bracket:
HALFEN logo is visible, bevelled edge at the top.



3 Fixing steel components


Attach to the top threads first,
then attach to the bottom threads.



4 Check the steel connection has been installed as planned

Check the gradient is in accordance with the design specifications! Check if the element is horizontally level or if the camber (where planned) is correct.

On-site reinforcement must be placed
as specified by the structural engineer.



5 Final adjustment, then tighten the nuts

The thread anchors may be shortened;
ensure **at least two turns** of the threads remain
visible after final installation.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Design and installation of the connected elements

Expansion joint spacings


Calculation of the allowable joint spacing is in accordance with Building Authority Approval no. Z-15.7-336 and is based on a balcony slab firmly fixed to steel supports. In this case, expansion joints must be provided in the exterior component.

The distance between the expansion joints must not exceed s_{joint} [m] for linear, cantilevered balcony slabs. Balcony designed for external corners, are limited to a maximum expansion joint spacing of $0.5 s_{\text{joint}}$ for each leg.

A limit of $0.5 s_{\text{joint}}$ per leg also applies for inner corners. s_{joint} refers to outer edge HIT to outer edge HIT. Overhang on the right and left can be included here.

If constructive measures are taken to allow expansion/contraction between the balcony slab and each steel beam – such as designing slotted holes in the cross beams – then expansion joints are not required.

Tension bar diameter in the insulation [mm]	s_{joint} max. expansion joint spacing [m]	
	HIT-HP (80 mm)	HIT-SP (120 mm)
M16	9.8	16.5
M22	7.9	13.3





HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

The illustration of the temperature field in the horizontal section through a ceiling slab, shown here as an isothermal curve, demonstrates the excellent insulating properties of the HIT Steel to concrete connectors.

These connectors form effective thermal separation of the

exterior balcony components. The good insulation stops the temperature sinking below the point of condensation preventing water damage. The efficient, building physic design also prevents cracks forming caused by thermal expansion of the metal balcony components.



Contents

Page

Key values for thermal bridgings	57
Key values for thermal bridges according to Building Authority Approval	58
Key values for thermal bridges for HIT-HP and masonry using ETICS	62
Key values for thermal bridges for HIT-SP and masonry using ETICS	63

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Key values for thermal bridges

Equivalent thermal conductivity λ_{eq}

Composite building elements — including the HIT insulated connection — consist of different building materials with different thermal conductivities.

A detailed analysis of this type of product can be very complex. To simplify the process, a homogeneous, cuboid substitute sample is assumed in the insulation joint, with the same dimensions. An equivalent thermal conductivity λ_{eq} is assigned to the substitute sample so that the total heat transfer of both systems is identical. The definition of the λ_{eq} values is based on meticulous three-dimensional thermal bridge calculations.

Calculation of the equivalent thermal conductivity is defined in Building Authority approval no. Z-15.7-336 issued by the DiBt (German Institute of Building Technology).

The λ_{eq} values cannot be used directly to calculate the primary energy demand of a building. The local thermal transfer coefficient χ can be determined using thermal bridge software, and therefore, the transmission losses can be calculated. In this case the thermal boundary conditions according to EN ISO 6946 and DIN 4108 annex 2 must be observed.

Heat transmission coefficient χ

Local thermal bridges are penetrations in the building envelope that can be referenced to a specific area. The heat loss resulting from these thermal bridges are defined using a local thermal transfer value χ . The χ values are therefore important variables for calculating the energy loss of local thermal bridges. The calculated values for a masonry wall using ETICS* can be found on page 62.

*ETICS External Thermal Insulation Composite System.




Figure: Cross section showing a HALFEN HIT element, connected to a (interior) concrete slab.

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal values according to Building Authority Approval

The thermal characteristic values for equivalent thermal conductivity λ_{eq} and equivalent thermal resistance R_{eq} have been calculated based on Building Authority

approval no. Z-15.7-336, for all HIT Steel to concrete connections with heights from 18 to 28 cm; see the tables on the following pages.

HIT Type	Height [mm]	Insulation thickness [mm]	Equivalent thermal conductivity λ_{eq} [W/(mK)]	Equivalent thermal resistance R_{eq} [m²K/W]
HIT-HP SDV-2M16-0208				
HIT-HP SDV-2M16-0208-18	180	80	0.314	0.255
HIT-HP SDV-2M16-0208-20	200	80	0.286	0.280
HIT-HP SDV-2M16-0208-22	220	80	0.263	0.304
HIT-HP SDV-2M16-0208-24	240	80	0.244	0.327
HIT-HP SDV-2M16-0208-26	260	80	0.228	0.350
HIT-HP SDV-2M16-0208-28	280	80	0.215	0.373
HIT-HP SDV-2M16-0210				
HIT-HP SDV-2M16-0210-18	180	80	0.333	0.240
HIT-HP SDV-2M16-0210-20	200	80	0.304	0.263
HIT-HP SDV-2M16-0210-22	220	80	0.279	0.286
HIT-HP SDV-2M16-0210-24	240	80	0.259	0.309
HIT-HP SDV-2M16-0210-26	260	80	0.242	0.331
HIT-HP SDV-2M16-0210-28	280	80	0.227	0.352
HIT-HP SDV-2M22-0208				
HIT-HP SDV-2M22-0208-18	180	80	0.531	0.151
HIT-HP SDV-2M22-0208-20	200	80	0.482	0.166
HIT-HP SDV-2M22-0208-22	220	80	0.441	0.181
HIT-HP SDV-2M22-0208-24	240	80	0.407	0.196
HIT-HP SDV-2M22-0208-26	260	80	0.379	0.211
HIT-HP SDV-2M22-0208-28	280	80	0.354	0.226
HIT-HP SDV-2M22-0210				
HIT-HP SDV-2M22-0210-18	180	80	0.551	0.145
HIT-HP SDV-2M22-0210-20	200	80	0.499	0.160
HIT-HP SDV-2M22-0210-22	220	80	0.457	0.175
HIT-HP SDV-2M22-0210-24	240	80	0.422	0.190
HIT-HP SDV-2M22-0210-26	260	80	0.392	0.204
HIT-HP SDV-2M22-0210-28	280	80	0.367	0.218
HIT-HP SDV-2M22-0212				
HIT-HP SDV-2M22-0212-18	180	80	0.575	0.139
HIT-HP SDV-2M22-0212-20	200	80	0.521	0.154
HIT-HP SDV-2M22-0212-22	220	80	0.477	0.168
HIT-HP SDV-2M22-0212-24	240	80	0.440	0.182
HIT-HP SDV-2M22-0212-26	260	80	0.409	0.196
HIT-HP SDV-2M22-0212-28	280	80	0.382	0.209

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal values according to Building Authority Approval

HIT Type	Height [mm]	Insulation thickness [mm]	Equivalent thermal conductivity λ_{eq} [W/(mK)]	Equivalent thermal resistance R_{eq} [m²K/W]
HIT-HP SMV-2M16-0208				
HIT-HP SMV-2M16-0208-18	180	80	0.314	0.255
HIT-HP SMV-2M16-0208-20	200	80	0.286	0.280
HIT-HP SMV-2M16-0208-22	220	80	0.263	0.304
HIT-HP SMV-2M16-0208-24	240	80	0.244	0.327
HIT-HP SMV-2M16-0208-26	260	80	0.228	0.350
HIT-HP SMV-2M16-0208-28	280	80	0.215	0.373
HIT-HP SMV-2M16-0210				
HIT-HP SMV-2M16-0210-18	180	80	0.333	0.240
HIT-HP SMV-2M16-0210-20	200	80	0.304	0.263
HIT-HP SMV-2M16-0210-22	220	80	0.279	0.286
HIT-HP SMV-2M16-0210-24	240	80	0.259	0.309
HIT-HP SMV-2M16-0210-26	260	80	0.242	0.331
HIT-HP SMV-2M16-0210-28	280	80	0.227	0.352
HIT-HP SZV-0208				
HIT-HP SZV-0208-18	180	80	0.202	0.396
HIT-HP SZV-0208-20	200	80	0.186	0.431
HIT-HP SZV-0208-22	220	80	0.172	0.465
HIT-HP SZV-0208-24	240	80	0.161	0.497
HIT-HP SZV-0208-26	260	80	0.151	0.528
HIT-HP SZV-0208-28	280	80	0.143	0.558
HIT-HP SZV-0210				
HIT-HP SZV-0210-18	180	80	0.222	0.360
HIT-HP SZV-0210-20	200	80	0.204	0.393
HIT-HP SZV-0210-22	220	80	0.189	0.424
HIT-HP SZV-0210-24	240	80	0.176	0.455
HIT-HP SZV-0210-26	260	80	0.165	0.484
HIT-HP SZV-0210-28	280	80	0.156	0.512
HIT-HP SZV-0212				
HIT-HP SZV-0212-18	180	80	0.247	0.324
HIT-HP SZV-0212-20	200	80	0.226	0.354
HIT-HP SZV-0212-22	220	80	0.209	0.383
HIT-HP SZV-0212-24	240	80	0.194	0.411
HIT-HP SZV-0212-26	260	80	0.182	0.439
HIT-HP SZV-0212-28	280	80	0.172	0.465

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal values according to Building Authority Approval

HIT Type	Height [mm]	Insulation thickness [mm]	Equivalent thermal conductivity λ_{eq} [W/(mK)]	Equivalent thermal resistance R_{eq} [m²K/W]
HIT-SP SDV-2M16-0208				
HIT-SP SDV-2M16-0208-18	180	120	0.314	0.382
HIT-SP SDV-2M16-0208-20	200	120	0.286	0.420
HIT-SP SDV-2M16-0208-22	220	120	0.263	0.456
HIT-SP SDV-2M16-0208-24	240	120	0.244	0.491
HIT-SP SDV-2M16-0208-26	260	120	0.228	0.525
HIT-SP SDV-2M16-0208-28	280	120	0.215	0.559
HIT-SP SDV-2M16-0210				
HIT-SP SDV-2M16-0210-18	180	120	0.333	0.360
HIT-SP SDV-2M16-0210-20	200	120	0.304	0.395
HIT-SP SDV-2M16-0210-22	220	120	0.279	0.430
HIT-SP SDV-2M16-0210-24	240	120	0.259	0.463
HIT-SP SDV-2M16-0210-26	260	120	0.242	0.496
HIT-SP SDV-2M16-0210-28	280	120	0.227	0.528
HIT-SP SDV-2M22-0208				
HIT-SP SDV-2M22-0208-18	180	120	0.531	0.226
HIT-SP SDV-2M22-0208-20	200	120	0.482	0.249
HIT-SP SDV-2M22-0208-22	220	120	0.441	0.272
HIT-SP SDV-2M22-0208-24	240	120	0.407	0.295
HIT-SP SDV-2M22-0208-26	260	120	0.379	0.317
HIT-SP SDV-2M22-0208-28	280	120	0.354	0.339
HIT-SP SDV-2M22-0210				
HIT-SP SDV-2M22-0210-18	180	120	0.551	0.218
HIT-SP SDV-2M22-0210-20	200	120	0.499	0.240
HIT-SP SDV-2M22-0210-22	220	120	0.457	0.262
HIT-SP SDV-2M22-0210-24	240	120	0.422	0.284
HIT-SP SDV-2M22-0210-26	260	120	0.392	0.306
HIT-SP SDV-2M22-0210-28	280	120	0.367	0.327
HIT-SP SDV-2M22-0212				
HIT-SP SDV-2M22-0212-18	180	120	0.575	0.209
HIT-SP SDV-2M22-0212-20	200	120	0.521	0.230
HIT-SP SDV-2M22-0212-22	220	120	0.477	0.252
HIT-SP SDV-2M22-0212-24	240	120	0.440	0.273
HIT-SP SDV-2M22-0212-26	260	120	0.409	0.293
HIT-SP SDV-2M22-0212-28	280	120	0.382	0.314

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal values according to Building Authority Approval

HIT Type	Height [mm]	Insulation thickness [mm]	Equivalent thermal conductivity λ_{eq} [W/(mK)]	Equivalent thermal resistance R_{eq} [m²K/W]
HIT-SP SMV-2M16-0208				
HIT-SP SMV-2M16-0208-18	180	120	0.314	0.382
HIT-SP SMV-2M16-0208-20	200	120	0.286	0.420
HIT-SP SMV-2M16-0208-22	220	120	0.263	0.456
HIT-SP SMV-2M16-0208-24	240	120	0.244	0.491
HIT-SP SMV-2M16-0208-26	260	120	0.228	0.525
HIT-SP SMV-2M16-0208-28	280	120	0.215	0.559
HIT-SP SMV-2M16-0210				
HIT-SP SMV-2M16-0210-18	180	120	0.333	0.360
HIT-SP SMV-2M16-0210-20	200	120	0.304	0.395
HIT-SP SMV-2M16-0210-22	220	120	0.279	0.430
HIT-SP SMV-2M16-0210-24	240	120	0.259	0.463
HIT-SP SMV-2M16-0210-26	260	120	0.242	0.496
HIT-SP SMV-2M16-0210-28	280	120	0.227	0.528
HIT-SP SZV-0208				
HIT-SP SZV-0208-18	180	120	0.202	0.594
HIT-SP SZV-0208-20	200	120	0.186	0.647
HIT-SP SZV-0208-22	220	120	0.172	0.697
HIT-SP SZV-0208-24	240	120	0.161	0.746
HIT-SP SZV-0208-26	260	120	0.151	0.793
HIT-SP SZV-0208-28	280	120	0.143	0.838
HIT-SP SZV-0210				
HIT-SP SZV-0210-18	180	120	0.222	0.540
HIT-SP SZV-0210-20	200	120	0.204	0.589
HIT-SP SZV-0210-22	220	120	0.189	0.636
HIT-SP SZV-0210-24	240	120	0.176	0.682
HIT-SP SZV-0210-26	260	120	0.165	0.726
HIT-SP SZV-0210-28	280	120	0.156	0.768
HIT-SP SZV-0212				
HIT-SP SZV-0212-18	180	120	0.247	0.486
HIT-SP SZV-0212-20	200	120	0.226	0.531
HIT-SP SZV-0212-22	220	120	0.209	0.575
HIT-SP SZV-0212-24	240	120	0.194	0.617
HIT-SP SZV-0212-26	260	120	0.182	0.658
HIT-SP SZV-0212-28	280	120	0.172	0.698


HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal bridge characteristic values for HIT-HP and wall masonry with ETICS*

The thermal bridge coefficients for the local heat transfer coefficients χ and the minimum surface temperature Θ_{si} as well as the temperature factor f_{Rsi} have been calculated for a wall construction using ETICS* and are available in the table.

*ETICS External Thermal Insulation Composite System.



Wall detail

Masonry with ETICS external thermal insulation composite system

Section details

Wall details

- 1 plaster (exterior)
- 2 insulation
- 3 load bearing wall
- 4 plaster (interior)

Floor details

- 5 Screed
- 6 footfall insulation
- 7 edge insulation strips
- 8 floor slab

$$U_{uninterrupted} = 0,193 \text{ W/(m}^2\text{K)}$$

HIT Type	Height [mm]	Insulation thickness [mm]	λ_{eq} [W/(mK)]	R_{eq} [m²K/W]	min. Θ_{si} [°C]	$f_{R,si}$ [-]	χ [W/K]
HIT-HP SDV-2M16-0208							
HIT-HP SDV-2M16-0208-20	200	80	0.286	0.280	18.710	0.948	0.115
HIT-HP SDV-2M16-0208-28	280	80	0.215	0.373	18.760	0.950	0.123
HIT-HP SDV-2M16-0210							
HIT-HP SDV-2M16-0210-20	200	80	0.304	0.263	18.680	0.947	0.121
HIT-HP SDV-2M16-0210-28	280	80	0.227	0.352	18.730	0.949	0.128
HIT-HP SDV-2M22-0210							
HIT-HP SDV-2M22-0210-20	200	80	0.499	0.160	18.400	0.936	0.168
HIT-HP SDV-2M22-0210-28	280	80	0.367	0.218	18.470	0.939	0.179
HIT-HP SDV-2M22-0212							
HIT-HP SDV-2M22-0212-20	200	80	0.521	0.154	18.360	0.934	0.175
HIT-HP SDV-2M22-0212-28	280	80	0.382	0.209	18.440	0.938	0.183
HIT-HP SMV-2M16-0208							
HIT-HP SMV-2M16-0208-20	200	80	0.286	0.280	18.710	0.948	0.115
HIT-HP SMV-2M16-0208-28	280	80	0.215	0.373	18.760	0.950	0.123
HIT-HP SMV-2M16-0210							
HIT-HP SMV-2M16-0210-20	200	80	0.304	0.263	18.680	0.947	0.121
HIT-HP SMV-2M16-0210-28	280	80	0.227	0.352	18.730	0.949	0.128
HIT-HP SZV-0208							
HIT-HP SZV-0208-20	200	80	0.186	0.431	18.920	0.957	0.083
HIT-HP SZV-0208-28	280	80	0.143	0.558	18.930	0.957	0.090
HIT-HP SZV-0210							
HIT-HP SZV-0210-20	200	80	0.204	0.393	18.880	0.955	0.089
HIT-HP SZV-0210-28	280	80	0.156	0.512	18.900	0.956	0.096
HIT-HP SZV-0212							
HIT-HP SZV-0212-20	200	80	0.226	0.354	18.840	0.954	0.095
HIT-HP SZV-0212-28	280	80	0.172	0.465	18.870	0.955	0.103

HALFEN HIT STEEL TO CONCRETE CONNECTOR

Building physics

Thermal bridge characteristic values for HIT-HP and wall masonry with ETICS

HIT Type	Height [mm]	Insulation thickness [mm]	λ_{eq} [W/(mK)]	R_{eq} [m²K/W]	min. θ_{si} [°C]	$f_{R,si}$ [-]	χ [W/K]
HIT-SP SDV-2M16-0208							
HIT-SP SDV-2M16-0208-20	200	120	0.286	0.420	18.910	0.956	0.806
HIT-SP SDV-2M16-0208-28	280	120	0.215	0.559	18.950	0.958	0.084
HIT-SP SDV-2M16-0210							
HIT-SP SDV-2M16-0210-20	200	120	0.304	0.395	18.890	0.956	0.085
HIT-SP SDV-2M16-0210-28	280	120	0.227	0.528	18.930	0.957	0.088
HIT-SP SDV-2M22-0210							
HIT-SP SDV-2M22-0210-20	200	120	0.499	0.240	18.640	0.946	0.126
HIT-SP SDV-2M22-0210-28	280	120	0.367	0.327	18.710	0.948	0.131
HIT-SP SDV-2M22-0212							
HIT-SP SDV-2M22-0212-20	200	120	0.521	0.230	18.620	0.945	0.130
HIT-SP SDV-2M22-0212-28	280	120	0.382	0.314	18.680	0.947	0.135
HIT-SP SMV-2M16-0208							
HIT-SP SMV-2M16-0208-20	200	120	0.286	0.420	18.910	0.956	0.806
HIT-SP SMV-2M16-0208-28	280	120	0.215	0.559	18.950	0.958	0.084
HIT-SP SMV-2M16-0210							
HIT-SP SMV-2M16-0210-20	200	120	0.304	0.395	18.890	0.956	0.085
HIT-SP SMV-2M16-0210-28	280	120	0.227	0.528	18.930	0.957	0.088
HIT-SP SZV-0208							
HIT-SP SZV-0208-20	200	120	0.186	0.647	19.070	0.963	0.055
HIT-SP SZV-0208-28	280	120	0.143	0.838	19.090	0.964	0.058
HIT-SP SZV-0210							
HIT-SP SZV-0210-20	200	120	0.204	0.589	19.050	0.962	0.059
HIT-SP SZV-0210-28	280	120	0.156	0.768	19.060	0.962	0.063
HIT-SP SZV-0212							
HIT-SP SZV-0212-20	200	120	0.226	0.531	19.010	0.960	0.065
HIT-SP SZV-0212-28	280	120	0.172	0.698	19.030	0.961	0.069

CONTACT HALFEN WORLDWIDE

HALFEN is represented by subsidiaries in the following countries, please contact us!

Austria	HALFEN Gesellschaft m.b.H. Leonard-Bernstein-Str. 10 1220 Wien	Phone: +43-1-259 6770 E-Mail: office@halfen.at Internet: www.halfen.at	
Belgium / Luxembourg	HALFEN N.V. Borkelstraat 131 2900 Schoten	Phone: +32-3-658 07 20 E-Mail: info@halfen.be Internet: www.halfen.be	Fax: +32-3-658 15 33
China	HALFEN Construction Accessories Distribution Co.Ltd. Room 601 Tower D, Vantone Centre No. A6 Chao Yang Men Wai Street Chaoyang District Beijing · P.R. China 100020	Phone: +86-10 5907 3200 E-Mail: info@halfen.cn Internet: www.halfen.cn	Fax: +86-10 5907 3218
Czech Republic	HALFEN s.r.o. Business Center Šafránková Šafránková 1238/1 155 00 Praha 5	Phone: +420-311-690 060 E-Mail: info@halfen.cz Internet: www.halfen.cz	Fax: +420-235-314 308
France	HALFEN S.A.S. 18, rue Goubet 75019 Paris	Phone: +33-1-445231 00 E-Mail: halfen@halfen.fr Internet: www.halfen.fr	Fax: +33-1-445231 52
Germany	HALFEN Vertriebsgesellschaft mbH Liebigstr. 14 40764 Langenfeld	Phone: +49-2173-970-0 E-Mail: info@halfen.de Internet: www.halfen.de	Fax: +49-2173-970 225
Italy	HALFEN S.r.l. Soc. Unipersonale Via F.lli Bronzetti N° 28 24124 Bergamo	Phone: +39-035-0760711 E-Mail: tecnico@halfen.it Internet: www.halfen.it	Fax: +39-035-0760799
Netherlands	HALFEN b.v. Oostermaat 3 7623 CS Borne	Phone: +31-74-267 14 49 E-Mail: info@halfen.nl Internet: www.halfen.nl	Fax: +31-74-267 26 59
Norway	HALFEN AS Postboks 2080 4095 Stavanger	Phone: +47-51 82 34 00 E-Mail: post@halfen.no Internet: www.halfen.no	
Poland	HALFEN Sp. z o.o. Ul. Obornicka 287 60-691 Poznan	Phone: +48-61-622 14 14 E-Mail: info@halfen.pl Internet: www.halfen.pl	Fax: +48-61-622 14 15
Spain	HALFEN IBERICA, S.L. Polígono Industrial Santa Ana c/ Ignacio Zuloaga 20 28522 Rivas-Vaciamadrid	Phone: +34 91 632 18 40 E-Mail: info@halfen.es Internet: www.halfen.es	Fax: +34 91 633 42 57
Sweden	Halfen AB Vädursgatan 5 412 50 Göteborg	Phone: +46-31-98 58 00 E-Mail: info@halfen.se Internet: www.halfen.se	Fax: +46-31-98 58 01
Switzerland	HALFEN Swiss AG Hertistrasse 25 8304 Wallisellen	Phone: +41-44-849 78 78 E-Mail: info@halfen.ch Internet: www.halfen.ch	Fax: +41-44-849 78 79
United Kingdom / Ireland	HALFEN Ltd. A1/A2 Portland Close Houghton Regis LU5 5AW	Phone: +44-1582-47 03 00 E-Mail: info@halfen.co.uk Internet: www.halfen.co.uk	Fax: +44-1582-47 03 04
United States of America	HALFEN USA Inc. PO Box 18687 San Antonio TX 78218	Phone: +1 800.423.91 40 E-Mail: info@halfenusa.com Internet: www.halfenusa.com	Fax: +1 877.683.4910
For countries not listed HALFEN International	HALFEN International GmbH Liebigstr. 14 40764 Langenfeld / Germany	Phone: +49-2173-970-0 E-Mail: info@halfen.com Internet: www.halfen.com	Fax: +49-2173-970-849

HALFEN is represented with sales offices and distributors worldwide. Please contact us: www.halfen.com

NOTES REGARDING THIS CATALOGUE

Technical and design changes reserved. The information in this publication is based on state-of-the-art technology at the time of publication. We reserve the right to make technical and design changes at any time. HALFEN GmbH shall not accept liability for the accuracy of the information in this publication or for any printing errors.

The HALFEN GmbH subsidiaries in Germany, France, the Netherlands, Austria, Poland, Switzerland and the Czech Republic are Quality Management certified according to **ISO 9001:2015**, Certificate no. 202384-2016-AQ-GER-DAKKS.

