

# LOW LEVEL ROOF EDGE PROTECTION



Our Low Level Roof Edge Protection system is designed to provide safe access and edge protection on low level roofs such as on a single garage roof or on a collection of flat roof units.

The system consists of one Easi-Dec platform with winged gates, 2 x 3m and 1 x 1.5m Body-Guard systems with adjustable extensions and 1 x demarcation handrail. The legs are adjustable from 2.34m to 2.9m.

The Level Roof Edge Protection provides cost effective protection when working on low level roofs. A standard 3m Body-Guard system with a 500mm adjustable fixed extender on either side can provide 4m total coverage. Systems can accommodate different width roofs and can be installed as a straight run to provide edge protection for specific roof areas, or connected at right angles around the perimeter of the roof for complete collective protection.



## Technical Description

- Easi-Dec 2m Platform (winged gates) 2m to 3.590m (wing gate span)
- Width (1.5m Body-Guard system) 1.885m to 2.885m
- Width (3m Body-Guard system) 3.165m to 4.165m
- Fixed adjustable extender (up to) 500mm
- Material High grade aluminium
- Leg Length 2.34m to 2.9m
- Demarcation rail (4 per kit) 1500mm sections

SYSTEM MUST BE TIED IN TO THE BUILDING WHEN IN USE

*Photographs for illustration purposes only.*



**easi-dec®**

A KEE SAFETY COMPANY