Uniclass L2123 + L7315		EPIC J3413
CI/SfB	(52.5)	

## **ACO Technologies plc**







Surface water management systems for permanent way and rail infrastructure





### Introduction to the ACO Group

Throughout the world ACO branded drainage and surface water management systems are recognised for their innovative design, high quality manufacture, environmental excellence and industry leading performance.

Today the ACO Group has a research and production base that reaches across four continents. This unmatched resource pioneers the development of solutions that are tailored to individual applications, meeting the need for high performance, sustainable products that deliver optimum value throughout their operational life.

### **ACO Technologies plc**

ACO operates as ACO Technologies plc in the United Kingdom. Founded over 25 years ago, the company has grown quickly on a reputation for design innovation and customer service.


There are now four specialist divisions within ACO Technologies that serve every sector of the construction industry, providing solutions for applications as diverse as rail, highways, airports, landscaping, retail, distribution centres and environmentally sensitive projects.



To help architects, designers and contractors meet the legal requirements that now tightly control the way surface water is managed; ACO has created its unique 'Surface Water Management Cycle' – Collect, Clean, Hold, Release – the four core processes now required for the complete and sustainable management of surface water drainage.

For more information please visit www. aco.co.uk.





## **Contents**

Constructing a sustainable rail future	Page 4
ACO product offering	Page 5
ACO design support	Page 6
TRAM AND LIGHT RAIL	
ACO Water Management Systems for light rail	
ACO TramDrain 200	Page 7
ACO Grooved RailDrain Boxes	Page 8
ACO V100G Tram	Page 8
ACO Derailment containment	Page 9
ACO Cable Troughs	Page 9
Light rail case study – Manchester Metrolink	Page 10
HEAVY RAIL, STATIONS AND SURROUNDING INFRASTRUCT	URE
ACO Water Management Systems for heavy rail	
ACO MultiDrain MD	Page 11
ACO ParkDrain	Page 12
ACO S Range	Page 12
ACO RoadDrain	Page 13
ACO KerbDrain	Page 13
ACO Qmax	Page 14
ACO Q-Ceptor	Page 14
ACO StormBrixx	Page 15
ACO Q-Brake Vortex	Page 15
ACO Building Drainage systems for heavy rail	
ACO Modular 125	Page 16
Heavy rail case study – East Midlands Parkway	Page 17
Link Up Certification	Page 18
Link Up Certification	Page 19



### Visit the ACO website

For the latest information on surface water management, visit the ACO website www.aco.co.uk

The ACO website is a new online destination for anyone looking for information on this subject and provides detailed product information, design support, technical downloads and much more.

### Constructing a sustainable rail future

A safe, reliable and efficient mixed-rail network will play a vital role in the United Kingdom's economic future.

Recognising that rail strategy needs to focus on balancing the differing needs of network users on both local and national levels, the Government has set long-term objectives in three key areas: increasing the capacity of the railway, delivering a quality service for passengers, and fulfilling rail's environmental potential.

Pressure brought by the increasing volumes of passengers and freight being carried each year highlights the need for significant investment. Meeting the Government's targets will require the upgrade of much of the track and terminal infrastructure in order to secure its sustainable future.

# The role of surface water management

The need to effectively remove surface water from all passenger, vehicle and rolling stock environments is essential if the network is to operate safely and reliably.

Modern surface water management systems that exploit the latest hydraulic mapping design techniques provide 'surface to outlet' solutions that maintain optimum performance throughout their operational life.



#### **Introduction to ACO Technologies**

For over 60 years, ACO has been pioneering the management of surface water through the development of innovative drainage solutions and support services. This depth of understanding is reflected in the diversity and quality of our products, which cover every aspect of the water management cycle and set the benchmark for performance.

A major part of ACO's portfolio includes manufacturing specialist water management systems for the UK national rail and light rail networks. ACO's high performance product ranges have been used extensively throughout the modern railway environment to overcome significant design challenges and to satisfy demanding aesthetic requirements.

ACO has designed many systems for use at both regional and national level including Ebbsfleet International station, Transport for London and DLR extension upgrades and Manchester Metrolink.

The extensive product range ensures a wide variety of applications can be catered for including the track slab, platforms, station buildings and infrastructure, parking areas, maintenance and storage depots.



If you need help with specification, design or installation, or just wish to learn more about this and other Surface Water Management products from ACO, contact our free, no obligation ACO Design Services Team who can provide advice and dedicated design support for your project – 01462 816666 or visit www.aco.co.uk.

#### **ACO Water Management**

The ACO Water Management range provides architects, specifiers and engineers with a complete package of integrated systems suitable for use across the entire spectrum of civil engineering projects.

The ACO Water Management range boasts the widest range of channel collection systems, innovative and award-winning attenuation and infiltration systems, as well as a range of hydrocarbon separators and flow control systems.

Visit www.aco.co.uk

#### **ACO Building Drainage**

ACO Building Drainage is a new concept within ACO Technologies and specialises in the development of corrosion resistant drainage systems for internal and external applications.

The technical expertise, global resources and fabrication capacity within our division make it possible for architects, engineers and contractors to realise the highest quality and value when selecting from our standard products, or, when using our bespoke design services.

Visit www.acobd.co.uk

# **London Underground Fire Performance Assessment**

ACO MultiDrain™ MD channels manufactured from Vienite concrete have been assessed and tested in accordance with fire performance test criteria as given in London Underground Standard 1-085 'Fire Safety Performance of Materials'. This covers three aspects, combustibility, smoke emission and toxic fume emission. ACO Vienite Polymer Concrete was assessed for fire performance according to these criteria and approved for use in below ground locations.



#### **Assurance**

As a major supplier to the rail sector, ACO understands the importance of delivering high performance, sustainable drainage systems. Investment in leading technology, design expertise and rigorous quality management ensure absolute consistency and levels of assurance. Every system ACO manufactures is tested beyond the requirements of the toughest performance standards.



ACO is a registered supplier through Link-up. Link-up is the UK rail industry supplier qualification scheme, providing a single common registration, qualification and audit

process for suppliers to the UK rail industry.

#### Use of sustainable materials

ACO's continuous investment in research and development and the drive for innovation push forward the development of new sustainable products and materials. Where possible ACO aims to incorporate as much recycled material or waste material as is practicable during the manufacturing process.

Recently, the company has developed Vienite\*, a genuine breakthrough in the development of recycled materials. Vienite\* utilises high levels of post consumer recycled waste without compromising strength or performance characteristics. At the end of a product's operational life, Vienite\* can be collected, processed and returned to production as a raw material.

The high strength resin-based material is four times stronger than traditional concrete with a compressive strength in excess of 90 N/mm² and a flexural strength in excess 22 N/mm².

The material has a low water absorption rate which makes it resistant to freeze thaw attack. Vienite® is also more resistant to chemical and mould attack than traditional polymer concrete.



The nature of this material makes it possible to develop complex shapes and products that can not be achieve with many other materials.

### ACO design support

Surface water management system design can often be a complex task. Success in combining products and processes requires a thorough understanding of how these different elements work together.

ACO has two design services teams who are able to work closely with you through the entire design process to ensure accurate and cost effective product selection is made.

All services are free of charge and without obligation. Here are the services we offer:

- Whole system design, from collection to the attenuation of surface water
- Specification, design and installation advice
- Hydraulic calculations & AutoCAD detailing
- · Parts schedules



#### **Design Services Team**

#### ACO Water Management:

Tel: 01462 816666 Fax: 01462 851081 Email: technical@aco.co.uk

#### ACO Building Drainage:

Tel: 01462 816666 Fax: 01462 851490

Email: abdtechnical@aco.co.uk



#### ACO bespoke design service

The specialist design team can cater for bespoke designs or modify traditional ACO ranges to ensure that high performance drainage systems can be supplied to complex or difficult installations.

By exploiting both ACO's UK and European design and manufacturing capabilities, ACO can deliver cost effective bespoke products to meet any specification. Using the latest 3D drawing software, initial ideas can be modelled and transformed into concept design proposals in a short space of time. ACO's engineers are able to offer detailed advice on every aspect of the product design, operational performance, and installation.

Modifications to both UK and European standard product ranges can also be catered for.

## ACO Water Management Systems for light rail

The majority of Light Rail Transit systems form part of local, multi-modal transport networks that need to balance a wide range of varying operational demands in order to provide a reliable service.

Managing surface water run-off in this environment where pedestrians, cyclists, passenger and commercial vehicle traffic overlaps with the light rail infrastructure requires a specialist approach. ACO Water Management's dedicated light rail product range has been developed to meet the very specific requirements of this application and has the capability to be adapted to the individual needs of any project.

A brief overview of the ACO Water Management systems suitable for tram and light rail applications is provided below. For more detailed information regarding any of these systems please visit www.aco. co.uk or email technologies@aco.co.uk

#### **ACO TRAMDRAIN 200**


ACO TramDrain 200 is a high capacity drainage system designed to provide efficient surface water drainage to the grooved rail profile and to the 4-Foot and 6-Foot sections of the track slab.

The ACO TramDrain 200 assembly is 260mm wide by 400mm deep, and is designed to suit a wide range of rail profiles and varying track configurations.



ACO TramDrain 200 is manufactured from Vienite®, ACO's sustainable high strength material. The material does not absorb water therefore does not conduct electricity and will provide protection against stray current.

System maintenance is simplified by using ACO TramDrain 200 rodding access units.



#### Key benefits

- Provides positive surface water drainage for tram and light rail schemes
- Range of accessories including rail connectors and under-rail drainage culverts
- Integral gratings eliminate the risk of loss, vandalism or vibration



#### Project references

► Greater Manchester Metrolink ► Luas, Dublin's light rail tram system

#### ACO GROOVED RAILDRAIN

The grooved rail is an area which can be difficult to access and maintain on many tram and light rail applications. ACO's Grooved RailDrain Boxes offer a solution to this problem by providing simple and effective drainage of this area.

The one-piece units can be installed against coated or uncoated rail sections providing a dedicated drainage point to intercept water from the groove in the rail profile. The boxes can also be installed continuously to avoid interference with other services contained within the track slab.



ACO Grooved RailDrain boxes are manufactured from Vienite\*, ACO's sustainable high strength material. The material does not conduct electricity and will provide protection against stray current.

Reversible ductile iron access cover for maintenance and cleaning



Two depths available to suit Ri59/Ri60 and R41GP track profiles

Each unit is 500mm in length

Optional outlet positions for connection to underground drainage

Fully certified to Load Class D 400 BS EN 1433:2002

#### Key benefits

- Suitable for use in twin running track sections (tram/vehicular traffic)
- Reduces the chance of water leakage onto the truck bed
- Designed for use with encapsulated or non-encapsulated rail sections



#### Project references

► Nottingham Express Transit (NET) ► Greater Manchester Metrolink


#### ACO V100G TRAM

ACO V100G Tram is a shallow channel drainage system designed to drain the 4-Foot and the grooved rail profile. The flexibility of the system ensures the unit can be easily integrated into second stage track slab construction.



ACO V100G is supplied as standard with ductile edge rails for improved strength and ACO Drainlock\* slotted ductile iron gratings certified to Load Class E 600.

In addition, a further assembly is now available with black composite Heelguard gratings certified to Load Class C 250. This channel assembly is suitable for a lighter duty application and can also help reduce the possibility of stray current.



#### Key benefits

- Provides effective surface water drainage of the rail track
- Can easily be integrated into second stage track slab construction
- Designed for use with encapsulated or nonencapsulated rail sections



#### Project references

▶ Blackpool tram network ▶ Edinburgh Trams

#### ACO DERAILMENT CONTAINMENT


ACO Derailment containment channels provide effective surface drainage whilst acting as a wheel trap in the event of a derailment.

The system is installed parallel with the tram track and is fitted with frangible gratings which will collapse if struck by a tram wheel.



The channel drainage unit is fitted with composite edge rails and Heelguard™ composite gratings. Both features offer excellent protection against stray current.

A channel assembly with outlet points is also available for connection to underground drainage.



#### Key benefits

- · Provides effective surface water drainage and derailment containment system
- Suitable for use on bridges, flyovers and anywhere an extra degree of protection is required against de-railed trams
- · Gratings collapse if struck by wheel



#### Project references

► Luas, Dublin's light rail tram system ► Nottingham Express Transit (NET)

#### **ACO CABLE TROUGHS**

ACO Cable Troughs provide a secure shallow trench for cable management.

The Trough features easy access for maintenance and servicing operations whilst provided a protective cover for the cabling from the external environment.



Manufactured from Vienite, ACO's sustainable high strength material, the cable trough is resistant to mould, frost and UV attack.

The smooth finish on the internal surfaces of the cable trough has also been found to cause less damage to the cable sheath when drawn through the trough compared to some alternatives.



Internal dimensions are identical to traditional concrete cable troughs

> Smooth internal finish helps to reduce cable damage

### Key benefits

- · Provide secure protection for above ground cables and services
- · Material resistant to mould, frost, and UV attack

Greater Manchester's Metrolink is one of the most successful light rail systems in the UK. Owned by GMPTE, the Greater Manchester Passenger Transport Executive, its three lines operate a fleet of more than 32 trams that carry over 20 million passengers every year between Bury, Altrincham and Eccles and Manchester city centre. The Bury and Altrincham lines opened in 1992 followed by the Eccles line in 2000 creating a network of 37 stops covering 37km.



#### Project:

Greater Manchester Metrolink

#### Client: GMPTF

#### **Brief:**

Provide effective water management system at busy intersection to prevent standing water damaging track bed and rails



Situated within Metrolink's City Zone, the Shudehill stop is one of the key points on the network providing a link between the trams and the city's bus routes. It lies on a major road intersection at the foot of a steep incline – a feature that gave rise to drainage issues during periods of prolonged rainfall, when surface water running off the surrounding roads would build up and cause problems with standing water around the tracks.

To solve the problem Metrolink's engineers were able to exploit the specialised drainage systems developed by ACO Technic which had proven their effectiveness on tracks with a similar profile used on light rail networks in Nottingham and Dublin.

By using the ACO Grooved RailDrain, ACO TramDrain 200 and ACO \$100, the team was able to realise a remedial works scheme for Shudehill that would allow a new localised surface water management system to be introduced without the need to undertake wider and more substantial works across the surrounding roads. Over the section of track that needed attention, this would greatly reduce the project timeframe and lessen the impact on other road users.

ACO Grooved RailDrain boxes were installed in 16 locations where the existing surface water drainage was insufficient to remove run-off from the road surface itself. The units were installed immediately adjacent to these low points in the track to ensure quick removal of all water intercepted by the rail groove.

In locations where the capacity of the existing surface water drainage needed to be increased, runs of ACO TramDrain 200, which are installed perpendicular to the rails and extend across both up and down tracks, have been installed. Further capacity has also been added in the critical section where the tracks run alongside the Shudehill platform with a single 100 metre run of \$100 channel.



# ACO Water Management Systems for heavy rail

Carrying ever increasing numbers of passengers faster and more efficiently requires high performance Heavy Rail infrastructure that is capable of meeting the demands of this intense and pressurised environment. The effective removal of surface water from exposed station platforms, car parks, and walkways ensures passengers can move quickly, freely and, above all, safely in any transfer area.

ACO's leading range of surface water management systems are designed using the latest materials and dynamic hydraulic modelling techniques. Any Heavy Rail system that is developed in partnership with ACO forms part of an integrated Sustainable Drainage Solution that considers every aspect of the surface water management cycle: from the four key design stages – collect, clean, hold, release – through to the four core service principles – train, design support, care – which ensure that the system maintains optimum performance throughout its operational life.

A brief overview of the ACO Water Management systems suitable for heavy rail applications is provided below. For more detailed information regarding any of these systems please visit www.

#### ACO MULTIDRAIN MD

ACO MultiDrain MD is a high quality general purpose channel drainage system designed to provide quick and efficient removal of surface water.

The main channel unit is manufactured from Vienite\*, ACO's sustainable high strength material and is available in three channel widths. A choice of constant and sloping channels is also offered to suit varying hydraulic designs.



To provide a wider choice of products, an alternative base is available. ACO MultiDrain PPD is a high strength channel drainage system manufactured from recycled polypropylene.

The channel forms the main component of the system which can then be combined with one of the many different grating styles to complement the surround environment. ACO MultiDrain MD gratings are fitted with ACO Drainlock, a bar-less locking device which reduces the risk of blockages and improves hydraulic capacity. An additional security locking system is also available.

\*Not suitable for carriageways of roads.

Wide variety of slotted, intercept, perforated and Brickslot gratings and solid covers available in ductile iron, composite and galvanised and stainless steel



ACO MultiDrain MD system is available in three channel widths; 100mm, 150mm and 200mm

Manufactured from Vienite®, ACO's sustainable high strength material



#### Applications:

- Station platforms
- Building thresholds
- Piazzas and forecourts
- Taxi drop-off points
- Car parking



#### Project references

- ► DLR extension upgrades (West India Quay, Mudchute, Crossharbour, South Quay)
- ► East London Line (Haggerston, Hoxton and Dalston stations)

#### ACO MultiDrain MD - London Underground Fire Performance Assessment

ACO MultiDrain MD channels manufactured from Vienite concrete have been assessed and tested in accordance with fire performance test criteria as given in London Underground Standard 1-085 'Fire Safety Performance of Materials'.

This covers three aspects, combustibility, smoke emission and toxic fume emission. ACO Vienite Polymer Concrete was assessed for fire performance according to these criteria and approved for use in below ground locations.

#### ACO PARKDRAIN

ACO ParkDrain® is a one-piece drainage system suitable for use in pedestrian areas, car parks and hard landscaped areas.



Its one-piece design with integral grating means that the drainage system is not vulnerable to vandalism or loosening, and the Heelguard™ 8mm inlet slot makes the system ideal for pedestrian traffic.

Access for cleaning is provided by rodding or sump units to ensure simple maintenance. A range of accessories for connection to the underground drainage is available.



#### Applications:

- · Station platforms
- · Piazzas and forecourts
- · Car parking

### ACO S RANGE

ACO S Range is a robust channel drainage system designed to provide efficient removal of surface water from applications that are subject to heavy wheel loads.



To support a wide variety of catchment depths, hydraulic capacities and applications, the system is available in four channel widths and is offered in constant and sloping depths for optimum performance and system design.

The ACO S100 system has a choice of slotted, heelguard, intercept and solid cover ductile iron gratings to ensure a wide variety of applications is catered for. ACO S150, S200 and S300 channels are supplied complete with slotted ductile iron gratings.



#### Applications:

- Bus pick-up and drop-off zones
- · Coach parking
- · Car parking
- · Maintenance depots
- · Loading and container yards



#### Project references

- Ebbsfleet International
- East London line (Wapping, Shadwell and Dalston stations)



Manufactured from Vienite®, ACO's sustainable high strength material, the one-piece system is strong and robust in design, and the absence of separate gratings improves the strength of the system and offers superb protection against vandalism or breakages.

ACO RoadDrain® is available in two channel widths: 100mm and 200mm, and has a variety of depths and accessories to suit many design schemes.



#### Applications:

 Station road infrastructure

channel design

scheme design

- · Maintenance depots
- · Loading and container yards



#### Project references

► Ebbsfleet International

#### **ACO KERBDRAIN**

ACO KerbDrain® is an award-winning one-piece combined kerb and drainage system which can be used widely across the rail environment.



Manufactured from Vienite®, ACO's sustainable high strength material, the system conforms to BS EN 1433:2002 Load Class D 400 and carries the BSI Kitemark.

A full range of accessories is available including perforated and flush centre stones, drop kerb assemblies, radius unit and bus stop kerbs to complement many applications.

The system is available in a range of depths; 225mm, 280mm, 305mm and 480mm





and splay profiles

Complies with IAN 117/08 and is Kitemarked to BS EN 1433:2002 D400 for use on trunk roads



#### **Applications:**

- · Pick-up and drop-off zones for all types of vehicles
- · Buses and coach parking
- · Car parking
- · Surrounding road infrastructure



### Project references



ACO Qmax® is specifically designed to form an integral part of any modern, sustainable surface water management solution. The system provides all necessary components to deliver conveyance, attenuation and source control for effective SuDS drainage schemes and designs.

The ACO Qmax® system has five channel sizes and rail designs ensuring greater system flexibility for engineers and designers to optimise scheme hydraulics.

Patented 'Pavement beam' feature permits continuous flow of concrete through the product, for strong and cost effective installation

CE marked and fully certified to BS EN 1433:2002 for all Load Classes up to and including F 900



Lightweight material and design for easy manual handling and fast installation

> One piece design provides minimal connection joints and simple installation

Levelling feet for ease of installation and stability

Simple push fit channel connection detail for easy edge rail alignment

Integrated channel seal to enable watertight connection

Channels can be cut at pre-determined lengths to suit application

Recycled MDPE construction provides tough, highly corrosion resistant structure



#### Applications:

- · Buses and coach parking
- · Car parking
- Maintenance depots
- · Loading and container yards



#### Project references

East Midlands Parkway

#### ACO Q-CEPTOR

ACO Q-Ceptor is an innovative range of bypass and full retention oil separators. Oil separators are installed on sites where there is a risk of accidental spillages or leaks of oil from vehicles, plant and machinery.



ACO Q-Ceptors work by separating oil contamination from water flows. Oil and silt are retained within the separator until they can be removed safely from the site, with the treated water being allowed to discharge.

Manufactured from polyethylene, the innovative single chamber design is extremely compact and robust offering significant advantages in installation and handling costs over traditional GRP products.

Full retention separators for peak flows from 3 to 10 l/s



Large diameter opening for easy

> High flow rate bypass separators for peak flows from

> > Class 1 and Class 2 oil separators

30 to 100 l/s

All environment agency compliant and certified to BS EN 858-1:2002 and BS EN 858-2:2003

#### Applications:

Compact design

- · Buses and coach parking
- · Car parking
- · Maintenance and refuelling areas
- · Freight hubs

· Loading and container vards


#### **ACO STORMBRIXX**

ACO StormBrixx is a unique and patented plastic geocellular stormwater management system. Designed for surface water infiltration and storage, its versatility allows it to be used in applications across all construction environments as a standalone solution or as part of an integrated sustainable drainage (SuDS) scheme.



The open cell structure permits completely free access for CCTV and jetting equipment which allows the whole system, including all the extremities, to be inspected and maintained from just a few access points.

ACO StormBrixx benefits from a patented cell brick and cross bonding feature which provides unparalleled stability in the construction of the tank.



#### Applications:

- · Car parking
- · Park n Ride schemes

#### Project references

► Three Bridges Railway Crawley

Remote access cable for

#### **ACO Q-BRAKE VORTEX**

The design of a vortex flow control is based on the fluid mechanics principle of the forced vortex, which permits flow regulation without any moving parts.

ACO Q-Brake Vortex utilises the upstream head and discharge to generate a vortex within the structure of the unit.



ACO Q-Brake Vortex is fitted with an integral bypass door which can be opened in the event of a blockage to drain the unit. A stainless steel wire attached to the bypass door is run to cover level and provides control of the bypass door. Once the water level within the manhole subsides the blockage can be cleared.



#### Applications:

- · Buses and coach parking
- · Car parking
- · Maintenance and refuelling areas
- · Freight hubs
- · Loading and container yards



#### Project references

Three Bridges Railway Crawley

# ACO Building Drainage Systems for heavy rail

Our built environment is becoming ever more complex. Applications are becoming more sophisticated and the increasing pressure of regulations and standards make achieving design, performance and financial goals ever tougher.

ACO Building Drainage is a new concept within the ACO Group. Our mission: to eliminate design risk, to reduce installed and life cost and to deliver exceptional finish and performance in every product application.

For more detailed information regarding any of our services and products, please visit www.acobd.co.uk or email abdtechnical@aco.co.uk

#### ACO MODULAR 125

ACO Modular 125 is a highly durable channel drainage system for internal and external drainage applications. Manufactured in corrosion resistant 304/316 grade austenitic stainless steel that is fully pickle passivated, making the material suitable for rail applications that require a reliable, stylish, and long life performance in very demanding conditions.

ACO Modular 125 lightweight and durable channels sections are easy to install and minimise the risk to construction employees during the installation process. ACO can also provide a wide range of gratings compatible with the system with loading class A15 to C250, and when required will provide a unique grating security locks.





#### Key benefits

- · Corrosion resistant stainless steel providing long lasting durable systems
- · Shallow depth and Vee bottomed profile which improves hydraulic flow enabling self-cleansing
- · Aesthetically pleasing stylish designs complete with a wide range of heel friendly gratings



#### Project references

Docklands Light Railway



### East Midlands Parkway

East Midlands Parkway is the region's newest mainline station. Opened in 2009 on the Midland Main Line, it provides park and ride facilities for passengers on the routes from Leicester to Derby and Nottingham. Situated close to the M1, the station's location was carefully selected to encourage motorists to switch to more fuel-efficient rail transport, relieving pressure on the surrounding congested road network and delivering a net reduction in carbon emissions.



#### Project:

East Midlands Parkway

Network Rail / East Midlands Trains

#### Brief-

Provide effective water management to various areas across this new station development



Served by over 100 train services per day, the £25 million station is expecting to attract up to half a million passengers a year. Owned by Network Rail and operated by East Midlands Trains, it comprises four platforms, a step-freeaccess main station building with ticket office and secure parking for 850 vehicles.

In line with its green operational objectives. Network Rail wished, in its construction, to use new technologies wherever possible that would minimise the impact on the local environment. In partnership with main contractor, Birse Civils, it meant working with suppliers who were committed to using locallysourced and recycled materials.

ACO Water Management's selection was due to the versatility and breadth of its product range together with the strength of its environmental credentials both in manufacturing and distribution. The design team had also worked closely with Network Rail's engineers to show how, through ACO's Value Engineering process, a fully integrated surface water management system would reduce ground infrastructure, saving money and shortening installation time.

Three products have been used extensively across the key areas of the station: ACO Qmax® together with ACO KerbDrain® keep the car park clear of standing water; ACO KerbDrain® has been installed to remove run-off from the new station access road and used to create the bus and taxi pull-ins along the main entrance apron; and ACO MultiDrain™ provides drainage around the station perimeter and along the exposed passenger platforms.

To speed installation further, 1m long ACO KerbDrain® units have been used to complete longer runs. ACO KerbDrain® drop kerbs, rodding access units and shallow gullies have also been installed to provide step-free-access, to allow easy maintenance and to tie the runs into the main drain that discharges into the adjacent River Soar.

The composite grating used in all the ACO MultiDrain<sup>™</sup> runs complement both the glazed façade of the main station building and the non-slip textured surface finish of the platforms. Easily changed or removed for maintenance, the gratings use ACO's Drainlock™ bar-less locking system to prevent any vertical movement or unwanted access.





# Certificate of Registration

# Aco Technologies Plc

Supplier Number: 094698

are now fully registered as a supplier on Link-up



CLO Hours

Chris Hornung Chief Operating Officer Achilles Information Limited

#### Registration Expiry Date:19 July 2013

This is not a legal document and cannot be used as such.



#### **Achilles Information Limited**

7 Burnbank Business Park, Souterhead Road, Aberdeen, AB12 3LF, United Kingdom

T:+44 (0)1235 861118 E: link-up@achilles.com www.achilles.com





#### PRODUCT CODE SUMMARY

### LINK-UP QUALIFICATION SCHEME

### **Aco Technologies Plc**

#### 0303.1001.SMP Track Drainage - SMP

Scheme	Status	With Link-up Audit	Specialist Risk Based Assessment Only
National Rail	Scored Evaluation	No	N/A
Underground	Scored Evaluation	N/A	N/A

58004-18601/95589 18601 20 September 2012

# 0802.1010.SMP External Works (Drainage, Including Surface, Foul & Sewerage Treatment) - SMP $\,$

Scheme	Status	With Link-up Audit	Specialist Risk Based Assessment Only
National Rail	Scored Evaluation	No	N/A
Underground	Scored Evaluation	N/A	N/A

58004-18601/95589 18601 20 September 2012

#### 1204.1003.SMP Tunnel Drainage - SMP

Scheme	Status	With Link-up Audit	Specialist Risk Based Assessment Only
National Rail	Scored Evaluation	No	N/A
Underground	Scored Evaluation	N/A	N/A

58004-18601/95589 18601 20 September 2012

#### 1290.1001.SMP Materials & Parts (Civils) - SMP

Scheme	Status	With Link-up Audit	Specialist Risk Based Assessment Only
National Rail	Scored Evaluation	No	N/A
Underground	Scored Evaluation	N/A	N/A

58004-18601/95589 18601 20 September 2012

#### **ACO Technologies plc**

- ACO Water Management
  Civils + Infrastructure
  Urban + Landscape
- ACO Building Drainage
- ACO Sport
- ACO Wildlife

#### ACO Technologies plc

ACO Business Park, Hitchin Road, Shefford, Bedfordshire SG17 5TE

Tel: 01462 816666 Fax: 01462 815895

#### **ACO Water Management Contacts:**

e-mail Sales: customersupport@aco.co.uk e-mail Technical: technical@aco.co.uk

website: www.aco.co.uk

#### ACO Building Drainage Contacts:

e-mail Customer Enquiries: abdcommercial@aco.co.uk

e-mail Technical: abdtechnical@aco.co.uk

website: www.acobd.co.uk

The ACO Group: A strong family you can depend on.

© June 2013 ACO Technologies plc. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the Company. It is the customer's responsibility to ensure that each product is fit for its Intended purpose, and that the actual conditions of use are suitable. This brochure and any advice is provided by ACO Technologies plc (the Company) free of charge and accordingly on terms that no liability including liability for negligence will attach to the Company or its servants or agents arising out of or in connection with or in relation to this brochure or any such advice. Any goods supplied by the Company will be supplied solely upon its standard conditions of sale, copies of which are available on request. The Company's policy of consultance product development and improvement renders specifications liable to modification. Information provided in this brochure is therefore subject to change without prior notification.

#### ACO CARES ABOUT THE ENVIRONMENT

Printed on material approved by the Forest Stewardship Council (FSC) who provide a means of assuring that products come from responsibly managed forest.

















ISO 9001 FM 13502



ISO 14001 EMS 538781



OHSAS 18001 OHS 524145

