

BARRIER RANGE

HEAVY CONTRACT ENTRANCE CARPET SOLUTIONS

Description	Test Standard	Sheet	Tiles	Sheet	Sheet
Product Name		Dominator	Dominator	Trackmaster	Hercules
Fibre Type	-	100% Polypropylene	100% Polypropylene	100% Polypropylene	100% Polypropylene
Fibre Weight ($\pm 10\%$)	-	1500g/m ²	1500g/m ²	1250g/m ²	1400g/m ²
Total Weight ($\pm 10\%$)	-	2650g/m ²	4600g/m ²	2400g/m ²	2820g/m ²
Total Thickness ($\pm 10\%$)	-	10.5mm	11.5mm	11mm	10.5mm
Dimensions	-	2m x 12.5m	50 x 50cm	2m x 25m	2m x 25m
Backing Material	-	Rubber	Bitumen	Rubber	Rubber
Tiles per Box	-	-	12	-	-
Light Reflectance Value	BS 8493:2008	See Table	See Table	See Table	See Table
Static Loading	BS 4939/ISO 3416	Pass	Pass	Pass	Pass
Dynamic Loading	BS ISO 2094	Pass	Pass	Pass	Pass
Lisson Trettrad	BS EN 1963-A	Grade 1	Grade 1	Grade 1	Grade 1
Colour Fastness: Light	BS EN ISO 105-B02	Grade 6	Grade 6 (8 max.)	Grade 6	Grade 6
Colour Fastness: Shampoo	BS 1006-UK-T8	Grade 5	Grade 4/5	Grade 4/5	Grade 4/5
Colour Fastness: Rub	BS EN 105-X12	Grade 5	Grade 5	Grade 4/5	Grade 4/5
Colour Fastness: Water	BS EN 105-E01	Grade 5	Grade 5	Grade 5	Grade 5
Hot Metal Nut	BS 4790	Low radius char	Low radius char	Low radius char	Low radius char
Electrical Resistance	IBM / ICL Electrodes	Pass	Pass	Pass	Pass
Dimensional Stability to Heat	BS 4682 Part 3	Tested	Tested	Tested	Tested
Dimensional Stability to Water	BS 4682 Part 4	Tested	Tested	Tested	Tested
Dimensional Stability Ambient	BS 4682 Part 2	Tested	Tested	Tested	Tested
Methenamine Tablet	ASTM D2859	Tested	Tested	Tested	Tested
Thermal Resistance (Tog)	BS 4745	2.22	-	-	-
Body Voltage	BS EN 1815	Tested	Tested	Tested	Tested
Spike Resistance	BS 7044 Part 4:1991	Pass	Pass	-	-

All weights and thickness quoted $\pm 10\%$. Due to batch variation, production material may vary in colour from samples shown in this folder.

Installation

All aspects of sub floor preparation and flooring installation must be carried out in accordance with BS 5325:2001 Code of Practice for Installation of Textile Floorcoverings. Sheet and tile carpet should be fully adhered with approved adhesives. All products should be allowed to acclimatise for 24 hours at room temperature (15-20°C) prior to installation. We recommend that the tiles are installed by turning alternate tiles through 90° to obtain a chequerboard pattern. During both planning and installation, consideration must be given to batch matching and pile direction. For further information contact the Rawson Carpet Solutions Sales Team.

Maintenance

A regular maintenance programme is always recommended. Use a suction type of vacuum cleaner for daily maintenance. Periodic shampooing and cleaning by a professional cleaning company should be carried out to keep floorcoverings in good condition. Do not use petrol or similar solvents on these products. With tile products, traffic paths can be avoided by interchanging tiles as necessary.

Environmental Information

- Rawson products achieve either A or A+ across BREEAM defined building regulations. For specific rating, please refer to www.breem.co.uk
- All Rawson carpet sheet and tile products are made in the UK.
- Wherever possible, raw materials are sourced in the UK.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.
- Whenever possible manufacturing waste is recycled.



Recommended
Tile Layout



RAWSON
CARPET SOLUTIONS

Castle Bank Mills, Portobello Road, Wakefield, West Yorkshire, WF1 5PS

Tel: 01924 382860 Fax: 01924 366204

Email: rcsales@werawson.co.uk

www.rawsoncarpetsolutions.co.uk

