



Sovereign

the gold standard in building products

Technical
Data Sheet

173

Sovereign All Weather Sealant

A Universal Co-Polymer Sealant that can be used for a wide range of sealing and weatherproofing applications.



Product Code

Black: **30806026**

Clear: **30806027**

Description

A Universal Co-Polymer Sealant that can be used for a wide range of sealing and weatherproofing applications around the home and in industry. Can be applied in wet weather.

CE Marked.

Form Supplied: Thixotropic Paste

Pack Size: 300 ml Cartridges

Colour Range: Black and clear

Properties

Provides a superior adhesion to most surfaces such as glass, glazed surfaces, aluminium, lead and zinc. Can be used in building, glazing, roofing and ductwork applications and for emergency repairs in wet weather. Over paintable with most paints and stains.

Preparation

Surfaces must be dry, clean, and free of dust, rust, grease, oil and other contaminants. Porous or unsound surfaces should be primed before application. Deep joints must have the depth reduced to 50% of the width using either Sovereign Expanding Foam or joint backer rod.

Usage

Gun the sealant firmly into the joint to provide a solid fill. Sealant can be smoothed using a slightly wetted stick (soapy solution will make tooling easier) or spatula. Tooling must be carried out within 5 minutes of application. Never use fingers to tool down silicone sealants.



Sovereign All Weather Sealant

Technical
Data Sheet

173

CLEAN UP

Clean tools immediately after use with GripFilt Wipes.

LIMITATIONS

Do not use in joints subject to movement in excess of 15%. Do not use with aquariums. On surfaces containing bitumen or asphalt, discolouration can occur. It is user's responsibility to determine suitability.

DRYING TIME

Sovereign All Weather Sealant has a skinning time of 5 minutes and will be tack free in 10 minutes. Full cure is reached at a rate of 0.5 - 1.0 mm per 24 hours under ideal conditions.

COVERAGE

12 running metres for a 5 x 5 mm bead.

Storage: Between 5°C - 30°C.

Shelf Life: 12 months unopened.

GENERAL SAFETY PRECAUTIONS

- ! Avoid skin and eye contact.
- ! Handle only when wearing protective clothing.
- ! Wash splashes from skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.
- ! Contains: n-Butyl acetate.
- ! Flammable liquid and vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



**Health & safety information
available on request**



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

