



Sovereign

the gold standard in building products

Technical
Data Sheet

61

Sovereign Path & Drive Sealer

Sovereign Path and Drive Sealer is a polymeric, clear sealer for external application.



Product Code

5 Litres: **30806278**

25 Litres: **30615277**

Description

Sovereign Path and Drive Sealer is a polymeric, clear sealer for application to exterior paving bricks, concrete, flagstones and porous tiles. Sovereign Path and Drive Sealer is a solvent system to allow deep penetration into the substrate.

Form Supplied: Liquid ready to use

Pack Sizes: 5 Litre and 25 Litres

Colour Range: Clear

Contains: Polymer and water repellents in Solvent

Properties

Path and Drive Sealer penetrates the surface and forms an invisible barrier to prevent staining caused by oils, dirt and water.

Preparation

Ensure all surfaces are clean, dry and free from grease, oil, dust or loose material that may interfere with the penetration of the sealer to be applied. Dirt, moss and lichen and other loose material can be removed by using Sovereign Masonry Sterilising Wash. Allow to dry thoroughly (at least 3 days after rain or cleaning). Surfaces must be dry to allow maximum penetration.



Sovereign Path & Drive Sealer

Technical
Data Sheet

61

USAGE

Shake well before use. For best results apply using a long pile roller and a roller tray or an emulsion brush. Ensure the surface is evenly coated and that the coating does not 'pool' in surface depressions. Brush well into the surface re-distributing any excess material.

For best results two coats of Sovereign Path and Drive Sealer should be applied, allowing 3-4 hours between coats. (Two coats are normally recommended but open, porous substrates could benefit from an extra coat to ensure maximum protection).

Sovereign Path and Drive Sealer contains a solvented product and must be allowed to dry thoroughly. Under normal conditions the treated surface will allow foot traffic after 4 hours. Leave for 24 hours before allowing vehicle trafficking. However, in cold, damp conditions drying, re-coating and in-service times will be extended.

GENERAL

PRECAUTIONS

Do not apply to damp surfaces, in conditions of high humidity or when rain is forecast. Protect from rain until dry. Care should be taken to ensure that Sovereign Path and Drive Sealer has cured thoroughly prior to parking vehicles on the driveway.

Note: Sovereign Path and Drive Sealer will not totally prevent reoccurrence of efflorescence. It will also not give a glossy finish. A glossy surface after application is only caused by over application or application on to a very low porosity substrate. Re-treatment will usually require only a single coat.

Spillages and drips of oils, petrol and hydraulic fluid etc, must be cleaned away as soon as possible.

CLEAN UP

Use white spirit / brush cleaner for cleaning tools and equipment.

LIMITATIONS

Do not apply to non-porous surfaces (e.g. quarry tiles, certain types of dense brick, etc.).

COVERAGE

Typically 6 m²/litre but will vary according to the porosity and topography of the substrate.

Storage: Between 5°C - 30°C.

Shelf Life: Minimum of 12 months when unopened

HEALTH & SAFETY

- ! Avoid skin and eye contact.
- ! Handle only when wearing protective clothing.
- ! Wash splashes from skin with soap and water, flush eyes with copious amounts of water and seek medical attention if irritation persists.



Health & safety information
available on request



Important Disclaimer

The information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that product, techniques and codes of practice are under constant review and changes occur without notice. Please ensure you have the latest updated information.



Sovereign
the gold standard in building products

Sovereign Support: 01229 870800 | www.sovchem.co.uk

FIND US HERE

