

Wall Panels



The Marlbrook® Range from AKW



Create your ideal space with a quick and stylish transformation

AKW is the market leader in accessible showering solutions in the UK.

We have an excellent heritage of more than 30 years of providing bathroom products which enhance people's safety in the bathroom and create accessible, easy to maintain solutions. We are passionate about ensuring that people can live in stylish, aspirational surroundings and this is particularly relevant for modern bathrooms.

We are now manufacturing our own wall panels to be able to offer our customers a full bathroom solution which does not compromise on style. The wall panels we offer fulfil all the requirements of tiles but with none of the stress. This product is so versatile it will fit beautifully into any bathroom, whatever the preferred style, leaving you able to design and create your ideal space.



WALL PANELS

Benefits of Wall Panels



Cost saving

On average it'll be 25% cheaper than installing tiles, mainly because AKW panels do not require a specialist tiler. As an addition to this, panels last much longer than tiles further saving on the full life cost.



No more mould

We're fed up of grout, it takes a long time to apply, it's a nightmare to clean and after a while it just goes mouldy. There's no grout used with our panels, so that means no more mould.



Extra time

AKW panels are so much quicker to fit than tiles that it'll save you money and the effort of getting someone in for long periods of time. Of course it also means that you'll be without your bathroom for a lot less time, which is great.



An end to tough cleaning

No need to scrub tiles or clean grout, wall panels can be easily and hygienically cleaned with warm soapy water.



Watertight guarantee

The AKW panel system is guaranteed to remain watertight and waterproof for fifteen years from date of purchase if installed correctly.

WALL PANELS

AKW Marlbrook Wall Panels

Duo Finish Wall Panels

Finished on both sides of the panel, to allow either side to be used as the face. This is more forgiving if scuffs occur on site, reducing the chance of needing replacements.

Minimal time and equipment required for installation

Quick and easy to fit with the items in your toolbox. No specialist skills or equipment needed to install.

High coverage, 1220mm x 2440mm surface area

Panels cover a large area and can be fitted directly over tiles, making installations less labour intensive. A large 1800mm x 900mm shower area would require just three panels and relevant extrusions.

High Pressure Laminate faces on WPS plywood substrate

High Pressure Laminate (HPL) is then bonded to both faces of the plywood to give a completely waterproof surface.

Structural grade material

Wall panels are made of structural materials, which means fixtures such as shower seats and grab rails can be fitted securely, without impacting weight loading.



Multiple extrusions available

A wide variety of extrusions are available, offering a solution to any installation challenge you may face.

Hard wearing, easy clean laminate surface

High pressure laminate surface is resistant to scuffs and easy to clean.



Marlbrook product range

AKW Marlbrook wall panels offer a stylish waterproof finish to your bathroom with a scratch resistant finish and luxurious feel.

Wall panels allow you to create a sophisticated bathroom area, quickly and efficiently.

AKWs straight edge wall panels come in one size 1200mm wide and can be trimmed to suit any bathroom.

Profiles are available in white or silver.





WALL PANELS


Colour options



Black Marble 27390BMR

Quartz 27390QRZ





Savannah 27390SVH

Gloss White 27390WHT

Specification:


Size: 1220mm x 2440mm x 12mm


Finishes: White Gloss, Savannah, Quartz, Black Marble

Full range of End caps, Externals, H-Sections, Internals and Bottom profiles are available to suit this range. The profile lengths are 2440mm and available in white PVC and satin anodised aluminium.

EDGE FRAMING PROFILES


How Profiles are used






Wall Panel to Tile Profiles

For wet room floors In wet areas we do not recommend that the panels are fitted right down to the floor. In such areas the distance between the floor and the bottom of the panels should be at least 75mm. The preferred option with the panels sitting on a bottom profile.



Wall Panel to Vinyl floor profile

For wet room floors in wet areas we do not recommend that the panels are fitted right down to the floor. In such areas the distance between the floor and the bottom of the panels should be at least 75mm. The preferred option with the panels sitting on a bottom profile with the flooring coved up the wall.




Wall Panel to Tray -Transeal Profile


If the panels are being fitted above a bath or a shower tray, a "Transeal" sealing profile is advised, as the bath or shower trays are liable to be flexible if plastic, or uneven if ceramic.


Using a bottom seal will ensure that the silicone will always provide a barrier against water ingress that may have a detrimental effect on the panels at some future date.






















Please Note: Drawings are for illustration purposes only and are not representative of our product

AKW

MARLBROOKS WALL PANELS

Technical Specification

+ Material	WBP Plywood
+ Method of manufacture	High pressure laminate bonding
+ Height	2440mm
+ Width	1220mm
+ Weight	22.5Kg
+ Thickness	12mm
+ Trimmable	Yes
+ Warranty	15 Years
+ Click and lock	No

Fitting Wall Panels

AKW panels are designed so that any competent tradesperson should be able to fit them. Comprehensive fitting instructions are provided with every order and can also be downloaded directly from our web site at www.akw-ltd.co.uk.

1. Tools required

No specialist equipment is required, just normal woodworking tools. Such as a wood saw, screwdriver, sealant gun, spirit level, tape measure, drill, etc.

2. Cutting the panels

When using a fine toothed handsaw, make sure the decorative side is faced upwards to ensure the best results. When cutting holes for valves and pipes, a minimum of 2mm clearance should be left all the way around. This clearance must then be filled with silicone sealant.

3. Preparing the walls

AKW panels can be fixed to most surfaces including concrete, chipboard and existing tiles. It is important to ensure the walls are even and sound to ensure for the best possible fixing. The walls must be clean and dry when adhesive is to be used to ensure the most effective bond.

Note the primary fixing method used should always be mechanical, i.e. by the use of screws and raw plugs depending on the structure of the substrate.

4. Other Fittings

Shower attachments and other fittings can be secured directly to AKW panels using the appropriate fixings.

Product Codes Laminated Square Edge Wallboard 2440mm x 1220mm Gloss White 27390WHT Laminated Square Edge Wallboard 2440mm x 1220mm Savannah 27390SVH Laminate Square Edge Wallboard 2440mm x 1220mm Black Marble 27390BMR Laminate Square Edge Wallboard 2440mm x 1220mm Quartz 27390QRZ Wallboard Edging Strip Alum 2440mm 27683 Wallboard External Corner Radiused Alum 2440mm 27680 Wallboard 'H' Section Alum 2440mm 27685 Wallboard Internal Corner Alum 2440mm 27682 Wallboard Bottom to Skirting Alum 3000mm 27684 Wallboard Square Edging Strip PVC 2440mm 27694 Wallboard Radiused External Corner PVC 2440mm 27691 Wallboard 'H' section PVC 2440mm 27686 Wallboard Internal Corner PVC 2440mm 27692 Wallboard Bottom onto Vinyl PVC 3000mm 27690 Wallboard Bottom onto Tray PVC 3000mm 27689 Wallboard Edging Strip With Radius Alum 2440mm 27681 27688 Wallboard Internal Corner Alum & PVC Assembly Wallboard 'H' section Alum & PVC Assembly 27687 Wallboard Radiused Edging Strip PVC 2440mm 27693



Orders & Quotes

01905 823 299 orders@akw-ltd.co.uk

General Enquiries

01905 823 298 sales@akw-ltd.co.uk

Technical Enquiries

01905 560 219 technicalenquiries@akw-ltd.co.uk

AKW

Pointon Way, Hampton Lovett Droitwich Spa, WR9 0LR

www.akw-ltd.co.uk orders.akw-ltd.co.uk







