

Envirolastic[™] 940 DTM

High build, single coat, direct-to-metal polyaspartic urethane coating

The long term durability of the single coat application is comparable to a two coat epoxy primer and urethane topcoat system.

Dry to handle within two hours, Envirolastic[™] 940 DTM provides a fast return to service. The fast cure enables an accelerated throughput in shop applications, improving productivity and lowering costs overall. Envirolastic[™] 940 DTM can be applied in temperatures as low as 2°C extending the painting season in-shop or on-site.



The Envirolastic[™] 940 DTM polyaspartic technology offers protection of steel in corrosive environments up to C3 as defined in ISO 12944. For aggressive corrosion environments, C4 and C5 (ISO12944), Envirolastic[™] 940 DTM can be applied over an approved anti-corrosive epoxy primer.

High performance, excellent colour and gloss retention coupled with long term durability make Envirolastic™ 940 DTM suitable for commercial and architectural applications improving the overall aesthetics and extending the life of the building.

Features

- Single coat, direct-to-metal application.
- Fast cure chemistry.
- Low temperature application.
- High resistance to corrosion.

Benefits

- Saves application time and labour cost versus a two coat system of primer and topcoat. Comparable performance to a two coat system for corrosion protection and colour/gloss retention.
- Improves the dry to handle times and overall productivity.
- Extends painting schedule.
- Extends the life of the asset.

Key Applications

Envirolastic[™] 940 DTM applies direct-to-metal over blasted or galvanized steel. It is dry to touch in one hour, preventing unwanted debris pick up. Envirolastic[™] 940 DTM replaces two coat intermediate/topcoat systems for:

- High performance architectural applications.
- Steel fabrication.
- Steel structures.
- Oil and gas (onshore structures, tank exteriors etc.).
- ldeal for new construction or maintenance applications.



The Sherwin-Williams Difference

By putting our customers first, we know that the innovation, imagination, research and development we put into each and every product will be worth it. You are at the centre of our thinking wherever we operate around the world across five continents whether it is advice, specification or on-site inspection. You are the reason we exist. This is the Sherwin-Williams difference.



To learn more, contact us

Europe, Middle East & Africa: +44 (0)1204 521771

North America: +1 800 524 5979

Asia: +8 621 5158 7798 sales.uk@sherwin.com

www.sherwin-williams.com/protectiveEMEA