



Eaves comb filler

Designed to prevent entry of birds and vermin below profiled roof tiles

Use

- At the eaves of a roof
- Below profiled roof tiles to exclude birds and vermin

Features and benefits

- Effective, quick and easy to fit
- Durable and totally resistant to decay
- Supplied in convenient 1m lengths

Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

Material and colour choice

- Injection moulded in polypropylene
- Available in black only


Bill of quantity

G20 Carpentry/Timber Framing/First Fixing


Clause

900^ EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk
- Product Reference: 1136
- Type: Eaves Comb Filler (1000mm)
- Colour:Black



1136



Installation advice

- Fit on the top of the fascia board before tiles are laid. The comb must angle outwards away from the roof
- Secure with clout nails through the holes provided
- Bed bottom row of tiles on to the comb

How to order

- Measure the overall length of the eaves and divide by 1m to determine the number of combs required

Product codes

6m eaves vent pack

Depth of comb	Length	Product code
55mm	1m	1136