

THERMO-LOC

FRSTOP

Fire-Rated Cavity Stop Sock

Fire-rated thermal and acoustic cavity stop sock

Available in smaller quantities for convenience



Also available to suit cavity widths of up to 300mm



Use

- To restrict the spread of flames within external masonry
- To further minimise the effect of flanking noise pollution at wall junctions

Features and Benefits

- FRstop cavity stop socks are lengths of low resin, non-combustible, rockfibre mineral wool sleeved in 35 micron polythene for on-site weather protection
- 1 hour fire integrity and minimum 15 minute insulation
- Polythene encapsulated cavity stop sock
- Available in standard widths of 50, 75, 85, 90, 100, 115, 125 and 150mm
- Also available to suit cavity widths of up to 300mm
- Special cavity widths are available on request up to 300mm
- Meets the requirements of the Robust Detail, Approved Document B and NHBC Standards
- Boxed in smaller quantities for convenience

Quality

- Satisfies all NHBC requirements
- Complies with all relevant Building Regulations
- Meets all relevant British Standards
- LABC registered detail
- Independently tested by Warrington Fire

Material and Colour Choice

- Manufactured using Rockfibre mineral wool
- Rockfibre uses no CFC's, HCFC's in the manufacturing process
- Thermal conductivity of Rockfibre insulation 0.037w/mK

Installation Advice

- FRstop is designed to friction fit within the cavity and is easily installed both vertically and horizontally into the cavity during construction. Care should be taken to ensure butt joints are closely fitted and the cavity sock fully fills the cavity.
- This method should be incorporated with a preformed horizontal cavity tray (refer to Technical Department for appropriate type) and proprietary wall weep vents (1143) at 900mm centres to prevent water ingress from bridging the cavity.

Product Codes

Product Code	To Suit Cavity Width	Dimensions	Fire Integrity	Lead Time
FRSTOP50	50mm	65 x 65 x 1200mm	1 hour	Next working day
FRSTOP75	75mm	85 x 85 x 1200mm	1 hour	Next working day
FRSTOP85	85mm	100 x 85 x 1200mm	1 hour	Next working day
FRSTOP90	90mm	100 x 85 x 1200mm	1 hour	Next working day
FRSTOP100	100mm	110 x 100 x 1200mm	1 hour	Next working day
FRSTOP115	115mm	130 x 100 x 1200mm	1 hour	Next working day
FRSTOP125	125mm	140 x 100 x 1200mm	1 hour	Next working day
FRSTOP150	150mm	160 x 120 x 1200mm	1 hour	Next working day

NB. Non standard cavity sizes up to 300mm are available to special order

