



Innovation | Manufacturer | Design | Solution

Features

- Specifically designed for sump pump applications
- O Provides power to a system when the primary source of power is unavailable
- O The PowerMaxx is capable of running both primary and secondary pumps
- O Virtually inaudible
- O Easy to understand LCD screen
- O Easy Installation
- O The PowerMaxx is free standing and can be installed in any dry ventilated area
- The PowerMaxx unit is fitted in a series between the spur and the pump; no additional electrical spurs are required
- The PowerMaxx can operate as a stand-alone unit or can be used in conjunction with AlertMaxx2
- Can be used as a direct replacement for previous versions

Benefits

- Produces electricity during blackout situation (saving irreparable damage)
- O Offers uninterruptible power supply
- During power failure the PowerMaxx will automatically run the sump pump system, ensuring your structure is kept dry and the pumps running
- The PowerMaxx is able to run 1 x V3 ground water pump without mains power for up to 4 days (depending on number of cycles/hr)
- The PowerMaxx is able to sit in standby mode for 10 days
- O Internal trickle charger keeps the unit fully charged so ready whenever there is power failure
- O The PowerMaxx will automatically recharge when mains power returns

BATTERY BACK-UP



PEACE OF MIND IS A STANDARD



Features

- The Hi-PowerMaxx provides battery backup for larger pumps such as the V4, V6, Foul and Bespoke
- O Provides power to a system when the primary source of power is unavailable
- O The Hi-PowerMaxx is capable of running both primary and secondary pumps
- O Virtually inaudible and easy installation
- O The Hi-PowerMaxx is free standing and can be installed in any dry ventilated area
- The Hi-PowerMaxx unit is fitted in a series between the spur and the pump; no additional electrical spurs are required
- O The Hi-PowerMaxx can operate as a stand-alone unit or can be used in conjunction with the AlertMaxx2
- The Hi-PowerMaxx can also be used as a direct replacement for previous versions

Benefits

- O Produces electricity during blackout situation (saving irreparable damage)
- O Offers uninterruptible power supply
- The Hi-PowerMaxx provides standby mode for 50 days
- The Hi-PowerMaxx provides 13 days pump time based on 1 cycle/hr of a V6 pump
- An electric charger keeps the Hi-Power
 Maxx battery-backup fully charged so it'll be ready at any time
- Internal trickle charger keeps the unit fully charged so ready whenever there is power failure
- The Hi-PowerMaxx will automatically recharge when mains power returns

Our Battery Backups are leading the industry in performance, hours of additional protection are offered to your property from water damage in the event of power failure.

	POWERMAXX	HI-POWERMAXX
Size (without cable glands)	155mm x 425mm x 300mm	475mm x 425mm x 300mm
Weight (without batteries installed)	6.5kg	15.5kg
Weight (with batteries installed)	19.5kg	80.5kg
Mains supply	200-250V AC (50Hz)	200-250V AC (50Hz)
Internal batteries	24V – 5 x 22 Ah Total = 100 Ah	24V – 5 x 22 Ah Total = 100 Ah
Power (standby)	<3W	<3W
Peak Power Handling	600W P1	2000W P1
Power (charging)	55W	55W
Visual display	Red, Blue, Green LED	Red, Blue, Green LED
Operating temperature	5-35°C	5-35°C
Approximate installation time	30 minutes	30 minutes
Warranty	2 years	2 years
Pump Type	V3	V4/V6/D10

Delta Membrane Systems Ltd, Delta House, Merlin Way, North Weald, Epping, Essex, CM16 6HR